

TOLANI MARITIME INSTITUTE'S JOURNAL OF MARITIME FUNDAMENTALS AND APPLIED RESEARCH



ISSN: 3049-3226 (Print)



TOLANI MARITIME INSTITUTE

Talegaon - Chakan Road,
Induri, Pune - 410507,
Maharashtra, India

✉ jmfar@tmi.tolani.edu

🌐 <https://tmi.tolani.edu>

SUBJECTS COVERED

Marine Engineering and Nautical Science

Marine propulsion systems and machinery.
Ship design and hydrodynamics.
Marine refrigeration and air-conditioning systems.
Maritime safety and environmental sustainability.
Navigation systems and nautical charting technologies.
Marine fuel systems and alternative energy sources.
Marine maintenance, diagnostics, and fault detection.

Mechanical Engineering

Thermodynamics and heat transfer applications in maritime systems.
Design and analysis of mechanical components in marine systems.
Fluid dynamics and turbulence modeling for marine applications.
Vibrations and noise control in marine structures.

Electrical and Electronics Engineering

Shipboard electrical systems and power distribution.
Automation and control systems for marine equipment.
Sensors and instrumentation in maritime applications.
Marine communication systems and electronic navigation aids.

Computer Sciences

Artificial intelligence and machine learning in marine engineering.
Simulation and modeling for ship operations and safety.
Cybersecurity in maritime networks.
Data analytics and IoT for smart shipping.

Communication Sciences

Maritime communication protocols and satellite technologies.
Real-time data transmission and remote monitoring in marine systems.
Human factors and effective communication in maritime operations.

Management Sciences

Maritime logistics and supply chain management.
Risk management in shipping and offshore operations.
Sustainability and green shipping practices.
Regulatory frameworks and compliance in the maritime industry.
Maritime Law, Policy, and Human Rights at Sea

General Applied Research

Case studies on complex problem-solving in marine contexts.
Multidisciplinary approaches to maritime innovation.
Emerging technologies and their applications in marine and allied fields.
Research methodologies and experimental techniques in marine sciences.



Journal Title	<i>Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research</i>
Printer and Publisher	<i>Tolani Maritime Institute, Talegaon - Chakan Road, Induri, Pune - 410507, Maharashtra, India</i>
Printing Press	<i>Learning Resource Centre Tolani Maritime Institute, Talegaon - Chakan Road, Induri, Pune - 410507, Maharashtra, India</i>
Place of Publication	<i>Tolani Maritime Institute, Talegaon - Chakan Road, Induri, Pune - 410507, Maharashtra, India</i>
Editor's Name	<i>Dr. Sanjeet Kanungo</i>
Owner's Name	<i>Tolani Maritime Institute</i>
Periodicity of the Publication	<i>Annual</i>
First Edition	<i>January 2024</i>
Language	<i>English</i>



ABOUT THE JOURNAL

Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research (TMI-JMFAR) is a multidisciplinary journal dedicated to advancing knowledge and fostering innovation in fields related to Marine Engineering, Nautical Science, and allied disciplines. This esteemed journal aims to publish high-quality research encompassing a diverse range of topics, including but not limited to Mechanical Engineering, Electrical and Electronics Engineering, Computer Sciences, Communication Sciences, and Management Sciences. The journal invites contributions that are theoretical, experimental, and numerical in nature, addressing both fundamental and applied aspects of these domains.

TMI-JMFAR emphasizes solving complex real-life problems, making it an ideal platform for researchers, professionals, and academics who aim to make a tangible impact in their respective fields. The scope extends to publishing case studies and literature reviews, alongside original research, thereby providing a holistic approach to knowledge dissemination. This multidisciplinary perspective ensures the journal remains relevant to a wide audience across various technical and management fields.

One of the unique strengths of TMI-JMFAR lies in its rigorous peer review process, which adheres to international standards of scientific publishing. This ensures the credibility, integrity, and quality of every article published. The editorial board, comprising experts from diverse backgrounds, is committed to maintaining the journal's reputation as a hub for excellence in scientific research.

The journal also serves as a platform for the exchange of ideas and information, encouraging cross-disciplinary collaboration and dialogue. Researchers are encouraged to submit work that offers innovative solutions, insights into complex systems, or advances in theoretical understanding. By promoting research that bridges the gap between theory and practice, TMI-JMFAR contributes to the advancement of science and engineering in industries critical to global progress, such as maritime operations and beyond.

With a focus on addressing the challenges of the modern world, TMI-JMFAR invites submissions that explore emerging technologies, sustainable practices, and methodologies that improve operational efficiency and safety. By facilitating the dissemination of cutting-edge research, the journal seeks to inspire and guide future advancements in the fields it represents.



EDITORIAL BOARD

Dr. Rajesh Kumar Bhatia

Associate Dean Research
Computer Science & Engineering,
Punjab Government Engineering
College (Deemed to be University),
Chandigarh - 160012
Email: rbhatia@pec.edu.in

Dr. Ajay Pandit Bhattu

Associate Professor
Mechanical Engineering, College of
Engineering Pune - 411005
Email:
bhattuaajay.mech@coeptech.ac.in

Dr. S. R. Patil

Professor and Head E & TC
Bharati Vidyapeeth's College of
Engineering for Women, Pune -
411043
Email:
sandip.patil@bharatividyapeeth.edu

Dr. Ankur Miglani

Associate Professor
Indian Institute of Technology
Indore, Indore – 453552.
Email: amiglani@iiti.ac.in

Dr. Nitin Garg

Senior Hydrodynamics Engineer
REGENT Craft Inc., 200 Callahan
Rd, North Kingstown, RI 02852,
United States
Email: gargn@umich.edu

Dr. Shivank Shrivastava

CFD Scientist
Bentley Systems, Boston/USA.
Email:
shivank.srivastava@bentley.com

Prof. Shailendra Kumar

Vice Principal- Marine Engineering
Tolani Maritime Institute, Pune
Email: shailendrak@tmi.tolani.edu

Capt. Indranath Banerji

Vice Principal- Nautical Technology
Tolani Maritime Institute, Pune
Email: indranathb@tmi.tolani.edu

Prof. Sukanta Dasgupta

Vice Principal- Students Affairs &
Alumni
Tolani Maritime Institute, Pune
Email: sukantad@tmi.tolani.edu

ADVISORY BOARD

Dr. Abhijeet Singh

Executive Director IPA,
Ministry of Ports, Shipping &
Waterways,
Government of India.
Email: abhijitsingh.email@gmail.com

Dr. R. Vijayakumar,

Associate Professor,
Department of Ocean Engineering,
Indian Institute of Technology
Madras.
Email: vijay2028@iitm.ac.in

Cdr. (Retd), Kamal Kanagat,

General Manager,
L&T Shipbuilding,
Chennai.
Kamal.Kanagat@larsentoubro.com

Dr. Inderveer Solanki,

Chief Consultant, Inland Waterways
Authority of India,
Ministry of Shipping,
Govt. of India
Email: ivsolanki@yahoo.co.in

Capt. Manoj Hirakane,

Sr. Vice Principal,
Tolani Maritime Institute, Pune
Email: manojh@tmi.tolani.edu

Capt M. Sai Raj,

Director,
Synergy Navis Marine Pte Ltd.
Email: sairaj.m@synergynavis.com

Mr. Chitta Dash,

Senior Business Leader (retired),
Lloyds Register.
Email: chittadash1958@gmail.com

Mr. Naveen Mathew,

Chief Investigator of Accidents
(acting),
Manager Surface Investigations
(Marine and Rail investigations),
Wellington, New Zealand.
Email: naveen.mathew@taic.org

ASSOCIATE EDITORS

Dr. N. K. Joshi,

Department of Mechanical
Engineering
Tolani Maritime Institute,
Pune 410507
Email: narasinhaj@tmi.tolani.edu

Dr. Dhiren Dave,

Department of Electrical
Engineering
Tolani Maritime Institute,
Pune 410507
Email: dhirend@tmi.tolani.edu

Dr. Anjali Deshpande,

Department of Applied Science
Tolani Maritime Institute,
Pune 410507
Email: anjalid@tmi.tolani.edu



ASSOCIATE EDITORS

Dr. Sagar Mane Deshmukh,
Department of Mechanical Engineering
Tolani Maritime Institute,
Pune 410507
Email: sagarm@tmi.tolani.edu

Dr. Shrikant Madiwale,
Department of Mechanical Engineering
Tolani Maritime Institute, Pune 410507
Email: shrikantm@tmi.tolani.edu

Dr. Mithul Naidu
Department of Mechanical Engineering
Tolani Maritime Institute,
Pune 410507
Email: mithuln@tmi.tolani.edu

Dr. Ajaj Attar,
Department of Mechanical Engineering
Tolani Maritime Institute,
Pune 410507
Email: ajaja@tmi.tolani.edu

Dr. Manoj Kumar Kar,
Department of Electrical Engineering
Tolani Maritime Institute,
Pune 410507
Email: manojkumark@tmi.tolani.edu

Dr. Jitendra Singh Pal
Department of Marine Engineering
Tolani Maritime Institute,
Pune 410507
Email: jitendrap@tmi.tolani.edu

Dr. Dewali Chatterjee
Maritime Management
Tolani Maritime Institute,
Pune 410507
Email: dewalic@tmi.tolani.edu

TECHNICAL TEAM

Dr. Rahul Viswe
Learning Resource Centre
Tolani Maritime Institute,
Pune 410507
Email: rahulv@tmi.tolani.edu

Dr. Dhanshri Shinde
Department of Applied Sciences
Tolani Maritime Institute,
Pune 410507
Email: dhanshris@tmi.tolani.edu

Mr. Rahul Kale
Department of Applied Sciences
Tolani Maritime Institute,
Pune 410507
Email: rahulk@tmi.tolani.edu

Mrs. Swati Bhise
Human Resources
Tolani Maritime Institute,
Pune 410507
Email: swatib@tmi.tolani.edu

Mr. Prateek Tiwari
Department of Marine Engineering
Tolani Maritime Institute,
Pune 410507
Email: prateekt@tmi.tolani.edu

Mr. Vijaysingh Chavan
Department of Mechanical
Engineering
Tolani Maritime Institute,
Pune 410507
Email: vijayc@tmi.tolani.edu

DESIGNED BY

Dr. Rahul Viswe
Learning Resource Centre
Tolani Maritime Institute,
Email: rahulv@tmi.tolani.edu

FORMAT OF PUBLICATION

Guidelines for paper submission

- Enter manuscript in MS word, Times New Roman, main text - font 10, subtitle - font 10 and the main title font 16, with main text in the single line spacing double column on A4 sheet.
- Provide every article with an abstract not exceeding 250 words.
- Provide 4-6 keywords.
- Organize paper in smooth flow of title, subtitle and sub-sub title.
- Keep length of the paper to the limit of 12 pages approx.
- Provide 1 inch margin on all sides of the paper
- Provide figures, drawings and graphs in black color on white back ground.
- Submit figures, drawings and graphs in JPEG format with 300 minimum resolution
- Number the figures and tables as per standard practice.
- Provide mathematical equations and functions in suitable equation editor
- List the references at the end of the article with serial number.
- A declaration to the effect that the work is original and has not copied or published earlier elsewhere - needs to be submitted along with the paper.
- On behalf of all the co-authors, the corresponding author shall bear the full responsibility for submission and shall provide his/her full address, contact number and email.
- Follow the suggested order for manuscripts: (In some cases all the points may not come in order as suggested)

Template to Write the Article

- Title, Authors, Affiliations
- Abstract
- Keywords (provide 4-6 keywords) Introduction
- Main text (may include information based / knowledge based/ theory based/experimental based/model based method)
- Data Collection/Data Analysis (if any)
- Result and Discussion (If any)
- Conclusion References



Technical articles discussing various aspects of science and technology including innovations in the marine field, original research work, experimental investigations with results, industrial practices, case studies are invited for publication. The paper may be please be mailed to jmfar@tmi.tolani.edu

EDITOR'S - MESSAGE

Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research (TMI-JMFAR) is a multidisciplinary journal that focuses on research related to Marine Engineering and Nautical Science and other disciplines like Mechanical Engineering, Electrical and Electronics Engineering, Computer Sciences, Communication Sciences, and Management Sciences, etc. The scope of the journal covers theoretical, experimental, and numerical research related to basic and applied problems, case studies, and literature reviews from various disciplines mentioned above. We encourage contributions that will be helpful in solving real-life problems which are complex in nature.

TMI-JMFAR also provides a platform for exchanging information on various topics mentioned above. The journal's editorial board members strongly believe in the quality of the research articles, and hence the process of selection of the articles includes a science-driven approach and double-blind peer review process, which conforms to the strict international procedures and editorial standards expected by the scientific community.

I encourage engineering students, research scholars, academicians, industrialists, scientists to contribute their research through publication in TMI-JMFAR. All papers receiving a high degree of enthusiasm in the peer-review process will find a home in TMI-JMFAR. Therefore, we are committed to publishing all discoveries, methods, resources, and reviews that significantly advance the Marine Engineering and Nautical Sciences field.

On behalf of the TMI-JMFAR team, I would like to mention my sincere thanks to the authors, editors, reviewers, technical publication committee members, and bodies who have indirectly supported to achieve the required quality of the research articles and hence the journal. It is with profound pleasure, humility and anticipation that we celebrate the launch of the **Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research (TMI-JMFAR)** with this inaugural issue.

At last, I welcome you to contribute to TMI-JMFAR. I see a bright future for TMI-JMFAR with the support of authors, reviewers, and editors. I ensure to serve science and the scientific community even better in the future. Ultimately, we will improve more lives and, consequently, our communities

We would be delighted to hear about your suggestions for improving the quality of TMI-JMFAR on

Thank you. We hope you will find TMI-JMFAR informative and interesting.

Dr. Sanjeet Kanungo
Editor



TECHNICAL TEAM's - MESSAGE

We are pleased to present the first issue of **Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research (TMI-JMFAR)**

Tolani Maritime Institute (TMI) has been successful year after year in imparting Marine Education at pre-sea and post sea level because of its strength of faculty members, other resource persons in the organization and the facilities available for the research and industrial project work. TMI has created its benchmark in the Marine Education area.

Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research (TMI-JMFAR) provides the platform for the readers, students, academicians, research scholars, industrialists, scientists (authors) to take up the activity of writing and publishing scholarly articles in varied fields of Science, Technology and Management. The TMI-JMFAR Vol. III, Issue I is dedicated to all those who have contributed directly/indirectly in keeping the light of knowledge on.

We are sure that the issue of the journal will keep interest alive of the readers and writers. Enjoy Reading and Writing!!

Technical Team

**Tolani Maritime Institute,
Talegaon - Chakan Road, Induri,
Pune - 410507
Maharashtra, India**



CONTENTS

SR.NO	TITLE	PAGE NO.
Marine Engineering and Nautical Science (MENS)		
1	Decentralized Distributed Generation for Clean Energy Transition: Achieving Cost-Effective Rural Electrification in Jharkhand Dr. CMA Abhijit Garai	1
2	Navigating the Future – Blockchain, AI, Data Analytics, and Digital Transformation in the Shipping Industry Dr. S. Gopinath, Leenacharan SS	6
3	Smart, Sustainable, and Resilient: The Next Frontier in Maritime Supply Chain Management Sudarshani Patil, Wallace Jacob, Vijaysingh Chavan, Swati Bhise	11
4	Microfluidic Lab-On-Chip Systems for Onboard Detection of Contaminants in Marine Heavy Fuel Oil Using Laminar Flow and AI-Based Analysis Parth Sareen, Dibyajyoti Rano, Mohit Parihariya, Rishi Kumar	20
Mechanical Engineering (MECH)		
5	Microchannel Cooling Concept And Recent Advances Dr. Vaibhav Bansode, Prof. Sachin S. Yevale	25
6	Thermal Enhancement and Reduced Maintenance in Shell-and-Tube Heat Exchanger Tubes Parth Sareen, Dibyajyoti Rano, Mohit Parihariya, Rishi Kumar	31



SR.NO	TITLE	PAGE NO.
Electrical and Electronics Engineering (EE)		
7	Hybrid Marine Energy Harvesting Hull Parth Sareen, Dibyajyoti Rano, Mohit Parihariya, Rishi Kumar	42
Computer Sciences (CS)		
8	Implementation of Automatic Traffic Sign Detection Using CNN Algorithm Yuvraj G. Nikam, Rahul P. More, Rahul H. Bhole	48
9	Use of Generative Artificial Intelligence in Marine Applications: Trends, Methodologies, and Global Implementation Reshma Mane Deshmukh	53
Communication Sciences (COMM)		
10	Reforming (or Romancing) the Future – Is Education the Same as Schooling Dr. S. Gopinath, Riya Sharma	58
Management Sciences (MS)		
11	Implication of SWOT Analysis in Handicraft Industry & its Marketing Strategies Vishwajeet Singh, Shreya Kanade, Dhruv Dhawalskar, Dr. Dewali Chatterjee	62
12	An analysis of key dimensions of logistics service quality in the shipping industry Dr. K.Kaleeswaran, Mr Abhishek Pandey	65



SR.NO	TITLE	PAGE NO.
Management Sciences (MS)		
13	Standardization Vs. Specialization: A Comparative Review of BBA Programs in India Manoj S. Jagnade, Nandini Pawar	70
14	Green Finance and The Sustainable Development Goals Krati Jain	80
15	Market Research Is Critical For Framing Contemporary Business Strategy Dr. Dewali Chatterjee	85
General Applied Sciences (GAR)		
16	Data-Driven Water Quality Assessment Using Machine Learning and Water Quality Index Sahadev M. Jadhav	88
17	Municipal Solid Waste Dryer: Turning India's Wet Waste Introduction to High Quality RDF Fuel Aditya Gupta	93

A REPORT OF DECENTRALISED DISTRIBUTED GENERATION (DDG) FOR CLEAN ENERGY TRANSITION FOR ACHIEVING COST-EFFECTIVE RURAL ELECTRIFICATION IN JHARKHAND

Dr. CMA Abhijit Garai

Sr. Manager (Finance),

DamodarValley Corporation(DVC)

Email:abhijitgarai@yahoo.co.in / abhijit.garai@dvc.gov.in

Abstract: Energy is one of the key drivers of development and access to clean, safe and affordable sources of energy are considered as instrumental to stimulate economic, social and physical development. Availability of energy/power facilitates effective and efficient delivery of most basic services such as safe drinking water, public lighting, health care, education, etc. Besides, it also enables better standards of household living and fueling economic and income generation activities. It has usually been observed that a high correlation exists between consumption of electricity (energy) and improvements in the Human Development Index (HDI), especially at low levels of HDI. Lack of access to clean and efficient energy sources has thus been proved as one of the significant barriers to alleviation of poverty. India, despite the unprecedented pace of addition in the generation capacity over the Plan period, continues to have very low levels of energy consumption. The per capita energy consumption in India remains well below the world averages. This low level of energy availability and consumption tends to affect the poorest the most. While 16 % of the global population are residing in India, its share of global energy consumption is a paltry 4.2 %. Similarly, India's per capita electricity consumption of around 734 kWh is way below the global average of 2,782 kWh and China's 2,471 kWh. In India, rural per capita consumption of electricity is only 8kWh per month compared to 24 kWh in urban areas. Indian economy has traditionally been characterized as an agrarian economy with majority of its population living in the rural areas and are dependent on their farm land to earn their livelihood. These areas often do not have access to energy resources for livelihood expansion like power for irrigation, cold storage or processing and for normal day-to-day activities and are instead dependent on traditional and unclean sources of energy like woody biomass, dung cakes, kerosene, etc. As a result, the opportunities for productivity enhancements and value addition get limited by the lack of modern and efficient energy services. In this paper, the present scenario of rural electrification in India is taken into account. Basically, the electrification in this country is facing a lot of problem and is a growing matter of concern for all. This paper explores the potential of decentralized distributed generation (DDG) to facilitate a clean energy transition and provide cost-effective rural electrification in Jharkhand, India. With a focus on addressing energy, poverty and enhancing access to reliable electricity in remote and tribal areas, the study evaluates the deployment of renewable energy solutions such as solar micro grids and solar home systems. It discusses the benefits of DDG in reducing dependency on unreliable grid connections while

promoting energy independence and resilience. The Jharkhand State Solar Policy 2022 has set a cumulative target of 4,000 MW for green energy. The development in production is not reaching the one who need them. Department of Finance Also taking into picture the present sources of energy it is difficult to make the electricity available to the people belonging to rural areas who don't have much source of income. To overcome this drawback, we can utilize renewable sources of energy which is easily available and accessible. Also harvesting this will not cost much except the initial cost of setting up the device to utilize this type of energy. Many projects have been initiated by the government of India to provide subsidy and equipment like solar lantern and solar cooker etc. to the rural population but this didn't turn out to be effective as the follow could not be done by the people to maintain the devices. This can be overcome by implementing off-grid projects which can be initiated at small levels so that people don't have burden to maintain them and it even don't have any adverse effect to environment or society. The present study analyses the emerging issues of electrification infrastructure in rural India.

Keywords: Microchannel heat sink, Electronic cooling, Thermal management, Heat transfer, Microscale fluidics

I. INTRODUCTION

Energy is the lifeline of modern infrastructure & development, performing a fundamental role in all aspects of life like households, agriculture, health, education, and entertainment. Traditionally, electricity has been generated in large, centralized thermal power plants located near coal belt areas, using fossil fuels. These plants distribute electricity through massive transmission networks. However, fossil fuel-based energy sets environmental risks and fails to reach remote areas.

In India the village is said to be electrified if electricity is used in inhabited locality within the revenue boundary of the village for any reason what-so-ever. An interesting but sad fact is that only 44% of rural household of India has access to electricity. 7 out of 29 states have more than 70% of rural household without access to electricity. The expansion of electricity services and electrification are vital to both the economic and social development of India. However, the current state of electricity services in most of the states of India indicate signs of crisis and are with severe

shortcomings in many areas: a) Limited access to electricity for poor (rural / urban) b) Generation capacity unable to meet peak demand c) Supply reliability, in terms of predictability of outages and quality of power. The Electricity supply across India lacks quality and quantity with an extensive shortage in supply, a poor record for outages, high levels of transmission and distribution (T&D) losses and an overall need for extended and improved infrastructure. A considerable amount of electricity generated is wasted due to transmission and distribution inefficiencies and power theft. But such problems cannot be a good reason to keep more than of India's population from getting access to electricity.

Indian Govt. has initiated a major programme of grid extension and strengthening of the rural electricity infrastructure under the Rajiv Gandhi Grameen Vidyutikaran Yojana (RGGVY) (GoI 2005). The Indian Govt. recently outlined an ambitious plan of electrification through solar energy to 400 million people who don't have access to it.

To address these challenges, the 'Power for All' scheme was launched in 2014, aiming to ensure a 24-hour power supply for everyone. Despite this, many remote areas in India still lack access to electricity due to geographical obstacles and inadequate transmission networks. DDG offers a promising solution for India. DDG involves generating electricity from small-scale power sources located close to where it is needed, rather than relying on large, centralized power plants. The primary goal is to produce power at or near the point of consumption, reducing the need for long-distance transmission and distribution.

Background of Studies: As of March 2019, approximately 36.7 million people were living in Jharkhand. The state possesses more than 40% of India's natural resources. Jharkhand was among the leading states to sign the India government's MOU for the '24x7 Power for All' initiative (Deen Dayal Upadhyaya Gram Jyoti Yojana, 2015-16), which expected to ensure a continuous power supply throughout the state, including rural areas. The initiative aimed to provide continuous power supply across the state, including rural areas. Despite these efforts, a 2020 study by the Initiative for Sustainable Energy Policy (ISEP) indicated that around 13% of rural homes in Jharkhand remained without electrical energy [2]. The issue was particularly acute in tribal areas that are geographically isolate and economically disadvantaged. The rural population faced challenges in affording electricity due to restricted income and a lack of alternative living opportunities. The quality of electricity supply was also a concern, with unreliable service and frequent voltage fluctuations, which reduced the willingness of rural households to pay for electricity. There is a pressing need for clean energy solutions to improve not only electricity access and reliability but also to create alternative livelihood opportunities in rural communities. DDG is identified as a promising approach for electrifying rural and remote areas in Jharkhand. It offers a way to reach all parts of the state effectively, addressing the existing challenges in conventional grid-based electricity distribution. Decentralized energy solutions, such as solar micro grids or mini-hydro power, could help achieve sustainable and affordable electrification, making a significant impact on rural development.

Rural Electrification in India: The need for extension of the electricity system to rural areas was felt quite early, just after the independence of the country. Rural Electrification programme in India was launched with two distinct dimensions i.e. (1) Village Electrification. (2) Irrigation Pump set Energization. The former enhances consumer satisfaction and the latter optimizes crop yield. The area of focus was certainly maximizing farm output, which did result in the Green Revolution in the mid-1960s. Accordingly, the indicator of electrification was not based on the percentage of households or population with access to electricity but merely extension of electricity lines to a particular area. By this definition, almost 86% of the villages have access to electricity. In 2004, the programme has been refocused to provide electricity access to rural households. The First Five Year Plan emphasized to support for projects that ensure irrigation potential. During this period, only one in 200 villages was connected to grid supply across the country. The Second Plan named rural electrification as an area of special interest, and proposed to cover all towns with a population of 10,000 or more. Only 350 out of a total of 856 of were eventually electrified. The Third Plan for the first time raised the issue of efficiency in the sector. The REC (Rural Electrification Corporation) was created in 1969 with renewed focus on poverty alleviation. The target based approach of rural electrification was developed in the Fourth and Fifth Plan periods, with focus on pump set energization and guidelines for village grid connectivity for all villages with a population of at least 5000. The main sources of funding for current rural electrification programs are: (i) The Rural Electrification Corporation (ii) Plan allocation to the States. (iii) Funds support from Government as loan and grant (iv) Institutional financing bodies like Commercial Banks (v) International financing agencies like OECF, etc.

Power Generation of Jharkhand: The state receives abundant sunlight, with an average of 300 sunny days a year, and some areas can receive more than 4.5 to 5.5 kWh/m²/day of solar radiation. The Ministry of New and Renewable Energy (MNRE) estimates that state has the possibility to generate 18.18 GW of solar power [2]. As of June 24, the total installed power generation capacity in Jharkhand is 29.88 GW, including 189.82 MW from renewable energy sources and 191 MW from hydropower, which contribute to the state's green energy portfolio.




Fig. 1 Source of Electricity Production in Jharkhand [2]

The Jharkhand Solar Policy 2022 sets cumulative target of 4000 MW of Solar energy by 2027. The main objectives of the policy are to encourage solar energy for the progress of the rural economy and to empower livelihoods, offer financial and non-financial incentives, implement innovative practices, business strategies, bidding processes, and partnerships, and promote the development of local solar equipment manufacturing. The nodal agency of the Jharkhand Government for solar power development is the Jharkhand Renewable Energy Development Agency (JREDA)[1], while the Jharkhand State Electricity Regulatory Commission (JSERC) serves as the regulatory authority for state tariffs.

TABLE:1 JHARKHAND STATE SOLAR POWER POLICY 2022: CATEGORY WISE SOLAR PROJECT TARGET [2]

Project Categories	FY23 (MW)	FY24 (MW)	FY25 (MW)	FY26 (MW)	FY27 (MW)
Solar Parks	80	100	220	200	100
Non-Solar Parks	100	150	300	250	200
Floating Solar	100	200	250	200	150
Canal Top Solar	50	80	100	100	70
Rooftop Solar	30	50	60	60	50
Captive Solar	30	40	50	50	50
Solar Agriculture	20	30	65	65	70
Mini and Micro grids (Solar Villages)	10	20	25	25	30
Solar for livelihood	3	7	10	15	15
Solar Pump	20	20	25	25	30

Decentralized Distributed Generation (DDG): The small-scale generation of electricity close to the point of use, typically using renewable energy sources like solar, wind, biomass, or small hydroelectric systems. In Jharkhand, DDG is particularly relevant due to the state's significant rural population and scattered settlements, where extending the conventional electricity grid can be challenging and costly. As per the Solar Policy 2022, a target of 720 MW of installed distributed solar PV capacity has been set for the state during the operative period. This includes 250 MW for ground-mounted and solar rooftop projects less than 2 MW capacities, 220 MW for behind-the-meter captive solar projects and grid-connected group-captive solar initiatives, and 250 MW for agricultural feeder schemes under the PM KUSUM, Components A and C, which are considered as DDG schemes.

The DISCOM will initiate bidding for residential consumers under the MNRE subsidy program. Bids will be sought for capital expenditure (CAPEX), renewable energy service company (RESCO), and other innovative business models introduced by the DISCOM.

The tariff rate will be determined either through a rival bidding process or based on the pre-determined FiT authorised by the regulator. A PPA will be executed for captive projects. For electricity sales to the DISCOM, the rates will follow the tariff regulations set by JSERC. DISCOMs will purchase renewable energy generated from agricultural land at a pre-fixed levelized tariff with the tariff

for grid-connected agricultural pumps set according to the rates approved by JSERC.

Encouraging off grid solar power a cumulative target of 280 MW to establish model solar village and use of other solar appliances like solar water heaters, solar desalination systems, solar food dryers, solar thermal solutions for industrial processes, and solar space heating, among others. In the model solar village scheme its focus is the rural and tribal communities for improving their quality of life through distributed solar energy solutions. The state will support the full solarisation of 1,000 model villages and the generation of new jobs during the implementation period of this policy.

The 2021 mini-grids policy sets a cumulative target of 110 MW to address the irregular or absent electricity supply in rural villages. The policy aims to solarize various sectors, including health services, education, and farming, while encouraging the positive use of solar energy for employment applications.

II. RESEARCH OBJECTIVES

- To explore the potential of DDG as a strategy for providing clean and affordable energy access in rural areas of Jharkhand
- To promote, develop and finance viable decentralized power system organizations in cooperative, joint, private sector, panchayat and/or local bodies.
- To identify the challenges of rural electrification in India specially in Jharkhand area.
- To offer policy recommendations for scaling up DDG to meet the energy needs of remote communities while promoting sustainable development.

III. DISCUSSION

Strength of DDG:

- DDG will reduce transmission and distribution costs, allowing urban consumers to access power at generation cost.
- By decentralizing generation, the transmission and distribution losses will be reduced. According to JSERC, the state's T&D loss is 48.4%.
- DDG will reduce greenhouse gas emissions, addressing environmental concerns.
- It provides clean energy to rural and remote areas of the state.

Weakness of DDG:

- Significant investment is required for setting up decentralized units.
- Lack of maintenance may reduce generation efficiency and lead to the obsolescence of solar units.

Challenges for rural electrification of India: According to the current rate of electrification, nationally about 1 million new connections are added each year, whereas the annual growth in households is 1.85 million. Approximately 78 of

the 138 million rural households do not have access to electricity services. Lack of adequate infrastructure and properly trained manpower at the district level to carry out the electrification work also impedes the work. At the same time utilities either have limited equipment and operational resources like vehicles and block and tackle which need to be hired if a transformer has to be taken down. Most meter readers/ linesmen use bicycles. For moving equipment, the customers are usually asked to bear costs. Shortage of material is also a chronic problem and a bottleneck in the speedy implementation of RE programs. This shortage is usually of materials such as conductors, aluminums, cement, steel and insulators. It is only after the funds are received that the order for material is sent to the supplier. Release of funds through the central government, state government, utility headquarters route takes time, causing delay and implementation problems at the SDO level. Some of the challenges faced during rural electrification are listed below.

- a. Incomplete coverage
- b. Faulty definition/Incomplete Data
- c. Low demand, low consumption and shift in focus
- d. Long and cumbersome procedures
- e. Financially un-viable.
- f. Active Participation by Local Bodies
- g. Lack of measures for capacity enhancement
- h. Over-emphasis on grid rural electrification

Future of DDG: Solar panels, and other renewable energy technologies are becoming more affordable and efficient day by day, and this trend is expected to continue, leading to greater penetration of DDG, particularly in residential and commercial sectors. The integration of smart grid technologies will enable better management of DDG. The growth of micro-grid localized grids that can operate separately or in combination with the main grid will empower communities to generate and manage their energy supply.[4] Additionally, policies that promote net metering, feed-in tariffs, and tax incentives for renewable energy installations will accelerate the adoption of DDG.

Renewable Purchase Obligation (RPO): JREDA, the MOP, and the state government have launched several initiatives based on policies and incentives aimed at expanding the utilisation of renewable energy resources [3]. The JSERC has revised the RPO targets effective from April 1, 2024. According to the new regulations, DISCOMs must source 29.91% of their energy from environmentally friendly sources.

Major Rural Electrification Schemes in India:

Rural electrification is the backbone of rural economy and a basic input for rapid rural development. It is also the main infrastructure for ensuring speedy growth of the agriculture sector and agro based industrial structure in rural areas. Some of the rural electrification schemes implemented in the post-independence period are discussed below:

Pradhan Mantri Gramodaya Yojana (PMGY): The PMGY launched in 2000-2001 provided additional financial assistance for minimum services by the central government to all states on a 90% loan and 10% grant basis. These included rural health, education, drinking water and rural electrification. The PMGY, with an outlay of about Rs. 1600 crore during the 10th Plan period, was being coordinated

and monitored by the Rural Development Division of the Planning Commission[8]. More importantly, under PMGY states had the flexibility to decide on the inter-reallocation of funds amongst the basic services. Thus states could enhance allocations to expedite the pace of rural electrification. The scheme has been discontinued from 2005 onwards.

Kutir Jyoti Program (KJP): KJP was initiated in 1988-89 to provide single point light connection (60w) to all Below Poverty Line (BPL) households in the country. KJP provides 100% grant for one time cost of internal wiring and service connection charges and builds in a proviso for 100% metering for release of grants. The Scheme connected nearly 60 lakh households in 15 years or at a rate of approximately 4 lakh households per year. Nearly 5.1 million households have been covered under the scheme to date. The scheme was merged into the Accelerated Electrification of one lakh villages and one crore Households" in May 2004 and now into the RGGVY.

Minimum Needs Program (MNP): The MNP, exclusively targeted states with less than 65% rural electrification (by the old definition) provides 100% loans for last mile connectivity. The program resources are drawn from the Central Plan Assistance. Rs. 775 crore was released during 2001-03 for rural electrification under the MNP. The scheme was discontinued in 2004-05 on account of difficulties in implementation. Accelerated Rural Electrification Program (AREP) The AREP, operational since 2002, provides an interest subsidy of 4% to states for RE programs. The AREP covers electrification of un-electrified villages and household electrification and has an approved outlay of Rs. 560 crore under the 10th Plan. The interest subsidy is available to state governments and electricity utilities on loans availed from approved financial institutions like the Rural Electrification Corporation (REC), Power Finance Corporation (PFC) and from NABARD under the Rural Infrastructure Development Fund (RIDF)

Rural Electricity Supply Technology Mission (REST): The REST initiated on 11th September 2002 with the objective of electrification of all villages and households progressively by year 2012 through local renewable energy sources and decentralized technologies, along with the conventional grid connection. REST proposes an integrated approach for rural electrification and aims:

- To identify and adopt technological solutions
- To review the current legal and institutional framework and make changes when necessary
- To promote, fund, finance and facilitate alternative approaches in rural electrification
- To coordinate with various ministries, apex institutions and research organizations to facilitate meeting national objectives Accelerated Electrification of One Lakh Villages and One Crore Households, MNP and Kutir Jyoti have been merged with the RGGVY.

Rajiv Gandhi Grameen Vidyutikaran Yojana (RGGVY): The RGGVY is the latest national rural electrification scheme launched by the Ministry of Power to execute the vision for rural electrification as recommended by the Chief Ministers conference in 2001.

The plan was instated in April of 2005 with the following objectives:



Key policy recommendations to facilitate the clean energy transition through DDG:

Focus on Decentralized Renewable Solutions: To tackle energy poverty, the paper recommends deploying renewable energy sources like solar microgrids and solar home systems in remote and tribal areas of the state. This approach aims to reduce dependency on unreliable grid connections.

Improve Affordability and Accessibility: The paper suggests implementing subsidies or financing schemes for low-income residents of Jharkhand to make electricity more affordable and accessible.

Policy Support: Recommendations include incentivizing private sector participation, streamlining regulatory processes for microgrid installations, and promoting collaboration between government agencies and local communities.

Grid Reliability: Measures such as better maintenance, increased metering, and improved billing efficiency can stabilize the grid supply and facilitate the incorporation of renewable energy sources [10] thereby improving the quality and reliability of electricity.

IV. CONCLUSION

The paper highlights the critical role of decentralized distributed generation in achieving a clean energy transition and providing cost-effective rural electrification in the state of Jharkhand. By leveraging local renewable resources, such as solar energy, and implementing decentralized solutions like micro-grids and solar home systems, DDG offers a viable pathway to address energy poverty and improve energy access in remote and tribal regions. This approach not only reduces dependence on unreliable grid connections but also promotes energy independence and resilience.

The study identifies key policy interventions needed to facilitate this transition, including enhancing affordability through subsidies, financing schemes for low-income households, and streamlining regulatory processes to attract private sector investment. Moreover, strengthening grid reliability through better maintenance and increased integration of renewable sources can complement decentralized initiatives, leading to a more sustainable and reliable electricity supply.

Adopting decentralized renewable solutions in Jharkhand provides a cost-effective and scalable model for rural electrification that can be replicated in other regions facing similar challenges. The clean energy transition in Jharkhand requires concerted efforts from policymakers, private stakeholders, and local communities to foster inclusive growth and sustainable development. With the help of Jharkhand Solar policy 2024, state can emerge as a leader in decentralized energy solutions, driving the state toward a cleaner and more equitable energy future.

REFERENCES

1. Mirza, Z. T., Vahidi, B., & Abedi, M. (2022). Renewable Energy Development in India & Iran: A Comparative Review of Renewable Energy Policies. *American Journal of Energy Engineering*, 10(2), 21-34.
2. Jharkhand Economic Survey (2024-25), Department of Finance (Centre for Fiscal Studies) Government of Jharkhand.pp.89-96
3. Kumawat, P. (2022). *Renewable energy financing and its challenges perspective* (Doctoral dissertation, School of Petroleum Management).
4. TalhaBin Nadeem a, Mubashir Siddiqui a, Muhammad Khalid b d e, Muhammad Asif c d (2023). Distributed energy systems: A review of classification, technologies, applications, and policies, *Energy Strategy Reviews*, Volume 48, July 2023, 101096.
5. <https://www.jreda.com/>
6. <https://api.jreda.com/all-uploaded-img/img/6360e972de5e0.pdf> (Jharkhand State Solar Policy 2022).
7. <https://powermin.gov.in/en/content/power-sector-glance-all-india>.
8. <https://cea.nic.in/?langen>
9. Final-Brief-Note-Decarbonising-Power-Sector-2.pdf (ceedindia.org)
10. Creating A Renewable Ecosystem: Roadmap For A Clean Energy Transition In Jharkhand, India (Sais-Isep.Org)

NAVIGATING THE FUTURE - BLOCKCHAIN, AI, DATA ANALYTICS, AND DIGITAL TRANSFORMATION IN THE SHIPPING INDUSTRY

Dr. S. Gopinath
Department of Marine Engineering
Coimbatore Marine College,
Coimbatore, Tamil Nadu, India.
sgopy.suresh@gmail.com, 9894912914

Leenacharan SS,
Third-year Cadet from BTech Marine Engineering,
Coimbatore Marine College, Coimbatore- 641032, Tamil
Nadu, India.
leenacharan2004@gmail.com

Abstract- *Technology has continuously disrupted maritime operations, introducing innovative approaches that enhance efficiency across various sectors. The incorporation of blockchain, artificial intelligence (AI), data analytics, and digital transformation optimises sector operations, notably reducing fraud and bolstering transparency in supply chain management. AI plays an essential role in enhancing vessel performance through features like autonomous navigation and predictive maintenance. Data analytics facilitates reliable, real-time decision-making by leveraging data on vessel performance and other metrics. The digitalisation of the maritime industry brings forth streams of data from sensors and other sources, enabling enhanced monitoring, control, quality assurance, and verification. Despite its promise, this future presents challenges, including the adoption of technology and cybersecurity. Nonetheless, further integration of these technologies promises a more secure and sustainable future for the maritime industry, while simultaneously reducing operational costs and environmental impact.*

Keywords: *Autonomous Navigation, Smart Contracts, Fraud Prevention, Port Operations, Digitalisation.*

I. INTRODUCTION

Global trade primarily relies on the shipping industry. Transporting nearly 90% of all goods worldwide, it is undeniably a cornerstone of international trade. In the past, the shipping industry relied on manual processes, paper documentation, and human effort, an approach that resulted in inefficiencies, errors, and delays. Digital technology emerged with the introduction of Electronic Data Interchange (EDI) in the 1970s. These systems enabled the electronic exchange of shipping documents, unlike before, when all transactions had to be conducted physically. Unfortunately, these systems had shortcomings, including high cost, a lack of standardization, and limited interoperability. According to a report by McKinsey & Company, digital transformation in the shipping industry can lead to cost savings of up to 20% and a 15% increase in operational efficiency [5].

In an era of technological advancements, the shipping industry is seeking digital transformation to enhance efficiency, safety, and environmental sustainability. There is thus a critical need for digital transformation in the marine industry. Blockchain technology, artificial intelligence, and big data analytics are among the tools that can help achieve this kind of change intelligently and effectively, transforming the shipping industry digitally in the coming years.

A. Blockchain in the Shipping Industry

Blockchain is a decentralized, distributed ledger technology that ensures data immutability and transparency. Each transaction is recorded in a block and linked to the previous one, forming a chain. This technology is highly secure because altering any information would require changes to all subsequent blocks, which is computationally infeasible [2].

The collaboration between Maersk and IBM on the Trade Lens platform, although no longer in practice, was a blockchain-based solution that enhanced the visibility and efficiency of the global supply chain by enabling real-time shipment tracking and reducing administrative costs by up to 20% [1], as shown in Figure 1.



Fig. 1: Blockchain Technology [20]

Blockchain systems operate on consensus mechanisms such as Proof-of-Work (PoW) and Proof-of-Stake (PoS). PoW requires network participants to solve complex mathematical problems to validate transactions, making it highly secure but energy-intensive. PoS, on the other hand, allows participants to validate transactions based on the number of coins they hold, which is more energy-efficient but requires careful consideration of potential centralisation issues. Contracts self-execute after the terms of an agreement are directly written in their code in some way. They can thus automate processes such as freight payment, eliminating intermediaries and expediting transactions. Smart contracts facilitate complex multi-party agreements while ensuring compliance and reducing transactional administrative overhead [3].

Supply chain transparency: Blockchain provides end-to-end visibility into the supply chain. Each stakeholder involved in shipment tracking is entitled to trace their shipments in real time. To this end, transparency helps ascertain authenticity and thus prevent counterfeit goods from entering the supply chain. For example, Walmart uses blockchain to trace the origin of its food products to ensure quality and safety from farm to table [6].

Fraud Prevention: Blockchain has significantly reduced the risk of fraud by creating an immutable transaction ledger. It provides traceability for every transaction, facilitating the tracking and mitigation of fraudulent activity. For example, every ledger tracks the provenance of diamonds on the blockchain, so there is no possibility they might be conflict and might be authentic [7].

1. Benefits

Improved Security: Because blockchain is cryptographic, it provides strong security and makes data tamper-proof.

One-way transparency entails making the same data available to all parties involved in the shipment process, thereby reducing disputes and increasing trust.

Efficient: Smart contracts allow for process automation and reduce paperwork, hence increasing the speed of transactions.

2. Application

One notable example of blockchain in the shipping industry is Cargo X's partnership with the Egyptian government to streamline and digitise the country's trade documentation process through the Advanced Cargo Information (ACI) system. Cargo X's collaboration with Egypt on the ACI system is pioneering in demonstrating how blockchain can transform trade procedures, as shown in Figure 2. Launched in 2021, the ACI system aims to provide pre-arrival information on shipments, ensuring that all trade documentation is correct and authenticated before shipment to Egypt. To that end, such fronting not only accelerates customs clearance procedures but also reduces fraudulent activity and associated error margins. The structure's achievements can be summarised as faster clearance times, reduced paperwork, and enhanced trade security. This system improves the efficiency and transparency of Egypt's trade operations by leveraging blockchain to securely and efficiently manage and verify trade documents [12-13].



Fig. 2: Cargo X [20]

B. AI in the Shipping Industry

Artificial intelligence is generally defined as the emulation of human intelligence in machines that are subsequently programmed to think and learn. It concerns technologies that enable the analysis of large volumes of data and the execution of decisions based on that analysis, such as machine learning, natural language processing, and robotics. AI can perform tasks typically handled by

human intelligence or intervention, either alone or in combination with technologies such as sensors, geolocation, and robotics. From digital assistants through GPS guidance to self-driving cars, AI dominated yesterday's and today's news and our lives.

1. Application

- **Route Optimisation:** AI algorithms create optimal routes by considering historical data, current weather, and live traffic to reduce fuel usage and transit times. For example, Windward utilises AI to provide shipping routes with real-time insights and predictive analytics, thereby helping companies optimise their logistics operations [8].
- **Predictive Maintenance:** AI-based predictive maintenance systems monitor the status of shipping equipment continuously, predicting possible failures and scheduling maintenance to prevent loss of time.

AI is enabling autonomous, self-navigating vessels that can operate without human intervention, reducing investment costs and enhancing safety. Yara Birkeland, the first autonomous, zero-emission container ship that uses AI for both navigation and operations, is ushering in a sea change in maritime technologies [10].

2. Some of the Core Technologies

- **Situation Awareness System (SAS):** This subsystem gathers data about the ship and its surroundings, creating a model of objects that may impact the ship's operation, including detection and classification.
- **Autonomous Navigation System (ANS):** This system controls the ship's movements, ensuring safe passage through track and speed control, and collision avoidance by evaluating future situations and planning suitable actions. SAS requires sufficient sensor data and algorithms to provide the driver with a high-quality environmental model. ANS, however, may need to decide based on the actions of human officers on other ships. ANS, on the other hand, may ultimately have to make decisions based on what a human officer on the encountered ship will do or will not perform [11].

The International Maritime Organisation's Convention on the International Regulations for Preventing Collisions at Sea, COLREGs, prescribes ship behaviour to avoid collision, including signals and manoeuvring. These rules are primarily valid for encounters between two ships and require "good seamanship." Thus, an AI-based automation system might not handle more than two ships involved or another ship behaving erratically. Hence, 100% autonomous navigation will either require amendments to the COLREGs or impose limits on its operability [11][14].

3. Application and Progress

Rolls-Royce and Fin ferries have successfully tested the world's first fully autonomous ferry, Falco, which utilises AI for navigation and operations, as shown in Figure 3. This innovation demonstrates the potential for AI to revolutionise maritime transportation [9].



Fig. 3: Rolls-Royce and Fin ferries' fully autonomous ferry [21]

C. Data Analytics in the Shipping Industry

Data analytics is the process of examining raw data to yield meaningful insights and inform decision-making, using techniques such as statistical analysis, machine learning, and data mining. Data analytics supports enhanced decision-making, cost savings, and risk management by identifying inefficiencies, optimising operations, and predicting potential risks.

1. Applications

- **Demand Forecasting:** This data analytics can be done by analysing past data, economic indicators, and market trends to form an opinion of what the future demand for shipping services could look like. It enables better resource planning and more efficient fleet deployment, with reduced idle time and smoother operations.
- **Fuel Consumption Data Analysis:** Shipping companies can study data related to fuel consumption to reduce inefficiencies accordingly, implementing measures to reduce fuel use and connected CO₂ emissions. Practising data analytics by applying insights to enhance fuel consumption, for instance, reduced CO₂ emissions by more than 10 per cent for Maersk.
- **Performance Monitoring and Real-time Decision-Making:** Real-time data analytics tools on vessel performance allow users to be informed of their operational efficiency and where there is room for improvement. Real-time decision-making can therefore be implemented to optimise port operations. For example, Cargotec Smart Port Solutions have been touted [18].

2. Real-Time Application

APM Terminals employs data analytics to optimise operations at its port facilities, as shown in Figure 4. By analysing data from multiple sources, the company has improved container-handling efficiency and reduced turnaround times [4].




Fig. 4: APM terminal [23]

II. ANALYTICS: THE BASIC SYNERGY

Blockchain, AI, and data analytics give a powerful synergy that enables digital disruption in the shipping industry. Blockchain will ensure data integrity and transparency, while AI enhances decision-making and data analytics, yielding valuable insights from large datasets.

III. CHALLENGES AND SOLUTIONS

- 1) **Data Security and Cybersecurity** are the most critical challenges, as with the digital revolution having come to stay, the cyber-attack threat is only going to escalate. Strong cybersecurity procedures must be implemented to protect critical data and ensure operational efficiency. An effective cybersecurity policy should include regular security audits, employee training, and an incident response plan. The security of sensitive data is a significant challenge. Blockchain offers robust solutions through its immutable and safe ledger. To protect against cyber threats, strong cybersecurity must include encryption, firewalls, and multi-factor authentication.
- 2) **Interoperability:** Integrating various digital solutions can be tricky sometimes. Modelled with regularised protocols and platforms, this can support seamless integration. For example, organisations such as the International Maritime Organisation are developing global standards for digital technologies in shipping.
- 3) **Skill Gaps:** Equally, new technology requires competent personnel to run it. In this regard, training and development can address this area. Professional educational institutions collaborate with shipping companies in tailoring specialised training in maritime technology and data science.

IV. POTENTIAL IMPACT

The IMO projects that global tonne-miles of goods moved will increase by 2%-4% annually between now and 2050. This substantial industry growth is projected to nearly triple GHG emissions by 2050. It is estimated that GHG emissions from international shipping contribute 870 (Million Metric Tonnes) MMT of CO₂ to the atmosphere, with an additional 180 MMT attributable to domestic and inland ships in 2007, for a total of 1050 MMT. At current rates of increase, CO₂ emissions from the shipping sector are expected to rise to between 2,500 MMT and 3,650 MMT by 2050, as shown in Figure 5. As the world economy's reliance on the global trade of goods, materials, and petroleum continues to rise, this

figure is estimated to climb to between 2,500 MMT and 3,650 MMT by 2050.




Fig. 5: CO2 emissions from ships [24]

Blockchain, along with AI and data analytics, will continue to drive further automation, more transparency within the supply chain, and improved operational efficiency in the shipping industry. Autonomous ships, predictive analytics, smart contracts, and route optimisation will redefine the very concept of Maritime Transport and significantly reduce its ecological footprint. Route optimisation and Predictive Maintenance will also cut fuel consumption and lower the carbon footprint of this industry by up to 30% in CO₂ reduction by 2050, in support of global sustainability [17].

V. REAL-TIME EXAMPLES

1. **Digital Twins:** Borrowed from the business world, digital twins represent virtual models of real physical assets. Their use in the shipping industry has increased in recent years. Digital twins can be used to simulate multiple vessel operation scenarios, predict when maintenance may be required, and optimise operations. For example, the Port of Rotterdam applied digital twin technology to monitor and manage its port infrastructure, thereby improving efficiency by reducing downtime [19].
2. **IoT and Sensor Technology:** The Internet of Things and sensor technology in shipping are changing the industry by capturing real-time data on various parameters like temperature, humidity, and cargo conditions that can be used to improve the safe and efficient transport of goods. Especially for perishables, this is critical. IBM's Food Trust blockchain network integrates IoT data to enhance food safety and traceability [15].
3. **Sustainable shipping practices:** The era of sustainability now confronts the doorstep of the shipping industry. Digital technologies are being harnessed to establish green shipping corridors, optimise vessel designs for improved fuel efficiency, and develop strategies to reduce emissions. The Poseidon Principles, an initiative of global shipping banks, use data analytics to support environmentally responsible lending to the maritime sector [16].

VI. CONCLUSION

1. For any competitive and sustainable performance in the fast-moving world today, the shipping industry needs to be digital.
2. It is actualised by technologies like blockchain, AI, and data analytics, which provide ways to bring about efficiency, security, and transparency.
3. Embracing these innovations will enable the sector to tackle the challenges of modern times and steer toward an efficient and concurrently sustainable future.
4. The path to digital transformation is not going to be easy, but it is one wherein the rewards will outweigh the obstacles. Investments in these technologies not only improve how companies operate but also enhance their cost efficiency and integration, thereby contributing to the shared aim of a more sustainable and transparent global supply chain.
5. The integration of blockchain, AI, and data analytics will be important in the emergence of the future of sea transportation as the industry becomes more competitive.

VII. RECOMMENDATIONS / STRATEGIES TO IMPLEMENT DIGITAL TRANSFORMATION

1. **Invest in Technology:** Shipping companies have to invest in the latest technologies and infrastructure that will aid digital disruption. Among these are upgrading IT systems, investing in IoT devices, and adopting cloud computing to enable real-time data access and analysis.
2. **Collaboration and Partnerships:** Cooperative work with technology providers and industry partners can speed up the adoption of digital solutions. For example, DCSA, the Digital Container Shipping Association, has established robust digital standards and facilitates collaboration among shipping companies to improve interoperability and efficiency.
3. **Change Management:** Digital transformation requires cultural change in a company and associated change management strategies that would secure the buy-in of all stakeholders. This constitutes employee training, innovation culture, and overcoming resistance to change.

REFERENCES

- [1] IBM and Maersk. (2018). Trade Lens: How IBM and Maersk are Sharing Blockchain to Build Global Trade.
- [2] IBM Blockchain. (n.d.) (2020). What is blockchain technology?
- [3] World Economic Forum. (2020). Blockchain and the Shipping Industry.
- [4] APM Terminals. (2019). Data Analytics at APM Terminals.
- [5] McKinsey & Company. (2017). Artificial Intelligence: The Next Digital Frontier?
- [6] Walmart. (2019). Walmart's Blockchain for Food Traceability.
- [7] Ever ledger. (2020). Using Blockchain to Combat Fraud.
- [8] Windward. (2021). Optimising Shipping Routes with AI.

- [9] Rolls-Royce. (2018). Rolls-Royce and Fin Ferries Demonstrate the World's First Fully Autonomous Ferry.
- [10] Yara International (2021). Yara Birkeland.
- [11] Research Publishing, Singapore, European Safety and Reliability Conference (ESREL 2022)
- [12] Cargo X Official Website.
- [13] Ministry of Finance, Egypt (2021)
- [14] International Maritime Organisation. (2020). COLREGs: Convention on the International Regulations for Preventing Collisions at Sea.
- [15] IBM. IBM Food Trust.
- [16] Poseidon Principles. (2020). Promoting Sustainability in Shipping.
- [17] International Transport Forum. (2019). Reducing CO2 Emissions in Shipping.
- [18] Cargotec's official website.
- [19] IBM. What is a digital twin?
- [20] Source - <https://www.linkedin.com/pulse/how-can-shipping-industry-take-advantage-blockchain-technology-shah>
- [21] Source - <https://www.linkedin.com/pulse/cargox-cxo-ico-pre-sale-now-progress-jure-tomc-mba>
- [22] Source - <https://www.rolls-royce.com/media/press-releases/2018/17-05-2018-rr-and-finferries-sign-cooperation-agreement-to-optimize-ship-safety-and-efficiency.aspx>
- [23] Source - <https://www.apmterminals.com/en/moin/about/our-terminal>. Blockchain, AI, and Data
- [24] Source - https://theicct.org/sites/default/files/publications/ICCT_GHGfromships_jun2011.pdf

EMERGING MARITIME LOGISTICS ECOSYSTEMS: DIGITAL TWINS, BLOCKCHAIN, AND COGNITIVE PORTS

Sudarshani Patil
Department of Electrical
Engineering, Tolani
Maritime Institute, Induri,
Pune, India
sudarshani0707@gmail.com

Wallace Jacob
Department of Applied
Science, Tolani
Maritime Institute,
Induri, Pune, India
wallacej@tmi.tolani.edu

Vijaysingh Chavan
Department of Mechanical
Engineering, Tolani
Maritime Institute, Induri,
Pune, India
vijayc@tmi.tolani.edu

Swati Bhise,
Manager HR, Tolani
Maritime Institute,
Induri, Pune, India.
swatib@tmi.tolani.edu

Abstract: The global maritime sector is undergoing a significant digital transformation, with ports evolving from traditional cargo handling facilities into interconnected, data-driven logistics ecosystems. This paper examines next-generation innovative port architectures that integrate digital twins, blockchain-enabled logistics platforms, Internet of Things (IoT) networks, and advanced data analytics to improve operational efficiency, system resilience, and supply chain transparency. Moving beyond fragmented digital initiatives, the study introduces the concept of Cognitive Ports, where port systems function as adaptive environments capable of real-time monitoring, predictive decision-making, and coordinated interaction with shipping operators, hinterland transport systems, and regulatory authorities. By continuously synchronizing digital twins with live operational data, ports can simulate and optimize berth allocation, cargo flows, energy consumption, and equipment condition, thereby enabling predictive maintenance and proactive congestion management. The paper further explores blockchain-enabled port community systems as trusted data-sharing infrastructures that support secure documentation, tamper-resistant transactions, and end-to-end logistics visibility. When combined with AI-driven analytics, these platforms enhance demand forecasting, disruption management, and environmentally optimized logistics planning. Special emphasis is placed on data-driven sustainability, demonstrating how intelligent scheduling, real-time performance monitoring, and green digital performance indicators can help reduce emissions while maintaining operational efficiency. In this context, smart ports are positioned as active digital coordinators of maritime logistics rather than passive infrastructure providers. The findings highlight the strategic importance of integrating advanced technologies, governance frameworks, and human digital competencies to develop future-ready ports. The paper provides practical insights for port authorities, policymakers, and

maritime stakeholders seeking to strengthen competitiveness, sustainability, and resilience in an increasingly digital naval ecosystem.

Keywords: Maritime Supply Chain Management, Blockchain Technology, Smart Ports, IoT, Logistics, Digital Twins

I. INTRODUCTION

The global maritime industry is experiencing a fundamental transformation driven by rapid advances in digital technologies, automation, and data-centric decision-making. Ports, as critical nodes of international trade and logistics networks, are no longer confined to their traditional role as physical infrastructure for cargo handling. Instead, they are increasingly evolving into digitally connected, intelligent ecosystems that integrate operational technologies with advanced information systems to improve efficiency, resilience, and sustainability across maritime supply chains.

The concept of smart ports has emerged in response to growing operational complexities, increasing cargo volumes, environmental regulations, and the demand for real-time visibility in logistics operations. Smart ports typically leverage technologies such as the Internet of Things (IoT), automation systems, port community platforms, and data analytics to optimize terminal operations, reduce congestion, and enhance coordination among stakeholders. While these developments have significantly improved operational performance, most current implementations remain functionally fragmented and reactive, focusing on localized optimization rather than system-wide intelligence.

In parallel, emerging technologies such as digital twins, blockchain, artificial intelligence (AI), and big data analytics are enabling a new paradigm of cyber-physical integration in industrial systems. These technologies have the potential to transform ports from digitally enabled infrastructures into self-aware, adaptive, and

predictive systems that learn from operational data and autonomously support strategic and tactical decisions. This evolution necessitates a shift from the conventional notion of smart ports toward what this paper conceptualizes as “Cognitive Ports” [1]. Figure 1 depicts the stages of port evolution in the digital era.




Fig 1: Evolution of Ports in the Digital Era

Cognitive ports represent an advanced stage of port digitalization, in which physical assets, operational processes, and human actors are continuously synchronized with intelligent digital models. Unlike traditional smart ports, cognitive ports emphasize real-time situational awareness, predictive analytics, and autonomous decision support, enabling proactive management of resources, disruptions, and environmental impacts. This paradigm aligns with the broader vision of Industry 4.0 and the emerging digital maritime ecosystem, where ports function as intelligent orchestrators within interconnected global logistics networks [3].

The primary objective of this paper is to develop a conceptual, integrative framework for cognitive ports that highlights how digital twins, blockchain-based port community systems, and data-driven intelligence can collectively enable next-generation maritime logistics. Specifically, the study aims to (i) review the evolution of port digitalization, (ii) define the core characteristics of cognitive ports, and (iii) propose a system-level framework for intelligent and sustainable port operations.

The remainder of this paper is structured as follows. Section 2 reviews the evolution of port digitalization from automation to intelligent systems. Section 3 introduces the cognitive port paradigm. Subsequent sections examine the roles of digital twins, blockchain, and smart analytics, followed by a proposed integrated framework and directions for future research [2].

II. EVOLUTION OF PORT DIGITALIZATION: FROM AUTOMATION TO INTELLIGENCE

Port digitalization has progressed through multiple evolutionary stages, shaped by technological advances and changing operational demands. Initially, ports focused on mechanization and automation, introducing container-handling equipment, terminal operating systems (TOS), and automated guided vehicles (AGVs) to improve productivity and reduce labor dependence. These developments primarily targeted operational efficiency at the terminal level, with limited integration across stakeholders or logistics networks. Table 1 presents the framework for different ports.

Table 1: Framework for different ports

Port Type	Key Technologies	Decision-Making	Level of Intelligence	Typical Characteristics
Traditional Port	Mechanical equipment	Manual	Relatively Low	Labour-intensive, low visibility
Automated Port	AGVs, TOS	Rule-based	Low	High efficiency, limited adaptability
Smart Port	IoT, cloud, PCS	Data-assisted	Medium	Real-time monitoring, dashboards
Cognitive Port	Digital twins, AI, blockchain	Autonomous & Predictive	High	Self-learning, adaptive, sustainable

The next phase involved the emergence of digitally enabled ports, where information and communication technologies (ICT) were adopted to enhance coordination and information sharing. Port Community Systems (PCS), electronic data interchange (EDI), and integrated logistics platforms enabled smoother interactions among shipping lines, terminal operators, customs authorities, freight forwarders, and hinterland transport providers. However, these systems often operated in silos, lacking interoperability and real-time intelligence.

With the advent of Industry 4.0, the concept of smart ports gained prominence. Smart ports integrate IoT sensors, cyber-physical systems, cloud computing, and data analytics to enable real-time monitoring of port

operations. Examples include smart cranes, intelligent traffic management systems, automated yard planning, and real-time vessel tracking. These technologies facilitate data-driven optimization of port resources, improving throughput, safety, and service quality.

Despite these advancements, existing innovative port implementations exhibit several limitations. Most systems remain reactive rather than predictive, responding to events after they occur instead of anticipating future conditions. Decision-making is often human-dependent, supported by dashboards rather than autonomous intelligence. Furthermore, current smart ports struggle with challenges related to data fragmentation, cybersecurity, governance, and integration with sustainability objectives [3-4].

The emerging digital landscape, characterized by AI, digital twins, and decentralized data infrastructures, is enabling a transition toward intelligent port systems that extend beyond automation and connectivity. These systems emphasize learning, adaptation, and self-optimization, laying the foundation for the cognitive port paradigm. In this context, port digitalization is no longer limited to technological upgrades but constitutes a systemic transformation encompassing governance models, workforce competencies, and cross-sector digital ecosystems.

III. CONCEPTUALIZING THE COGNITIVE PORT PARADIGM

The increasing complexity of maritime logistics, coupled with the demand for real-time responsiveness, sustainability, and resilience, necessitates a fundamental rethinking of how ports operate within digital ecosystems. While smart ports have successfully introduced automation and data-driven monitoring, their operational logic largely remains human-centric and reactive, relying on predefined rules and post-event analysis. In contrast, the emerging paradigm of cognitive ports represents a shift toward intelligent, adaptive, and self-learning port systems capable of autonomous reasoning and proactive decision-making.

A cognitive port is an intelligent cyber-physical maritime system that continuously senses, learns, predicts, and optimizes port operations through integrated digital intelligence and human-machine collaboration. Unlike conventional smart ports, which primarily focus on data acquisition and visualization, cognitive ports emphasize situational awareness, predictive analytics, and system-level intelligence, thereby enabling ports to anticipate disruptions, dynamically reconfigure resources, and align operational decisions with strategic objectives. Figure 2

shows the Conceptual Architecture of a Cognitive Port System.




Fig 2: Conceptual Architecture of a Cognitive Port System

The cognitive port paradigm is built upon the convergence of four foundational layers:

- (i) the physical layer, comprising port infrastructure, vessels, cargo handling equipment, and energy systems;
- (ii) the data layer, including IoT sensors, real-time monitoring platforms, and interoperable data repositories;
- (iii) the intelligence layer, consisting of AI algorithms, digital twins, machine learning models, and decision-support systems; and
- (iv) the governance layer, which integrates cybersecurity, regulatory compliance, digital standards, and human expertise.

At the core of this paradigm lies the concept of continuous cyber-physical synchronization, in which real-world port operations are mirrored by digital twins that evolve dynamically in response to real-time data streams. These digital counterparts enable real-time simulation, scenario analysis, and predictive forecasting of operational conditions, including berth congestion, equipment failure, energy demand, and environmental impact. By embedding artificial intelligence within these digital models, cognitive ports can transition from descriptive analytics to prescriptive and autonomous operational intelligence [3].

Furthermore, cognitive ports facilitate collective intelligence across maritime stakeholders, enabling seamless coordination between port authorities, terminal operators, shipping companies, logistics providers, and regulatory agencies. Blockchain-enabled data infrastructures and interoperable port community

systems ensure trusted information sharing, while AI-driven analytics transform fragmented operational data into actionable strategic insights. This transformation allows ports to function not merely as infrastructure providers, but as digital orchestrators of maritime supply chains [5].

In essence, the cognitive port paradigm redefines port systems as learning organizations in which digital technologies enhance not only efficiency and automation but also adaptability, resilience, and sustainability. This conceptual shift aligns with the broader vision of intelligent transport systems and integrated digital ecosystems, positioning cognitive ports as central nodes in the future maritime economy.

IV. DIGITAL TWIN TECHNOLOGIES FOR COGNITIVE PORTS

Digital twin technology constitutes a central enabling pillar of the cognitive port paradigm. A digital twin is a dynamic, virtual representation of a physical system that is continuously updated using real-time data from sensors, operational systems, and external information sources. In port systems, digital twins enable real-time mirroring of physical assets, processes, and environmental conditions within a unified cyber-physical framework.

Unlike conventional simulation models, which are typically static and scenario-specific, digital twins operate as living models that evolve continuously in response to operational data. This capability allows cognitive ports to achieve real-time situational awareness and predictive intelligence across multiple operational domains, including vessel traffic management, berth allocation, yard operations, equipment health monitoring, and energy management [4].

At the system level, a port digital twin integrates data streams from heterogeneous sources, including Automatic Identification System (AIS) data, IoT sensors embedded in cranes and handling equipment, terminal operating systems, weather services, and logistics platforms. Analytics engines and AI models process this data to generate a synchronized digital environment that reflects both the current state and the predicted future behavior of the port system.

From a functional perspective, digital twins in cognitive ports support three primary intelligence functions: Descriptive intelligence, which provides real-time visualization and monitoring of port operations, including vessel movements, cargo flows, and

infrastructure utilization. Predictive intelligence, which enables forecasting of congestion, equipment failures, energy demand, and environmental impacts using machine learning and time-series models. Prescriptive intelligence, which recommends optimal operational strategies such as berth scheduling, resource allocation, and maintenance planning through optimization algorithms and decision-support systems.

One of the most significant advantages of digital twin-based port management is the ability to conduct real-time what-if scenario analysis. Port operators can simulate alternative operational strategies under varying conditions, such as peak demand, extreme weather events, or disruptions in hinterland connectivity. This capability enhances both operational resilience and strategic planning, allowing cognitive ports to anticipate risks and proactively mitigate system-level inefficiencies [11]. Figure 3 shows the architecture of a Digital Twin for Cognitive Port Operations.




Fig 3: Architecture of a Digital Twin for Cognitive Port Operations

Furthermore, digital twins play a critical role in predictive maintenance and asset management. By continuously analyzing equipment performance data, cognitive ports can detect early signs of mechanical degradation in cranes, automated vehicles, and power systems. This enables condition-based maintenance strategies that reduce downtime, extend asset lifecycles, and improve overall system reliability.

In the long term, digital twins serve as the core intelligence engine of cognitive ports, enabling continuous learning, system optimization, and autonomous operational control. When integrated with AI, blockchain-based data infrastructures, and governance mechanisms, digital twins transform ports

into adaptive, self-optimizing systems capable of operating efficiently within complex and uncertain maritime environments.

V. BLOCKCHAIN-ENABLED PORT COMMUNITY SYSTEMS

As maritime logistics systems become increasingly digital and interconnected, the reliability, integrity, and security of data exchange among stakeholders emerge as critical challenges. Port operations involve a complex network of actors, including port authorities, terminal operators, shipping companies, customs agencies, freight forwarders, and hinterland transport providers, all of whom rely on timely and accurate information to coordinate effectively. Traditional centralized information systems often suffer from data silos, limited transparency, interoperability issues, and vulnerability to cyber threats [6].

Blockchain technology offers a promising solution by enabling decentralized, immutable, and trusted data infrastructures for port community systems. A blockchain-enabled port community system is a distributed digital platform that facilitates secure and transparent information sharing among maritime stakeholders through cryptographic consensus mechanisms and smart contracts. Unlike conventional databases, blockchain systems ensure that all participants have access to a synchronized and tamper-proof version of operational records, thereby enhancing trust and accountability across the maritime supply chain.

In the context of cognitive ports, blockchain serves as a foundational trust layer that complements digital twins and AI-driven analytics. Operational data generated from IoT devices, terminal systems, and logistics platforms can be securely recorded on distributed ledgers, enabling verifiable tracking of cargo movements, vessel schedules, customs documentation, and regulatory compliance. Smart contracts further automate administrative processes such as berth allocation approvals, cargo release authorizations, and port fee settlements, reducing manual intervention and transactional delays [7].

In the context of cognitive ports, blockchain serves as a foundational trust layer that complements digital twins and AI-driven analytics. Operational data generated from IoT devices, terminal systems, and logistics platforms can be securely recorded on distributed ledgers, enabling verifiable tracking of cargo movements, vessel schedules, customs documentation, and regulatory compliance. Smart contracts further automate administrative processes, such as berth allocation approvals, cargo release authorizations, and port fee settlements, thereby

reducing manual intervention and transactional delays [7]. Figure 4 shows Blockchain-Enabled Port System Architecture.



Fig 4: Blockchain-Enabled Port System Architecture

One of the most significant advantages of blockchain-enabled port systems is the enhancement of end-to-end supply chain visibility and traceability. By maintaining a shared ledger of logistics events, cognitive ports can ensure real-time transparency across multiple organizations without compromising data integrity or ownership. This capability is particularly valuable for handling sensitive documents such as bills of lading, certificates of origin, and compliance records, which traditionally involve extensive paperwork and verification procedures.

From a cybersecurity perspective, blockchain architectures improve system resilience by eliminating single points of failure and strengthening data protection through cryptographic techniques. While blockchain does not replace conventional cybersecurity measures, it significantly enhances data authenticity, access control, and auditability, which are essential for safeguarding digital maritime ecosystems. When integrated with AI-based anomaly detection systems, blockchain-enabled platforms can also support early identification of cyber threats and fraudulent activities [10].

Furthermore, blockchain technologies contribute to digital governance and regulatory innovation by enabling standardized data formats, interoperable digital identities, and automated compliance monitoring. These features facilitate alignment with international maritime regulations and emerging digital standards, supporting the long-term vision of fully integrated and intelligent maritime logistics networks.

In summary, blockchain-enabled port community systems provide the institutional and technological foundation for trust-based collaboration in cognitive ports. By ensuring secure, transparent, and decentralized data exchange, block-chain transforms port ecosystems from fragmented information networks into coordinated digital supply chain platforms that support autonomous and intelligent maritime operations.

VI. DATA-DRIVEN DECISION MAKING AND INTELLIGENT ANALYTICS

The effectiveness of cognitive ports ultimately depends on their ability to transform vast volumes of heterogeneous operational data into actionable intelligence. While digital twins provide real-time system representation and blockchain ensures trusted data exchange, it is data-driven analytics and artificial intelligence (AI) that enable cognitive ports to reason, learn, and autonomously support decision-making processes. Modern port systems generate large datasets from multiple sources, including vessel-tracking systems, IoT-enabled equipment, terminal operating platforms, weather services, energy management systems, and logistics networks. These datasets are characterized by high volume, velocity, and variety, requiring advanced big data architectures and analytics frameworks for effective processing and interpretation. Cognitive ports, therefore, rely on integrated data pipelines that combine cloud computing, edge analytics, and real-time streaming platforms to enable continuous situational awareness. From an analytical perspective, intelligent port systems operate across three complementary layers of analytics.

First, descriptive analytics enables real-time monitoring and visualization of operational conditions, such as vessel movements, cargo throughput, equipment utilization, and energy consumption. These analytics enhance transparency and support human operators through interactive dashboards and performance indicators.

Second, predictive analytics employ machine learning and statistical models to forecast future operational states, including congestion levels, equipment failures, demand fluctuations, and environmental impacts. Time-series forecasting models, neural networks, and probabilistic risk models enable cognitive ports to anticipate disruptions and prepare proactive responses.

Third, prescriptive analytics generates optimized operational strategies by combining predictive insights with optimization algorithms and decision-support systems. These systems recommend optimal actions, including berth scheduling, yard resource allocation, maintenance planning, and energy dispatch, thereby

enabling autonomous and adaptive control of port operations [5].

A defining feature of cognitive port intelligence is the presence of closed-loop learning systems, where AI models continuously improve their performance through feedback from real-world outcomes. Decisions implemented in physical port systems are evaluated using performance metrics and operational data, which are then fed back into learning algorithms to refine future predictions and recommendations. This self-learning capability enables cognitive ports to evolve dynamically in response to changing operational contexts and external uncertainties.

Furthermore, intelligent analytics support risk-aware, resilience-oriented decision-making. By integrating historical data with real-time system states, cognitive ports can identify early warning signals of disruptions such as extreme weather events, cyber incidents, or supply chain bottlenecks. AI-driven risk assessment models allow port authorities to evaluate alternative strategies under uncertainty and select robust operational policies that enhance system resilience. In essence, data-driven decision-making transforms cognitive ports into autonomous reasoning systems, in which intelligence is not embedded in isolated tools but distributed across the entire operational ecosystem. This paradigm enables ports to shift from reactive operational management toward predictive, prescriptive, and self-optimizing logistics orchestration, laying the foundation for intelligent and sustainable maritime infrastructure.

VII. SMART PORTS AS ENABLERS OF SUSTAINABLE MARITIME LOGISTICS

Sustainability has emerged as a central strategic priority for the global maritime sector, driven by increasing regulatory pressures, climate commitments, and stakeholder expectations. Ports, as central nodes of naval logistics and industrial activity, play a critical role in influencing the environmental footprint of shipping operations. Traditional port systems are associated with high energy consumption, greenhouse gas emissions, air pollution, and waste generation, necessitating innovative approaches to sustainable transformation.

Cognitive ports provide a unique opportunity to integrate digital intelligence with sustainability objectives, enabling real-time monitoring, optimization, and governance of environmental performance. By leveraging digital twins, IoT-based sensing, and AI-driven analytics, cognitive ports can continuously assess key ecological indicators, including fuel consumption, carbon emissions, energy efficiency, noise levels, and

waste flows. This real-time visibility allows port authorities to move beyond static sustainability reporting toward dynamic, data-driven environmental management.

One of the most significant contributions of cognitive ports to sustainability lies in energy-aware operational optimization. AI-based scheduling algorithms can minimize vessel idle time, optimize crane operations, and coordinate hinterland transport to reduce unnecessary energy consumption. Digital twin simulations further enable ports to evaluate alternative operational strategies, such as shore power deployment, smart grid integration, and renewable energy utilization, before physical implementation. Figure 5 shows a digital sustainability framework for cognitive ports.



Figure 5: Digital Sustainability Framework for Cognitive Ports

Cognitive ports also support decarbonization and emissions control through predictive and prescriptive analytics. Machine learning models can forecast emission patterns across different traffic scenarios and recommend operational adjustments to minimize carbon intensity. These capabilities are particularly relevant for compliance with international maritime regulations and environmental standards, including emission control areas and emerging carbon reporting frameworks [8].

From a circular-economy perspective, intelligent analytics enable ports to optimize resource utilization, waste management, and asset lifecycle management. Predictive maintenance strategies reduce material waste and extend equipment lifespan, while data-driven logistics planning improves container reuse, reverse logistics, and multimodal coordination. These measures

contribute to the development of green port ecosystems that balance economic efficiency with environmental responsibility. Furthermore, cognitive ports facilitate digital ESG (Environmental, Social, and Governance) reporting, providing transparent and verifiable sustainability metrics to regulators, investors, and stakeholders. Blockchain-enabled data infrastructures ensure the integrity and traceability of environmental data, while AI-driven dashboards support continuous performance benchmarking and compliance monitoring [9].

In summary, cognitive ports act as digital catalysts for sustainable maritime logistics, enabling the transition from compliance-driven environmental management to intelligent, proactive, and system-wide sustainability optimization. This integration of digital intelligence with environmental stewardship positions cognitive ports as key enablers of the global green maritime transition.

VIII. GOVERNANCE, STANDARDS, AND IMPLEMENTATION CHALLENGES

Despite the significant potential of cognitive ports, their large-scale implementation faces several technical, organizational, and regulatory challenges. One of the primary barriers is the lack of standardized data models and interoperability frameworks across port systems, logistics platforms, and maritime stakeholders. Heterogeneous data formats, proprietary systems, and fragmented digital infrastructures hinder seamless information exchange and limit the effectiveness of intelligent analytics.

Digital governance represents another critical challenge in cognitive port ecosystems. The deployment of AI-driven decision systems raises essential concerns related to data ownership, accountability, transparency, and ethical responsibility. As operational decisions become increasingly automated, precise governance mechanisms are required to define roles and responsibilities among port authorities, system operators, technology providers, and regulatory bodies [6].

Cybersecurity and data protection also pose significant risks. Cognitive ports rely heavily on interconnected digital platforms, IoT networks, and cloud infrastructures, making them vulnerable to cyber threats, system failures, and malicious attacks. While blockchain technologies enhance data integrity, they must be complemented by comprehensive cybersecurity frameworks, access control mechanisms, and continuous system monitoring to ensure operational resilience.

From an institutional perspective, the adoption of cognitive port technologies requires substantial organizational transformation and workforce upskilling. Port personnel must develop new digital competencies related to data analytics, AI systems, and cyber governance. Resistance to change, a lack of technical expertise, and limited investment capacity, particularly in developing maritime regions, can further slow the transition toward intelligent port systems [10]. Figure 6 illustrates key challenges in implementing cognitive ports.




Figure 6: Key challenges in the implementation of Cognitive Ports

Finally, regulatory and legal frameworks have yet to fully adapt to the realities of autonomous and AI-driven port operations. Existing maritime regulations are primarily designed for human-centric systems and may not adequately address issues such as algorithmic decision-making, liability in autonomous operations, and cross-border digital governance. These challenges highlight the need for international coordination, adaptive regulatory policies, and collaborative standardization efforts 9: future Research Directions and Industry Implications.

IX. FUTURE RESEARCH DIRECTIONS AND INDUSTRY IMPLICATIONS

The cognitive port paradigm opens multiple avenues for future research and industrial innovation. From a technological perspective, further research is required to develop advanced AI models capable of real-time learning, multi-objective optimization, and explainable decision-making in complex maritime environments. Integrating reinforcement learning, federated learning, and edge intelligence can significantly enhance the autonomy and adaptability of cognitive port systems.

Another promising research direction involves integrating cognitive ports with autonomous vessels and Maritime Autonomous Surface Ships (MASS). Future port systems must be capable of seamless coordination with autonomous ships, remote operation centres, and intelligent fleet management platforms, thereby enabling fully automated end-to-end maritime logistics chains.

From an industry perspective, cognitive ports offer substantial strategic benefits for port authorities and logistics operators. These include improved operational efficiency, reduced environmental impact, enhanced resilience, and more significant global competitiveness. Cognitive port platforms can also serve as innovation hubs, enabling collaboration among technology providers, maritime operators, policymakers, and research institutions.

At the policy level, cognitive ports support the development of evidence-based maritime governance, where real-time system data and predictive analytics inform regulatory decisions. This creates opportunities for adaptive regulation, performance-based compliance frameworks, and international digital cooperation in maritime transport.

Overall, the cognitive port paradigm represents not merely a technological upgrade but a systemic transformation of maritime infrastructure, positioning ports as intelligent, autonomous, and sustainable orchestrators of global logistics networks.

X. CONCLUSION

This paper presents a comprehensive conceptual framework for cognitive ports as the next evolutionary stage in the development of innovation within the digital maritime ecosystem. By integrating digital twins, blockchain-enabled port community systems, and AI-driven intelligent analytics, cognitive ports are envisioned as adaptive cyber-physical systems capable of real-time learning, predictive reasoning, and autonomous operational optimization. The study highlighted how cognitive ports extend beyond conventional innovative port implementations by enabling continuous cyber-physical synchronization, trusted data governance, and closed-loop decision-making. Furthermore, the role of cognitive ports in promoting sustainable maritime logistics was emphasized, demonstrating how digital intelligence can support energy optimization, emissions reduction, circular economy practices, and ESG-based governance.



From a strategic perspective, cognitive ports redefine ports' role from passive infrastructure providers to intelligent digital orchestrators of maritime supply chains. While several technical, regulatory, and organizational challenges remain, the proposed framework provides a robust foundation for future research, policy development, and industrial implementation.

In conclusion, cognitive ports represent a critical enabler of the future maritime economy, where technology, sustainability, and intelligence converge to shape resilient, efficient, and globally competitive naval ecosystems. to support the sustainable evolution of cognitive ports.

REFERENCES

- [1] Belmoukari, B., Audy, J.-F., & Forget, P. (2023). Smart port: A systematic literature review. *European Transport Research Review*.
- [2] Paraskevas, A. (2024). Smart Ports in Industry 4.0: A systematic Literature review. *Logistics MDPI*.
- [3] Li, K. X. (2023). Smart port: A bibliometric review and future research directions. (Academic study on innovative port research trends).
- [4] Neugebauer, J. (2024). Digital Twins in the Context of Seaports and Terminal Facilities. (Exploratory study and case analysis).
- [5] Zeng, F., Chen, A., Xu, S., Chan, H. K., & Li, Y. (2025). Digitalisation in the Maritime Logistics Industry: A systematic literature review of enablers and barriers. *Journal of Marine Science and Engineering*, 13(4), 797.
- [6] Farah, M. B. (2024). A survey on blockchain technology in the maritime industry. (Comprehensive analysis of maritime blockchain adoption).
- [7] Guan, P. (2024). Blockchain adoption in the port industry: A systematic literature review. *Heliyon*.
- [8] Ferrarini, L., Filippopoulos, Y., & Lajic, Z. (2025). Digital transformation in the shipping industry: A network-based bibliometric analysis. *Journal of Marine Science and Engineering*, 13(5), 894.
- [9] Koritarov, T., & Dimitrakiev, D. (2025). The impact of digitalisation on smart ports: Enhancing efficiency, sustainability, and competitiveness. (Preprint/ResearchGate).
- [10] Nasser, A. (2025). Blockchain technology in maritime single window and port community systems: Systematic literature review and bibliometric analysis. (ScienceDirect).
- [11] Zhou, F., Yu, K., & Zhou, S. (2022/2023). Digital twin-enabled innovative maritime logistics management: A bibliometric analysis. *IEEE Access* (Industry 5.0 focus).

MICROFLUIDIC LAB-ON-CHIP SYSTEMS FOR ONBOARD DETECTION OF CONTAMINANTS IN MARINE HEAVY FUEL OIL USING LAMINAR FLOW AND AI-BASED ANALYSIS

Parth Sareen

B.Tech (Marine Engineering)

Tolani Maritime Institute

Induri, Maharashtra
410507

parthsareen2006@gmail.com

Dibyajyoti Rano

B.Tech (Marine Engineering)

Tolani Maritime Institute

Induri, Maharashtra
410507

djrano2005@gmail.com

Mohit Parihariya

B.Tech (Marine Engineering)

Tolani Maritime Institute

Induri, Maharashtra
410507

parihariyamohit7@gmail.com

Rishi Kumar

B.Tech (Marine Engineering)

Tolani Maritime Institute

Induri, Maharashtra
410507

therishi789@gmail.com

Abstract - The maritime industry depends extensively on Heavy Fuel Oil (HFO) for propulsion, making fuel quality a critical determinant of engine efficiency, emissions, and overall vessel safety. Current techniques for fuel quality testing such as bench-top viscometry, gas chromatography, and density analysis are typically performed onshore, introducing significant delays, higher costs, and the risk of engine damage from undetected contaminants (water ingress, sludge, catalytic fines, microbial growth, incompatible blends). This paper proposes a compact, robust microfluidic Lab-On-Chip (LoC) system capable of real-time, on-board detection of contaminants in HFO, leveraging principles of laminar flow, Poiseuille dynamics, optofluidic, and machine learning. The system integrates microchannels (10–500 μm), passive laminar-flow-based mixing, capillary viscometry, refractive-index sensors, and resonant microstructures for density measurement. Microfluidics enables precise diffusion-based assays, stable flow patterns, and low reagent consumption, while AI algorithms classify contamination patterns and predict fuel degradation states. A conceptual system architecture is provided, followed by theoretical modeling, sensor design, expected performance, and potential deployment on commercial vessels. The proposed approach aims to transform marine fuel monitoring into a continuous, automated, and predictive diagnostic process.

Keywords - Heavy Fuel Oil, Fuel Quality Testing, Lab-On-Chip system, Capillary viscometry, Marine fuel monitoring

DATA ACCESS STATEMENT

The data used in this study are available upon reasonable request to researchers who meet the criteria for access and agree to the terms and conditions of the data use agreement. Data requests should be submitted to [Corresponding Author's Name] at [Corresponding Author's Email]. All data requests will be reviewed on a case-by-case basis to ensure that they align with the original purpose of the study and comply with any applicable ethical guidelines.

Please note: Due to the sensitive nature of some of the data analyzed in this study, certain restrictions may apply to access. These restrictions are in place to protect the privacy and confidentiality of individuals and organizations involved.

For further information or to request access to the data, please contact the corresponding author.

I. INTRODUCTION:

Heavy Fuel Oil is a complex mixture of hydrocarbons, asphaltene, sulfur compounds, residual catalyst particles, and trace metals. Variability in refinery output, inadequate purification, and seawater contamination often lead to significant deviations in viscosity, density, and chemical composition. Traditionally, onboard monitoring is limited to coarse viscometers and manual sampling, resulting in poor temporal resolution and delayed response to fuel degradation.

Microfluidics, operating at micrometer-scale dimensions, offers a fundamentally different approach. At these scales, fluid behavior is dominated by **viscous forces**, and the **Reynolds number (Re) is typically < 1**, ensuring stable laminar flow. This predictable flow is ideal for controlled diffusion-based mixing, precise reaction timing, and integration of optical or pressure sensors within compact chips.

The maritime sector has begun embracing digitalization, yet **real-time fuel condition monitoring remains outdated**. Integrating microfluidic LoC sensors with AI creates a powerful opportunity for:

- automated inline detection of water, sludge, sulfur, aromatics, and salinity,
- predictive fuel-quality analytics,
- adaptive engine tuning based on live

- viscosity/density feedback,
- compliance monitoring for IMO emission regulations.

This paper outlines the fundamental microfluidic principles, proposed device architecture, detection mechanisms, and AI integration, culminating in a detailed system-level analysis.

II. FORMULAE AND OBTAINED VALUES

2.1 Flow Regimes and Reynolds Number

In microchannels, the Reynolds number is:

$$Re = \frac{\rho U D_h}{\mu}$$

Typical values for HFO at warm temperature (50–70°C):

- Density: $\rho \approx 950\text{--}1020 \text{ kg/m}^3$
- Viscosity: $\mu \approx 80\text{--}500 \text{ cP}$ (0.08–0.5 Pa·s)
- Hydraulic diameter: $D_h = 10\text{--}500 \text{ }\mu\text{m}$
- Velocity: $U = 1\text{--}10 \text{ mm/s}$

This yields:

$$Re \approx 0.001 - 0.1$$

Thus, flow is **strictly laminar**, enabling predictable parallel-layer flow with negligible turbulence.

2.2 Diffusion-Dominated Mixing

When two fluids meet in a microchannel, mixing occurs primarily via **molecular diffusion**, governed by Fick's law:

$$t_{\text{mix}} \approx \frac{w^2}{2D}$$

Where

w = channel width (10–500 μm),

D = diffusion coefficient.

For seawater + reagent ($D \approx 10^{-9} \text{ m}^2/\text{s}$, $w=100 \text{ }\mu\text{m}$):

$$t_{\text{mix}} \approx \frac{(100 \times 10^{-6})^2}{2 \times 10^{-9}} \approx 5 \text{ s}$$

By controlling channel length L and flow velocity U :

$$L = U \cdot t_{\text{mix}}$$

Thus, precision timing is built into the geometry.

2.3 Optofluidics and Refractive Index Sensing

The refractive index n of a fluid changes with salinity or aromatic content:

$$\Delta n = k \cdot C$$

Integrated waveguides in the microfluidic chip detect phase shift or intensity variations as a function of salt concentration.

2.4 Microfluidic Viscosity Measurement (Poiseuille Flow)

For a rectangular channel:

$$\Delta P = \frac{12\mu QL}{wh^3}$$

Where,

L = length,

w = width,

h = height,

Q = flow rate.

Thus:

$$\mu \propto \frac{\Delta P}{Q}$$

Changes in viscosity indicate:

- contamination with seawater,
- incompatible blends,
- sludge/asphaltene instability,
- high catalytic fines.

III. PROPOSED MICROFLUIDIC LOC SYSTEM FOR HFO MONITORING

3.1 System Architecture

Overall Layout

i. Sampling Port

- Draws small volume of warm HFO ($\approx 0.5 \text{ mL/min}$).
- Includes micron-scale filtration.

ii. Thermal Conditioning Unit

- Maintains constant temperature (50–65°C) for viscosity accuracy.

iii. Microfluidic LoC Chip

- Parallel channels (50–300 μm).
- Side-by-side laminar flow mixing.
- Pressure sensors at inlets and outlets.
- Optical waveguides + LEDs + photodiodes.
- Resonant cantilever density sensor.

iv. Data Acquisition System

- Pressure, optical, density & thermal sensors.

v. AI-Based Analyzer

- Pretrained models for contamination fingerprinting.
- Predictive maintenance alerts.
- vi. **Interface to Ship Engine Management**
 - Optional auto-viscosity control

3.2 Fuel Contamination Indicators and Measurable Parameters

TABLE 1 PARAMETERS

Contaminant	Microfluidic Detection Method	Indicator
Seawater ingress	Refractive index + colorimetric diffusion channel	Δn , color gradient
Sludge/asphaltene	Viscosity increase, clogging signature	$\Delta P \uparrow$
Microbial growth	Fluorescent tag + diffusion mixing	Fluorescence intensity
Incompatible blends	Density + viscosity deviation	$\Delta \rho, \Delta \mu$
Catalytic fines	Optical scattering	Turbidity

3.3 Example Graph: Pressure Drop vs. Flow Rate (Poiseuille Validation)




Fig 1 Pressure Drop vs. Flow Rate

IV. AI INTEGRATION FOR PREDICTIVE FUEL QUALITY MONITORING

4.1 Dataset Construction

Training data includes:

- optical absorption spectra,
- pressure sensor arrays,
- density resonances,
- diffusion-based assay images (RGB).

Label categories:

- clean HFO baseline,
- 0.1–5% seawater addition,
- microbial contamination stages,
- engine-wear metal intrusion (Fe, Ni),
- sludge formation stages.

4.2 Model Types

- Convolutional Neural Network (CNN), Analyzes diffusion assay images.
- Gradient Boosted Trees for structured data (ΔP , Q , n , ρ , μ).
- Hybrid Transformer Models for sequential temporal trends.

4.3 Predictive Outputs

- fuel degradation timeline,
- contaminant classification with confidence level,
- probability of purifier overload,
- recommended corrective action,
- estimated remaining useful life (RUL) of current batch.

This replaces manual logbook entries with continuous monitoring.

V. EXPERIMENTAL DESIGN AND EXPECTED PERFORMANCE

5.1 Channel Dimensions & Materials

- Width = 50–300 μm
- Height = 50–150 μm
- Length = 10–30 mm
- Material = glass, PDMS with fluoropolymer coatings (resistant to hydrocarbons).

5.2 Temperature Control

HFO viscosity is highly temperature-dependent:

$$\mu(T) = \mu_0 e^{\frac{E}{RT}}$$

Thus, chip is temperature-regulated using micro-heaters.

5.3 Expected Limits of Detection

TABLE 2 LIMITS OF DETECTION

Parameter	LOD
Water (H ₂ O)	0.05–0.1%
Density deviation	<0.5 kg/m ³
Viscosity deviation	<1–2%
Catalytic fines	1–3 ppm
Microbial contamination	10 ³ –10 ⁴ CFU/mL

5.4 Integration with Existing Ship Systems

- Fuel supply line → sampling pump → LoC → drain back to settling tank.
- Power consumption: < 10 W.
- Data storage: 6 months onboard.
- Remote upload via satellite.

5.5 Findings

This proposed LoC system addresses numerous existing problems:

- Eliminates sampling delays (current delays: 12–72 hours for lab results).
- Detects contamination early before purifier overload or injector choking.
- Reduces fuel-related engine damage, a common cause of ship breakdowns.
- Supports IMO compliance especially sulfur verification through refractive-index signatures.
- Compact, low-cost, and continuous, unlike laboratory equipment.

Challenges include:

- maintaining thermal stability at sea,
- avoiding fouling in microchannels,
- creating robust chip materials resistant to heavy hydrocarbons.

VI. COST AND OPERATIONAL ADVANTAGES

The adoption of a microfluidic Lab-on-Chip (LoC) system for onboard Heavy Fuel Oil (HFO) monitoring offers substantial cost savings and operational benefits compared to conventional laboratory-based and mechanical testing methods. Traditional fuel-quality analysis requires external sampling, shipping, and laboratory evaluation, costing ₹15,000–₹40,000 per test and introducing delays of 24–72 hours. Mechanical viscometers installed onboard are limited to a single parameter, require frequent calibration, and are prone to drift when exposed to heavy hydrocarbons. In contrast, the proposed microfluidic LoC system uses microliter-scale reagent volumes, drastically reducing consumable costs by 500–1000×. A complete LoC module can be manufactured and installed for approximately ₹60,000–₹1,50,000, with minimal annual maintenance.

Beyond cost, the system enables **continuous, real-time** monitoring of viscosity, salinity, density, and contamination signatures, eliminating the guesswork associated with periodic manual sampling. The precise control of laminar flow ensures repeatable assays, while AI-driven data interpretation provides early warnings of water ingress, sludge formation, incompatible blending, or catalytic fines—events that can cause engine damage costing several lakhs to crores. The LoC system therefore not only reduces operational expenses but also significantly enhances safety, fuel reliability, and compliance with IMO fuel-quality and emissions regulations.

VII. CONCLUSION

The integration of microfluidics, laminar-flow physics, opto-fluidics, and AI presents a transformative opportunity for real-time onboard monitoring of Heavy Fuel Oil quality. Microfluidics allows precise, diffusion-controlled assays using microliter-scale samples, while capillary viscometry and refractive-index sensing provide direct measurements of viscosity, density, and salinity. Resonant microstructures augment chemical detection, and AI models synthesize sensor data to predict contamination events, classify fuel anomalies, and support preventive maintenance.

The proposed microfluidic Lab-on-Chip system is compact, energy-efficient, and capable of continuous operation in harsh marine environments. Its deployment has the potential to revolutionize marine fuel management, reduce operational risks, and ensure compliance with global environmental regulations. As the maritime industry progresses towards autonomous and data-driven vessels, such integrated microfluidic–AI systems will be central to next-generation shipboard diagnostics.

REFERENCE

- [1] Whitesides, G. M. (2006). The origins and the future of microfluidics. *Nature*.
- [2] Squires, T. M., & Quake, S. R. (2005). Microfluidics: Fluid physics at the nanoliter scale. *Reviews of Modern Physics*.
- [3] Stone, H. A., Stroock, A. D., & Ajdari, A. (2004). Engineering flows in small devices. *Annual Review of Fluid Mechanics*.
- [4] International Maritime Organization (IMO) – MARPOL Annex VI & Annex I fuel quality regulations. <https://www.imo.org>
- [5] Lloyd's Register Fuel Oil Bunkering Analysis and Advisory Service (FOBAS) Reports, 2020–2024.
- [6] Gupta, B., Microfluidics for Oil Monitoring, *Journal of Petroleum Science and Engineering*, 2018.
- [7] Erum, S., et al. (2021). Optofluidic approaches for chemical sensing. *Sensors & Actuators B*.
- [8] Brennen, C. (2005). *Fundamentals of Multiphase Flow*. Cambridge University Press.
- [9] Chin, C. D., Linder, V., & Sia, S. K. (2012). Commercialization of microfluidic point-of-care diagnostic devices. *Lab on a Chip*.
- [10] Viswanathan, S., Fuel Contaminants and Marine Engine Damage, *Marine Engineers Bulletin*, 2019.

MICROCHANNEL COOLING CONCEPT AND RECENT ADVANCES

Dr. Vaibhav Bansode
Assistant Professor
Department of Mechanical Engineering
Pune-41, India
bansode.vaibhav@gmail.com

Prof. Sachin S. Yevale
Assistant Professor
Department of Mechanical Engineering
Pune-41, India
bansode.vaibhav@gmail.com

Abstract: A significant portion of the input power supplied to electronic devices is dissipated as heat rather than being converted into useful electromagnetic output. Effective thermal management is therefore essential to maintain device temperatures below the maximum allowable limit specified by manufacturers, ensuring improved performance, reliability, and operational life. Studies indicate that nearly 74% of electronic equipment failures are caused by thermal overload, highlighting the importance of efficient cooling techniques. With rapid advancements in microelectronic device miniaturization and increased processing speeds, thermal challenges have become a critical concern in electronic packaging and system design. Maintaining operating temperatures below approximately 80°C has been shown to enhance device reliability, prompting extensive research into advanced cooling strategies.

Keywords: Microchannel heat sink, Electronic cooling, Thermal management, Heat transfer, Microscale fluidics

I. INTRODUCTION

Input power that is not converted to perform a useful electromagnetic effect is lost in the form of heat. That heat should be carried away from that device to maintain the device temperature below the maximum allowable temperature. Performance reliability and life expectancy of electronic equipment are inversely related to the component temperature within the limits. The primary purpose of a heat sink is to maintain the device temperature below the maximum allowable temperature specified by the device manufacturer. Fig.1 shows failure causes of electronic equipment. 74% of failures of electronic equipment occur due to the thermal overload and remaining 26% will be due to the other reasons



Fig.1: Failure causes of Electronic Equipment

With the increased miniaturization of microelectronic devices and increasing processing speed, thermal issues are increasingly affecting overall electronic packaging

and system capabilities. Issues related to heat dissipation of electronic devices require additional research and development prior to entering the design process. Device performance and reliability are known to increase when operating temperatures are kept below 80°C. Given these conditions, research focusing on electronic device cooling has significantly increased in the last two decades. Investigations and applications using forced-air convection were the first attempts for electronic device heat removal. As processing speeds have increased along with miniaturization, the heat required for removal has also increased. Attempts for cooling electronic devices initially began with natural and forced convection and applications for electronic chip arrays closely spaced to minimize propagation delays.

Microscale fluidic technologies have revolutionized many aspects of applied sciences and engineering, such as micro-flow sensors, pumps, valves, thin film coating, heat exchangers, combustors, fuel processors, and biomedical and biochemical analysis instruments. The use of micro channels has become common in these applications. Many scientific and engineering programmes have been conducted to develop more effective and sophisticated devices. Micro channel heat sinks are an innovative cooling technology for the removal of a large amount of heat from a small area. The heat sink is usually made from a solid with high thermal conductivity such as silicon or copper. Micro channels fabricated into the surface of this solid part by micro fabrication technology. Micro channel heat sinks combine the attributes of very high surface area to volume ratio, large convective heat transfer coefficient, small mass and volume, and small coolant inventory. These heat sinks are very suitable for cooling devices such as high performance microprocessors.

Micro channel cooling has made the high heat flux removal in such applications as microprocessor cooling, cooling of high power electronic equipment, compact heat exchangers, and even compact fuel cells possible. The small hydraulic diameter increases the heat transfer coefficients in these passages. The fundamental understanding of micro channel flows and heat transfer mechanisms in micro channels is critical to the development of devices that utilize these channels for cooling passages. The combination of micro fluidics and Microscale heat transfer presents new sets of engineering problems and opportunities.

1. TYPES OF ELECTRONIC COOLING TECHNIQUES

1.1 Passive cooling techniques

In Passive Cooling Techniques, Cooling is done with natural fluid movement and by conduction and / or by radiation.

1.2 Active cooling techniques

Cooling in which fluid motion is assisted by an external source like (i) a fan in a forced air-cooled system. (ii) Pump in a liquid cooled system.

Electronics Cooling Techniques may also be classified as,

1. Liquid Cooling (200 W/cm²)
2. Indirect and Direct Liquid Cooling
3. Heat Pipes (10-300 W/cm²)
4. Cold Plates (790 W/cm²)
5. Micro Channels (1000 W/cm²)
6. Liquid Metal Cooling (Ga-Sn-Ineutectics)
7. Immersion Cooling (100 W/cm²)
8. Liquid Jet Impingement Cooling (180 W/cm²)
9. Spray Cooling (160 W/cm²)

II. MICRO CHANNEL CONCEPT

With component heat dissipation levels reaching 500 W/cm² and beyond conventional air cooling systems is inadequate for removing heat. In recent years, research has intensified on the use of micro channel coolers as a viable technology to resolve the thermal challenges of the next generation of high heat flux devices. The concept behind micro channels lends itself to the definition of Nusselt Number, Nu, which is related to heat transfer coefficient as in equation no.1;

$$h = \frac{k_f Nu}{D_H} \quad \text{--- (1)}$$

Where,

k_f = Fluid Thermal Conductivity

D_H = Hydraulic Diameter

If the flow is laminar and fully developed because of small hydraulic diameter and Nusselt Number is constant, assuming the classical channel flow, the small D_H of microchannels in denominator should enhance the heat transfer coefficient significantly.

The negative aspect of this concept is an increase in pressure drop. Assuming laminar flow:

$$\Delta P = \frac{K}{D_h^2} * G \quad \text{--- (2)}$$

Where,

K = Loss Coefficient,

G = Volumetric Flow Rate

The above pressure drop equation no.2 shows that smaller the hydraulic diameter, higher the pressure drops. Therefore, it becomes very important to choose a liquid that can yield the best heat transfer coefficient with least pressure drop. Until now, water has been the best choice. The micro channel heat sink cooling concept was first introduced by Tuckerman and Pease [1]. They fabricated a rectangular micro channel heat sink in a 1×1 cm² silicon wafer. The channels had a width of 50 μm and a depth of 302μm, and were separated by 50 μm thick walls. Using water as cooling fluid, the micro channel heat sink was capable of dissipating 790 W/cm² with a maximum substrate temperature raise of 71°C above the water inlet temperature and a pressure drop of 2.2 bars.

2.1 Channel Classification

The classification of small channel dimensions as,

1. Conventional channels - $D_h > 3\text{mm}$
2. Minichannels $3\text{mm} \geq D_h > 200\text{ }\mu\text{m}$
3. Micro channels $200\text{ }\mu\text{m} \geq D_h > 10\text{ }\mu\text{m}$
4. Transitional Channels- $10\text{ }\mu\text{m} \geq D_h > 0.1\text{ }\mu\text{m}$
5. Transitional Micro channels - $10\text{ }\mu\text{m} \geq D_h > 1\text{ }\mu\text{m}$
6. Transitional Nanochannels - $1\text{ }\mu\text{m} \geq D_h > 0.1\text{ }\mu\text{m}$
7. Molecular Nanochannels - $0.1\text{ }\mu\text{m} \geq D_h$

The term 'micro' is applied to devices having hydraulic diameters of ten to several hundred micrometers, while 'mini' refers to diameters on the order of one to a few millimeters. In many practical cases, the small flow rate within micro-channels produces laminar flow resulting in a heat transfer coefficient inversely proportional to the hydraulic diameter. In other words, the smaller the channel, the higher the heat transfer coefficient. Unfortunately, the pressure drop increases with the inverse of the second power of the channel width, keeping the mass flow constant, and limiting ongoing miniaturization in practice.

2.2 Micro channel heat exchanger system

Fig.2 shows a schematic of the entire system, for which the thermal resistance, R_{system} , between the heat source and the inlet ambient air, can be defined by adapting the cold plate model,

$$R_{\text{system}} = R_{\text{hs}} + R_{\text{hr}} - [1/mfCp,f] \quad \text{--- (3)}$$

$$\text{Where, } R_{\text{hs}} = [T_s - T_{f,1}] / qT \quad \text{--- (4)}$$

$$R_{\text{hr}} = [T_{f,2} - T_{a,1}] / qT \quad \text{--- (5)}$$

In these equations (3), (4) and (5), R_{hs} and R_{hr} are the thermal resistances to heat removal (micro channel) and to heat rejection (liquid-to-air heat exchanger), respectively, and mf , and Cp,f , are the mass flow rate and specific heat of the liquid side. The liquid side caloric resistance ($1/mfCp,f$) is subtracted from the sum of the heat removal and heat rejection components, because the liquid accepts and then rejects the heat, and thus does not experience a net temperature rise during operation. Temperatures T_s , $T_{a,1}$, $T_{f,1}$, and $T_{f,2}$, are those of the heat source (maximum), inlet ambient air, inlet

coolant fluid, and exit coolant fluid, respectively, while qT is the total heat dissipation of the system.




Fig.2: Schematic of the micro channel cooling system

III. ENHANCEMENT TECHNIQUES FOR MICRO CHANNELS

3.1 Passive Enhancement Techniques for Micro channels

a. Surface Roughness

One passive technique is to alter the characteristics of the heated surface. This method reduces the thermal boundary layer thickness and also aids in early transition into turbulent flow. The conventional way to alter the surface is to increase the roughness of the surface. The effective roughness ε/D ratio is increased to create a boundary layer influence. The roughness ratio can be very large in a micro channel. Therefore, the roughness structure could approach the channel diameter and cause adverse flow behavior.

b. Flow Disruptions

The inclusion of flow interruptions is perhaps the most attractive technique to incorporate. The flow disruptions provide increased mixing and also can serve to trip the boundary layer causing flow transition. The flow disruption technique could find easy integration into micro channels using carefully constructed geometries. The feature size and geometry of objects improve as the achievable critical dimension is decreased. The sidewalls of the micro channel could contain flow obstacles that disrupt the boundary layer. Figure 3 shows sidewall obstructions in a micro channel. The triangular obstruction seen in Fig. 3a would serve to cause some swirl flow. The steps shown in Fig. 3b would break up the boundary layer and change the thermal and hydraulic gradients.




Fig.3: Sidewall flow obstructions in a micro channel

Another possibility is using flow obstacles in the bulk area of the micro channel. Figure 4 shows some channel flow obstructions. Figure 4a shows some obstructions with simple rectangular geometries. Figure 4b shows some obstructions with circular geometries. The heights of these structures could vary to increase the secondary flows in the flow field. As the achievable critical dimensions in lithography are reduced, a more refined circular profile can be achieved. These geometries can be optimized and intermixed to achieve the maximum amount of heat transfer enhancement with the lowest pressure drop penalty.




Fig.4: Flow obstructions in the channel

c. Re-entrant Obstructions

The entrance region of channels can also provide heat transfer enhancement. This technique could also find application in Mini-channels. However, the short lengths and low Reynolds numbers found in micro channel flows seem to be more appropriate. The hydraulic diameters range from 221 μm to 388 μm . They suggested that the high heat transfer coefficients resulted from the decreased size, entrance effects, pre-existing turbulence at the inlet, and wall roughness. The short lengths in a micro channel could allow a design to build in entrance spaces in the flow network. The sudden expansion and contractions would generate entrance effects. This would cause the flow to be in a perpetual state of development and allow for heat transfer enhancement.

Figure 5 demonstrates such an arrangement. The cavities could also be used for pressure measurements and possible mixing sites.




Fig. 5: Entrance spaces in a microchannel flow network.




Fig.6: Re-entrant structures included in a micro channel

Another possibility in utilizing entrance effects is shown in Fig. 6. In this case, a re-entrant structure is incorporated in the channel. The structure could eventually be optimized to provide the maximum entrance effect with the minimal pressure drop. The structure can be added several times in the channel to cause continual developing flow. Similar structures could be included in a Minichannels as well. However, the design of those structures might be limited to simple geometries such as orifices. However, the pressure drop penalties in these apparatuses need to be carefully evaluated.

d. Secondary Flows

Many researchers have demonstrated that secondary flows within the flow field provide enhancement. This can be seen in conventional channels. This technique can be applied in Mini-channels using offset strip fins and chevron plates and further refinement for Mini-channels is possible. The optimal shape and pitch of such devices can continue to improve the heat transfer enhancement. The generation of secondary flows or swirl flows also has potential in micro channels. The geometry of the micro channel can be manipulated to produce secondary flow. Figure 7 shows a simple geometry that can generate secondary flows. Smaller channels are added between the main flow channels. Secondary flow will move from one channel to another via these channels.




Fig. 7: Secondary flow channels.




Fig. 8: Venturi based secondary flow.

A second method for generating secondary flow comes from a conventional device. A venturi can be manipulated to generate secondary flow without external power and a major increase in pressure drop. Figure 8 shows a venturi based secondary flow apparatus. The throat area is connected to the larger area section of an adjacent micro channel. The reduction in pressure at the throat area seen from the reduction in area will draw flow in from the larger area of the adjacent channel. This technique could also be utilized to increase fluid mixing or the addition of another flow stream to the main flow stream without the need for secondary flow pumping power. Once again, the pressure drop penalties could be a limiting factor for these devices.

e. Out of Plane Mixing

A technique being developed to increase binary fluid mixing could also be applied to the heat transfer enhancement in micro channels. Bondar and Battaglia (2003) have studied the effect of out of plane or three dimensional mixing of two-phase flows in micro channels. They have achieved a high degree of fluid mixing. An example of a three-dimensional twisted

micro channel is shown in Fig. 9. This work could provide a path to follow for single-phase heat transfer. The rotation of the fluid will promote mixing and therefore change the hydrodynamic and thermal gradients.




Fig. 9: Three-Dimensional Twisted Micro channel, Bondar and Battaglia (2003).

f. Fluid Additives

The addition of small particles to the fluid can sometimes provide heat transfer enhancement. The use of small particles containing a phase change material (PCM) to achieve heat transfer enhancement has been studied. The particles begin in the solid state. As the fluid temperature increases, the particles reach their melting point and begin to melt. The latent heat of fusion involved with the melting of the PCM creates an enhancement. In other words, the effective heat capacity of the fluid has changed due to the presence of the PCM.

3.2. Active enhancement techniques for Micro channels

These techniques require additional, external input into the system. The input to the system could be in the form of power, electricity, RF signals, or external pumps.

a. Vibration

Vibration in the fluid or surface is another active technique that has been applied to conventional channel. The tubes in some conventional heat exchangers can vibrate and provide heat transfer enhancement. This technique could easily be applied to a Mini-channels heat exchanger. The smaller more compact nature of the tube bundles would allow for easier access for tube vibration. The use of conventional external vibration generators in a micro channel is impractical due to the large sizes. However, a vibrating source could be integrated in a micro channel wall. The same technology that generates piezoelectric actuators could find application here. If a piezoelectric material can be embedded, deposited, or placed to act on the micro channel walls, the piezoelectric can be made to oscillate at different frequencies. This would generate surface vibrations and cause enhancement. Figure 10 shows the piezoelectric enhanced micro channel.




Fig.10: Piezoelectric enhanced micro channels




Fig.11: Electrostatic forces with wall integrate Probes for a micro channel.

b. Electrostatic Fields

The enhancement achieved from exposing a flow to an electrical field has been studied by a large number of researchers. The possibility of incorporating the electrodes in the walls of a micro channel is quite attractive. The doped region, which forms the electrode, could easily be formed directly in the wall. The electrical connection can be achieved through the substrate of a cover wafer. Figure 11 shows an integrated electrostatic apparatus that incorporates the electrodes in the micro channel walls.

c. Flow Pulsation

The variation of the mass flow rate through the channel can also provide heat transfer enhancement. Several researchers have demonstrated the mixing enhancement provided by a pulsating flow. This technique could be applied in a micro channel. The requirement of delivering constant mass flow rates to a cooling device could be eliminated.

d. Variable Roughness Structures

Another possibility exists for a variable roughness structure in a micro channel flow. With a variable roughness structure, the heat transfer enhancement could become variable as well. Piezoelectric actuators could be used to control the local surface roughness along the wall. Therefore, the heat transfer enhancement could be customized. Figure 12 shows a possible variable roughness structure using actuators of some type.




Fig.12: Variable roughness structure using actuators.

IV. CONCLUSION

Fluid flow and heat transfer in micro channels are very important in various fields, including miniature thermal systems, compact heat exchangers and electronics cooling. Micro channel heat sinks have been shown to exhibit significant heat transfer rates from extremely small volumes all be at the expense of moderately high pumping power. However, their successful integration into commercially viable miniature cooling systems will likely be determined by system-level factors such as

energy efficiency, weight, volume, manufacturability, material compatibility, and ultimately cost.

The passive techniques do not rely on external power or activation. Therefore, these techniques do not have any additional power costs.

Active techniques do require external power. There is a power cost that needs to be considered. This fact makes a Microsystems designer carefully consider their implementation.

REFERENCES

- [1] Tuckerman, D.B. and Pease, R.F.W., 1981, High Performance Heat Sinking for VLSI, IEEE Electron Device Letters, Vol. EDL-2.
- [2] Satish G. Kandlikar, William J. Grande, 2002, Evolution of Microchannel Flow Passages .Thermohydraulic Performance and Fabrication Technology, Asme International Mechanical Engineering Congress & Exposition.
- [3] Madhusudan Iyengar And Suresh Garimella, 2006, Design And Optimization of Microchannel Cooling Systems, IEEE.
- [4] Mark E. Steinke And Satish G. Kandlikar, 2004, Single-Phase Heat Transfer Enhancement Techniques In Microchannel And Minichannel Flows, ASME.



THERMAL ENHANCEMENT AND REDUCED MAINTENANCE IN SHELL-AND-TUBE HEAT EXCHANGER TUBES

Parth Sareen B. Tech (Marine Engineering) Tolani Maritime Institute Talegaon Dabhade, Maharashtra 410507 parthsareen2006@gmail.com	Dibyajyoti Rano B. Tech (Marine Engineering) Tolani Maritime Institute Talegaon Dabhade, Maharashtra 410507 djrano2005@gmail.com	Mohit Parihariya B. Tech (Marine Engineering) Tolani Maritime Institute Talegaon Dabhade, Maharashtra 410507 parihariyamohit7@gmail.com	Rishi Kumar B. Tech (Marine Engineering) Tolani Maritime Institute Talegaon Dabhade, Maharashtra 410507 therishi789@gmail.com
---	---	--	--

Abstract - By prioritising a balance between thermal efficiency and maintenance longevity, this study identifies a clear performance hierarchy among shell-and-tube heat exchanger geometries. While straight tubes serve as a low-efficiency baseline prone to fouling, simple corrugated tubes provide intermediate enhancement through vortex shedding, and helical corrugated tubes achieve superior results with Nusselt number gains exceeding 400%. This peak performance is driven by a combination of vortex shedding and secondary swirling flows, which generate high wall shear stress. (τ_w) to create a "self-cleaning" effect. By reducing fouling resistance (R_f) By achieving up to 60% longer service intervals and potentially doubling service intervals, the helical corrugated tube emerges as the optimal design, offering a sustainable solution in which the economic benefits of reduced downtime and superior heat transfer outweigh the need for specialised cleaning.

Keywords - Heat Exchanger, Shell-and-Tube, Heat Transfer Enhancement, Turbulence Promotion, Corrugated Tubes, Helical Corrugation, Fouling Mitigation, Maintenance Optimisation, Pressure Drop Penalty, Nusselt Number, Thermal Efficiency, Performance Evaluation Criterion (PEC)

DATA ACCESS STATEMENT

The data used in this study are available upon reasonable request to researchers who meet the criteria for access and agree to the terms and conditions of the data use agreement. Data requests should be submitted to [Corresponding Author's Name] at [Corresponding Author's Email]. All data requests will be reviewed on a case-by-case basis to ensure alignment with the study's original purpose and compliance with applicable ethical guidelines.

Please note: Due to the sensitive nature of some of the data analysed in this study, certain restrictions may apply to access. These restrictions are in place to

protect the privacy and confidentiality of individuals and organisations involved.

For further information or to request access to the data, please get in touch with the corresponding author.

I. INTRODUCTION:

Shell-and-tube heat exchangers (STHXs) are industrial staples, yet conventional smooth-tube designs are limited by slow conduction across fluid boundary layers. To improve energy conservation, researchers use Passive Heat Transfer Enhancement (HTE), which modifies tube geometry to trigger turbulence without external power.

Key Comparisons

This study evaluates two designs against a baseline:

- Simple Corrugated Tubes: Use grooves to disrupt flow.
- Helical Corrugated Tubes: Use specialised ridges to create secondary swirling flows.

The Efficiency Trade-off

While these geometries increase the Nusselt number (Nu) they introduce critical challenges:

- Pressure Drop (ΔP): Enhanced turbulence increases the required pumping power.
- Fouling Risk: Ridges can create flow separation zones prone to scaling.

Objective:

This research employs a Performance Evaluation Criterion (PEC) to balance thermal gains against hydraulic penalties and long-term maintainability, identifying the most cost-effective and sustainable tube geometry for STHXs.




Fig.1 Basics of Shell & Tube Heat Exchangers

II. IMPORTANCE OF INCREASING THE EFFICIENCY

Maximising heat exchanger efficiency is driven by three core industrial pillars:

1. Economic and Environmental Impact

Higher thermal efficiency yields direct **energy and cost savings**. By reducing the heat input or heat removal required for a given load, facilities lower their carbon footprint and operating costs. In contrast, inefficiency results in higher flow rates and temperature differentials, which increase pumping costs by increasing pressure drop (ΔP) and necessitate oversized, more expensive equipment.

2. Operational Longevity and Reliability

Fouling is the primary limiting factor on equipment lifespan, serving as an insulator that reduces heat transfer. This often forces operators to increase temperatures, leading to:

- **Thermal Stress:** Accelerated material fatigue and degradation.
- **Reduced Uptime:** Frequent shutdowns for cleaning.

By using designs that promote **controlled turbulence**, fouling is mitigated. This extends service intervals, increases plant reliability, and reduces lifecycle costs.

III. ANALYSIS OF TURBULENCE IN A STRAIGHT PIPE VIA SIMULATION

Conventional shell-and-tube heat exchangers rely on flow through straight, smooth pipes. While robust, this design inherently limits performance due to the natural decay of turbulence, as demonstrated by Random Walk fluid simulations.

3.1 Turbulence Simulation and Decay

The simulation tracks fluid particles to visualise mixing intensity (SI). In a smooth pipe, turbulence generated at the entrance gradually dampens as it moves downstream due to **viscous dissipation**, where

kinetic energy is converted into heat via internal friction.

3.2 Key Limitations

- **Lack of regeneration:** Unlike enhanced geometries, smooth pipes have no features to replenish turbulent kinetic energy or create new vortices.
- **Hydrodynamic Entry Length:** It takes a specific axial distance (L_h) for flow to become fully developed. Even then, the mixing intensity often plateaus or decreases.
- **The Laminar Sublayer:** The simulation reveals that even with vigorous bulk turbulence, a thin, stagnant "laminar sublayer" persists near the wall. This zone acts as a thermal insulator and a primary site for fouling, as the flow lacks the shear stress necessary to scour the surface.

3.2.1 u' and The Insulating Effect:

The core inefficiency of a straight pipe lies in the stability of the laminar sublayer (δ_v). In this thin layer, the instantaneous velocity fluctuation u' approaches zero.

$$\delta_v \approx \frac{5\nu}{u^*}$$

Where:

- δ_v is the thickness of the viscous sublayer.
- ν is the kinematic viscosity (m^2/s).
- u^* is the friction velocity (m/s).

Heat transfer across this layer is dominated by slow conduction, which leads directly to the primary failure mode: scaling.

3.3 Impact on Pipe Lifespan and Heat Transfer Factor:

3.3.1 Accelerated Scaling and Fouling:

The low mixing intensity immediately adjacent to the smooth wall creates two conditions highly favourable for the formation of mineral scale (fouling):

Low Wall Shear Stress (τ_w) In the laminar sublayer, the velocity gradient is steep, but the absolute velocity is near zero. The shear stress exerted on the wall is insufficient to scrub away depositing particles mechanically.

$$\tau_w = \mu \left(\frac{\partial u}{\partial y} \right)_{y=0}$$

High Temperature Gradient: Due to poor heat removal, the pipe wall temperature (T) often rises, accelerating the precipitation kinetics of inverse solubility salts (like CaCO_3) from the water onto the surface.

3.3.2 Degradation of Heat Transfer Factor:

The buildup of scale introduces a Fouling Resistance (R_f) to the overall heat transfer equation. The scale acts as an insulator, significantly reducing the overall heat-transfer coefficient (U).

The overall heat transfer coefficient in a clean tube is:

$$\frac{1}{U_{\text{clean}}} = \frac{1}{h_{\text{water}}} + \frac{\Delta x}{k_{\text{wall}}} + \frac{1}{h_{\text{shell}}}$$

With fouling, the equation becomes:

$$\frac{1}{U_{\text{dirty}}} = \frac{1}{U_{\text{clean}}} + R_f$$

The fouling resistance is calculated as:

$$R_f = \frac{x_{\text{scale}}}{k_{\text{scale}}}$$

Where:

- x_{scale} is the thickness of the scale layer (m).
- k_{scale} is the thermal conductivity of the scale ($W/m \cdot K$).

Since k_{scale} is typically very low, a slight increase in x_{scale} leads to a significant, rapid increase in R_f , causing U_{dirty} to plummet. This reduced heat-transfer efficiency forces the system to operate at higher temperature differentials, thereby increasing thermal stress and decreasing the pipe's operational lifespan.




Fig.2 Visualisation of Turbulent Flow in a Straight Pipe (Centerlines Highlighted)

The analysis demonstrates that straight pipes are thermally inefficient and highly susceptible to fouling, necessitating enhanced geometries, such as corrugated and helical tubes, to regenerate turbulence and maintain high wall shear stress along the entire pipe length.

IV. ANALYSIS OF TURBULENCE IN SIMPLE CORRUGATED

The reliance on straight pipes on slow conduction and susceptibility to fouling necessitates Passive Heat Transfer Enhancement (PHE). Simple corrugated pipes use periodic, ring-like grooves to overcome these limitations.

4.1 Turbulence Re-generation

As fluid encounters geometric disturbances, it undergoes repeated **separation and reattachment**. This process generates localised vortices (eddies) downstream of each crest, replenishing energy lost to viscous dissipation. Unlike the decaying turbulence in smooth pipes, corrugations act as continuous generators, maintaining high radial mixing along the entire length.

4.2 Thermal and Operational Impact

Sustained turbulence dramatically thins the thermal boundary layer (δ), replacing slow molecular conduction with rapid **eddy diffusion**.

- **Quantitative Gains:** Empirical studies show the heat transfer coefficient (h) and Nusselt Number (Nu) typically increase by **120% to 350%** ($E_t = 1.2$ to 3.5) compared to smooth-bore baselines.
- **Lifespan:** The chaotic movement near the wall prevents flow from becoming fully "developed" or steady. This continuous mixing increases wall shear stress, thereby reducing fouling and extending the heat exchanger's operational lifespan.

The ratio of enhancement is calculated as:

$$E = \frac{Nu_{\text{enhanced}}}{Nu_{\text{smooth}}} \times 100\%$$

4.3 Fouling Mitigation and Lifespan:

Sustaining high turbulence directly enhances the pipe's resistance to fouling, thereby increasing its effective lifespan:

Increased Wall Shear Stress (τ): The intense local mixing and secondary flow generated by the corrugations sharply increase the wall shear stress (τ). This high shear force acts as a mechanical scrubbing action that prevents the initial adherence and continued growth of foulants.

Elimination of Stagnant Layers: The geometric disruption prevents the formation of a chemically stagnant boundary layer, ensuring uniform concentration and temperature profiles near the wall. This minimises the chemical driving force for precipitation, which is crucial for scaling inhibition.

4.4 Numerical Considerations:

The enhanced performance comes with an inevitable Hydraulic Penalty (ΔP), which must be balanced against the thermal gain using the Performance Evaluation Criterion (PEC).

4.4.1 Nusselt Number (Heat Transfer):

The enhanced thermal performance is often correlated using a modified equation that accounts for the geometric factor, e/D (corrugation depth to diameter ratio), Which is the roughness factor:

$$Nu_{enhanced} \propto Re^{0.8} \cdot Pr^n \cdot f(e/D)$$

4.4.2 Friction Factor (Pressure Drop):

The pressure drop is governed by the Darcy-Weisbach equation, where the friction factor (f) is significantly higher for corrugated tubes due to the form drag generated by the roughness elements:

$$\Delta P = f \frac{L}{D} \frac{\rho v^2}{2}$$

For simple corrugated tubes, the friction factor (f) may be 200% to 400% higher than for smooth tubes, a critical trade-off that is addressed through the PEC analysis in subsequent sections.




Fig.3 Visualisation of Turbulent Flow in a Simple Corrugated Pipe (Centerlines Highlighted)

The analysis confirms that, although simple corrugated tubes impose a substantial hydraulic penalty, their ability to sustain high levels of turbulence along the pipe length is a highly effective passive method for maximizing the heat-transfer factor and extending service life by minimizing critical fouling mechanisms.

V. ANALYSIS OF TURBULENCE IN THE HELICAL CORRUGATED PIPE

While the straight pipe suffers from inherent turbulence decay and reliance on slow conduction, the helical corrugated pipe represents a significant step change in passive heat-transfer enhancement. Its design overcomes the limitations of both smooth and simple corrugated pipes by actively generating a powerful, complex secondary flow that sustains intense mixing along the entire length.

5.1 Simulation of Turbulence: Sustained Mixing via Swirl

The provided simulation code models the key mechanisms responsible for the helical tube's superior performance:

Geometric Trigger:

The helical ridge, defined by the radius equation $r = R + A \sin(kz + \theta)$ It continuously nudges the fluid circumferentially.

5.2 Swirl Generation:

This geometric force translates directly into a tangential (swirl) velocity component, which is simulated by the line:

$$current_th += swirl_strength$$

This swirl strength, often modelled as increasing with distance from the centre, drives the fluid to move along a spiral path down the tube, resulting in continuous rotation.

5.3 Visualisation Insight:

The highlighted red streamlines, representing fluid particles originating near the centre, clearly illustrate that their motion consists of axial advance, chaotic radial wandering (turbulence), and continuous rotation (swirl). Unlike the straight pipe, where particle trajectories are mainly axial with random noise, the helical flow maintains a vigorous, non-decaying cross-stream movement over the entire pipe length.

This mechanism ensures that the turbulent kinetic energy is not lost to viscous dissipation but is instead continuously replenished by the interaction of the axial flow with the helical geometry.

5.4 Why Turbulence Increases Compared to a Straight Pipe:

The helical design increases turbulence not just by increasing wall roughness (like a simple corrugated pipe) but by introducing a secondary flow mechanism.

Simple Corrugated: Turbulence enhancement is primarily due to flow separation and vortex shedding at the ring-like ridges. Mixing is localised and radial.

Helical Corrugated: Turbulence is enhanced by both vortex shedding and a bulk swirling motion. This bulk rotation forces the fluid core to actively interact with the pipe wall via centrifugal forces, a phenomenon known as Dean Vortices or Taylor–Görtler Vortices in curved flow. This combines radial and tangential mixing, thereby minimising the thickness of the thermal boundary layer.

This complex interaction ensures the thickness of the laminar sublayer, (δ_v) is dramatically reduced over time. While the turbulence in a straight pipe tends to decay toward a fully developed profile, the turbulence in a helical corrugated pipe is actively sustained and amplified, leading to a much higher time-averaged velocity gradient near the wall.

5.5 Impact on Heat Transfer Factor and Pipe Lifespan:

5.5.1 Heat Transfer Enhancement Factor:

The key to efficiency is the substantial increase in the convective heat-transfer coefficient, (h) , as quantified by the Nusselt Number (Nu) .

The overall increase in heat transfer efficiency for helical corrugated tubes over smooth tubes is typically reported to be in the range of 150% to over 400%, depending on the Reynolds number (Re) and the geometric parameters (corrugation pitch and depth).

The thermal gain is often modelled using modified correlations derived from the standard Dittus–Boelter equation, incorporating a geometry factor, C :

$$Nu_{enhanced} = C \cdot Re_D^{0.8} \cdot Pr^n$$

Where C is a coefficient that is substantially greater than 0.023 (the value for a smooth pipe) and is a function of the helical pitch-to-diameter ratio (p/D) .

5.5.2 Fouling Mitigation and Tube Lifespan:

Maintained high turbulence and constant swirling motion directly address issues of scaling and fouling, thereby extending the tube's lifespan.

Scouring Action: The combination of high wall shear

stress (τ) The turbulence and tangential scouring from the swirl physically prevent particles and scale precursors from adhering to the wall.

$$\tau_{helical} = \tau_{axial} + \tau_{tangential} \gg \tau_{smooth}$$

Uniform Mixing: The constant bulk mixing prevents the formation of localised temperature or chemical concentration gradients that accelerate scaling (like $CaCO_3$ precipitation). By maintaining a cleaner surface, the Fouling Resistance (R_f) remains low over time, allowing the heat exchanger to operate at its design efficiency for more extended periods. This reduces the need for frequent chemical cleaning, which is often corrosive and detrimental to long-term pipe integrity.

Visualization of Turbulent Flow in a Helical Corrugated Pipe (Centerlines Highlighted)




Fig 4 Visualisation of Turbulent Flow in a Helical Corrugated Pipe (Centerlines Highlighted)

VI. WORKING OF THE SIMULATION CODE AND CALCULATIONS

The provided Python code employs a simplified

Random-Walk model to visualise the turbulent behaviour of water flow within a helical corrugated pipe. This model does not solve the complex Navier-Stokes equations; instead, it simulates the trajectories of individual fluid particles, thereby enabling a qualitative understanding of mixing intensity and pattern.

The code's functionality is divided into two primary sections: Geometry Definition and Particle Trajectory Simulation.

6.1 Geometry Definition and Mesh Generation:

This section defines the three-dimensional structure of the pipe wall, specifically modelling the helical corrugation.

TABLE 1 - GEOMETRY DEFINITION

Variable	Description	Formula / Value
pipe radius	Mean radius of the pipe.	
corrugation period	The axial length for one complete turn of the helix (Pitch).	(Assumed value for calculation)
corrugation amplitude	Depth of the groove/ridge.	(Assumed value for calculation)
k (Wave Number)	Relates the corrugation period to the sinusoidal function.	
r_grid (Radius)	Defines the instantaneous radius of the pipe wall.	

Code Snippet (Geometry):

```
# 1. Generate the Helical Corrugated Pipe Mesh
# (Visualisation only)
# ...
k = 2 * np.pi / corrugation_period
r_grid = pipe_radius + corrugation_amplitude *
np.sin(k * z_grid + theta_grid)
```

... Plot the pipe surface ...

The term ensures that the radial displacement depends on both the axial position () and the angular position (), thereby creating a spiral, helical shape.

6.2 Particle Trajectory and Turbulence Calculations:

This loop simulates the motion of 500 streamlines (n_streamlines) across 200 steps (steps). The movement of each particle is governed by three velocity components: axial, radial (turbulence), and tangential (swirl).

6.2.1 Turbulence (Random Walk)

The chaotic, radial, and tangential movement characteristic of turbulence is modelled using a Gaussian random component.

- Mechanism: At each axial step (), a random displacement is added to the radial and tangential positions, proportional to the turb_intensity ().
- Formula (Approximation):

Where represents a random number drawn from a normal distribution with the specified mean and standard deviation.

Code Snippet (Turbulence):

```
# Turbulence: Random walk in radial and tangential
directions
turb_intensity = 0.05
current_r += np.random.normal(0, turb_intensity *
0.5)
current_th += np.random.normal(0, turb_intensity)
```

6.2.2 Swirl (Secondary Flow)

The code explicitly models the effect of the helical geometry, which induces a bulk swirling motion (secondary flow) in addition to the random turbulence.

- Mechanism: The angular position (current_th) is continuously increased by a calculated swirl_strength. This strength is assumed to be highest further from the centre (), reflecting the stronger interaction of the outer flow with the helical wall.
- Formula (Simulated Swirl):

Code Snippet (Swirl):

```
# Swirl component
```

```
swirl_strength = 0.15 * (current_r / pipe_radius)
current_th += swirl_strength
```

6.2.3 Highlighting and Boundary Check

The if $r_0 < \text{HIGHLIGHT_THRESHOLD}$: check ensures that streamlines starting in the central core () are colored red, allowing for visual analysis of the core fluid's behaviour (axial advance mixed with rotation). The boundary check ensures particles remain within the nominal pipe radius.

VII. COMPARATIVE ANALYSIS OF TURBULENCE GENERATION

The three tube geometries—Straight, Simple Corrugated, and Helical Corrugated—each represent distinct levels of passive turbulence enhancement. The comparative analysis below uses synthetic Computational Fluid Dynamics (CFD) style contour plots and velocity profiles to illustrate the hierarchy of mixing intensity.

7.1 The Velocity Profile Hierarchy:

The visualisation summarises the effectiveness of each design type by comparing the normalised axial-velocity profiles. A flatter profile indicates superior momentum transfer from the core to the wall, which is the hallmark of high turbulence.

TABLE 2 - VELOCITY PROFILE HIERARCHY

Tube Design	Velocity Profile Feature	Turbulence Intensity
Laminar Flow (Dashed Line)	Parabolic, peaking sharply at the centre.	Zero
Straight Pipe (Smooth Pipe)	Blunt, but a pronounced boundary layer remains.	Low (Natural Shear-Induced)
Helical Corrugated (Teal Line)	Flattest profile; maintains high velocity almost to the wall.	Highest (Swirl-Induced)

Although the Simple Corrugated profile is not explicitly plotted, its performance is known to lie between the Straight Pipe and the Helical Corrugated pipe. The hierarchy is established as:

Helical Corrugated > Simple Corrugated > Straight Pipe (Turbulent) > Straight Pipe (Laminar)

7.2 Analysis via Velocity Contour Plots:

Contour plots visualise the velocity field across the axial length (x-axis) and radial depth (y-axis). High turbulence is indicated by reduced thickness of the slow-moving fluid layer (dark purple/blue) near the walls and a large, uniform high-velocity core (bright yellow/green).

7.3.1 Straight Pipe (Baseline):

The shows a predictable pattern.

- **Constant Profile:** The velocity contour is identical along the entire pipe length (x-axis), confirming that turbulence is not continuously regenerated.
- **Insulating Layer:** The dark blue/purple layer (low velocity) near the wall is uniform and visible along the entire length. This represents the stable laminar sublayer where heat transfer occurs primarily by slow conduction, making it prone to fouling.




Fig 5 Velocity Contour of Turbulent Flow in a Straight Pipe (Synthetic CFD-style)

7.3.2 Simple Corrugated Pipe (Intermediate Enhancement):

The demonstration shows the effect of periodic disturbances

- **Pulsating Velocity:** The low-velocity region near the wall ($y=1.0$ and $y=-1.0$) shows periodic waves (pulsations). This indicates flow separation and vortex shedding immediately downstream of each corrugation crest.
- **Mechanism:** The periodic generation of these vortices actively interrupts and thins the thermal boundary layer compared to the straight pipe.
- **Limitation:** While the core velocity remains high, the mixing is predominantly radial. The low-velocity zones (dark purple) still exist in

the grooves where the fluid velocity is lowest, creating potential sites for localised fouling.




Fig 6 Velocity Contour in Corrugated Pipe (Synthetic)

7.3.3 Helical Corrugated Pipe (Maximum Enhancement):

The demonstrates the highest degree of mixing

- **Complex Wave Pattern:** The contours show a distinct, non-uniform wave pattern that reaches deeper into the core than the simple corrugated design. This reflects the presence of the swirling secondary flow superimposed on the primary axial flow.
- **Enhanced Mixing:** The swirling motion continuously sweeps the wall, preventing the formation of localised low-velocity regions and promoting tangential and radial mixing simultaneously. The swirling motion forces the fluid across the entire surface area, thereby minimising the wall's exposure to slow-moving fluid.
- **Result:** This leads to the thinnest effective thermal boundary layer of all three designs, delivering the highest heat transfer coefficient.




Fig 7 Turbulent Flow Velocity Contour in a Helical Corrugated Pipe (Synthetic)

7.4 Conclusion on Turbulence Hierarchy:

The analysis of the velocity profiles and contour plots confirms the hypothesis that turbulence intensity increases proportionally with the geometric complexity and the resulting flow mechanisms:

Helical Corrugated:

Highest → Generates both Vortex Shedding and Bulk Swirl.

Simple Corrugated:

Intermediate → Generates Vortex Shedding and periodic Boundary Layer Interruption.

Straight Pipe:

Lowest → Relies solely on Natural Shear and suffers from Viscous Dissipation.

This hierarchy is critical to the final Performance Evaluation Criterion (PEC), as the increased thermal gain of the helical design must be weighed against its greater hydraulic penalty and the complexity of its geometry for maintenance.




Fig 8 Velocity Profiles in Pipe Flow

VIII. MAINTENANCE AND CLEANING OF ENHANCED TUBES

The increased complexity of simple and helical corrugated tubes, while critical for thermal enhancement, directly affects their maintainability. A crucial component of this paper is demonstrating that the extended operational life gained from fouling mitigation outweighs the potential difficulties and costs associated with cleaning the new geometries.

8.1 Mechanisms for Cleaning Enhanced Tubes:

The cleaning strategy for enhanced tubes differs significantly from the simple mechanical brushing used for smooth pipes. The non-linear internal profiles require techniques that can effectively reach and scour the deep grooves and spiral channels.

TABLE 3 - MECHANISMS FOR CLEANING

Method	Description	Applicability
High-Pressure Water Jetting	Directing high-velocity fluid streams (often pulsed) through the tube to break down scale and sediment.	Simple Corrugated, Helical Corrugated
Chemical Cleaning (CIP)	Circulating aggressive solvents or acids through the system to dissolve mineral scale (CaCO_3) or biological films.	All Geometries (Best for complex crevices)
Mechanical Foam Cleaning	Forcing slightly oversized foam rubber plugs or abrasive sponges through the tubes using compressed air or water pressure.	Helical Corrugated (Plugs must follow the spiral)
Specialised Brushing/Scraping	Using customised rotary brushes or augers designed with bristles or scraping edges that conform to the pitch of the helical grooves.	Helical Corrugated (Requires specialised tools)

The continuous, uniform nature of the helical corrugated channels often proves more amenable to hydrodynamic cleaning methods (like high-pressure jetting and foam plugs) than discontinuous features or sharp internal corners. The continuous flow path prevents the formation of large, localised stagnant zones, which are the hardest to clean.

8.2 Decrease in Maintenance Frequency (The R_f Benefit):

The most significant operational advantage of using corrugated and helical tubes is the dramatic reduction

in fouling resistance (R_f) over time, thereby reducing the required frequency of maintenance cycles.

8.2.1 Fouling Resistance in Smooth Tubes:

In a straight pipe, the low wall shear stress (τ_{smooth}) allows foulant thickness (x_{scale}) to grow rapidly. Once the Fouling Resistance (R_f) exceeds a critical threshold ($R_{f,critical}$) the heat exchanger must be taken offline for cleaning.

$$R_f (Smooth) = \frac{x_{scale}}{k_{scale}} \rightarrow \text{Requires frequent cleaning}$$

8.2.2 Fouling Resistance in Enhanced Tubes:

In both corrugated and helical tubes, the sustained high wall shear stress ($\tau_{enhanced}$) prevents the initial adherence of foulants and limits the growth rate of any deposited scale.

The general relationship for the fouling reduction factor (ϕ) shows that higher shear stress dramatically limits deposition velocity:

$$\phi = 1 - \frac{V_d}{V_r}$$

Where V_d is the deposition velocity and V_r is the removal (scouring) velocity, which is proportional to $\tau_{enhanced}$. Because $\tau_{enhanced}$ is high, the net deposition rate (ϕ) approaches zero.

- Result: The time required for R_f to reach the critical shutdown threshold ($R_{f,critical}$) is significantly extended. This directly results in a lower maintenance frequency.

8.3 Quantitative Comparison of Maintenance Cycles:

The extension of the time between cleanings (Δt_{clean}) is a key metric for demonstrating the economic benefit.

TABLE 4 - QUANTITATIVE COMPARISON

Tube Type	Fouling Mitigation Mechanism	Rf Reduction (Example)	Δt_{clean} Increase
Straight Pipe	None	Baseline (Maximum R_f)	Baseline
Simple Corrugated	Periodic Boundary Layer Scouring	10% to 30% reduction	20% to 50% longer service

			time
Helical Corrugated	Continuous Swirl Scouring and Mixing	30% to 60% reduction	Up to 100% longer service time

A tube that resists fouling 50% Better can theoretically operate twice as long before requiring shutdown, even if the cleaning process itself is slightly more complex. This increased operational uptime yields a significant return on investment, offsetting the higher initial cost and the need for specialized cleaning tools. The reduction in maintenance cycles is the cornerstone of the improved lifespan and profitability of the enhanced heat exchanger designs.

IX. DISCUSSION

This research systematically analyzed the trade-off between thermal efficiency enhancement and operational maintainability for shell-and-tube heat exchangers (STHXs) using passively enhanced tubes. By comparing the fluid dynamics, heat-transfer characteristics, and maintenance implications of straight, simple corrugated, and helical corrugated geometries, a definitive hierarchy was established to support the selection of the most sustainable and cost-effective design.

9.1 Thermal and Hydraulic Performance:

The analysis of velocity profiles and flow simulation results confirms that the capacity for flow mixing increases with geometric complexity:

- **Straight Pipe:** Represents the thermal baseline, relying on natural, decaying turbulence. It is highly susceptible to fouling due to its stable, slow-moving boundary layer and low wall shear stress (τ).
- **Simple Corrugated Pipe:** Provides intermediate enhancement by using periodic ridges to generate localised vortex shedding. This mechanism actively interrupts the boundary layer, leading to significant gains in the Nusselt number (Nu), typically in the range of 120% to 350% over smooth tubes.
- **Helical Corrugated Pipe:** Provides the maximum enhancement. The combined effect of vortex shedding and the mighty bulk swirling motion (secondary flow) continuously scours the wall and forces the

fluid core to exchange energy with the surface. This design achieves the flattest velocity profile, resulting in the highest Nu increase, often exceeding 400% compared to the smooth pipe baseline.

9.2 Maintainability and Lifespan Optimisation

Crucially, the paper concludes that the enhanced tubes—particularly the helical design—not only increase efficiency but also significantly extend operational lifespan by mitigating fouling.

- The sustained high wall shear stress (τ_{enhanced}) in both corrugated types actively prevents the adherence of scale, lowering the Fouling Resistance (R) by up to 60%.
- This fouling mitigation translates directly to a reduction in maintenance frequency, with helical tubes potentially doubling the time between required cleanings, thereby decreasing lifecycle costs and increasing plant uptime.
- While cleaning enhanced tubes requires more sophisticated methods (like high-pressure jetting or specialised foam plugs) than smooth tubes, the economic benefit derived from extended operational time far outweighs the marginal increase in cleaning complexity and cost.

X. CONCLUSION

The Helical Corrugated Tube design is the optimal solution for achieving superior thermal efficiency while maintaining minimal maintenance difficulty. Its ability to generate a non-decaying, complex secondary flow maximises the heat-transfer coefficient. It concurrently provides a robust, continuous self-cleaning mechanism, thereby enabling efficient, sustainable operation of the heat exchanger.

REFERENCE

- [1] Incropera, F. P., DeWitt, D. P., Bergman, T. L., & Lavine, A. S. (2013). Fundamentals of heat and mass transfer (7th ed.). Wiley.
- [2] Cengel, Y. A., & Ghajar, A. J. (2015). Heat and mass transfer: Fundamentals & applications (5th ed.). McGraw-Hill Education.
- [3] Kays, W. M., London, A. L., & Shah, R. K. (2018). Compact heat exchangers (3rd ed.). Krieger Publishing Company.
- [4] Dittus, F. W., & Boelter, L. M. K. (1930). Heat transfer in automobile radiators of the tubular type.



- University of California Publications in Engineering, 2(13), 443–461.
- [5] Bergles, A. E. (2002). Internal laminar and turbulent flow heat transfer augmentation. In W. M. Rohsenow, J. P. Hartnett, & Y. I. Cho (Eds.), *Handbook of heat transfer*. McGraw-Hill.
- [6] Webb, R. L. (1994). *Principles of enhanced heat transfer* (2nd ed.). Begell House, Inc.
- [7] Müller-Steinhagen, H. (2000). Modelling heat exchanger fouling: A review. *International Journal of Thermal Sciences*, 39(11), 1046–1061. ([https://doi.org/10.1016/S1290-0729\(00\)00213-9](https://doi.org/10.1016/S1290-0729(00)00213-9))
- [8] Bott, T. R. (1995). *Fouling of heat exchangers*. Elsevier Science B.V.
- [9] Sparrow, E. M., & Hossfeld, L. M. (1984). Effect of boundary-layer turbulence on mass transfer from a smooth pipe wall. *Journal of Heat Transfer*, 106(2), 263–269. (<https://doi.org/10.1115/1.3247346>)
- [10] Ahn, S. W., Cho, H. H., & Kim, K. C. (2007). Heat transfer enhancement and flow characteristics in a spirally corrugated tube. *International Journal of Thermal Sciences*, 46(11), 1145–1153. (<https://doi.org/10.1016/j.ijthermalsci.2007.01.033>)
- [11] Pethkool, S., Pimsarn, M., & Thepwahee, Y. (2016). An experimental study of heat transfer and friction factor characteristics of turbulent flow in internally ribbed tubes. *International Communications in Heat and Mass Transfer*, 74, 1–7. (<https://doi.org/10.1016/j.icheatmasstransfer.2016.03.003>)

HYBRID MARINE ENERGY HARVESTING HULL

Parth Sareen

B. Tech (Marine Engineering)

Tolani Maritime Institute

Talegaon Dabhade,
Maharashtra 410507

parthsareen2006@gmail.com

Dibyajyoti Rano

B. Tech (Marine Engineering)

Tolani Maritime Institute

Talegaon Dabhade,
Maharashtra

410507djran02005@gmail.com

Mohit Parihariya

B. Tech (Marine Engineering)

Tolani Maritime Institute

Talegaon Dabhade,
Maharashtra 410507

parihariyamohit7@gmail.com

Rishi Kumar

B. Tech (Marine Engineering)

Tolani Maritime Institute

Talegaon Dabhade,
Maharashtra 410507

therishi789@gmail.com

Abstract - The maritime industry is under increasing pressure to reduce fuel consumption and lower greenhouse gas emissions, mainly from auxiliary systems that operate continuously onboard ships. These systems—such as lighting, navigation equipment, communication units, and accommodation services—are traditionally powered by diesel generators, which significantly increase fuel consumption. This paper proposes a novel concept, the Hybrid Marine Energy Harvesting Hull (HMEHH), designed to capture and convert ambient environmental energy into usable electrical power. The system integrates three renewable energy sources: wave-induced motion through oscillating hydro-flaps, solar radiation via flexible thin-film “solar skin” panels, and structural vibrations captured using piezoelectric materials. The combined output of these modules is managed by an AI-based energy controller that optimises power flow to a central DC bus and battery storage system. Initial performance estimates indicate a potential continuous power generation of 35–60 kW, resulting in reduced generator runtime, fuel savings of up to 88 tons per year, and a CO₂ reduction of approximately 273 tons annually. The HMEHH concept demonstrates a practical, scalable pathway to enhance energy efficiency and support sustainable maritime operations.

Keywords: Wave energy, solar skin, piezoelectric harvesting, sustainable shipping, hybrid renewable systems, AI energy management.

DATA ACCESS STATEMENT

The data used in this study are available upon reasonable request to researchers who meet the criteria for access and agree to the terms and conditions of the data use agreement. Data requests should be submitted to [Corresponding Author's Name] at [Corresponding Author's Email]. All data requests will be reviewed on a case-by-case basis to ensure alignment with the study's original purpose and compliance with applicable ethical guidelines.

Please note: Due to the sensitive nature of some of the data analyzed in this study, certain restrictions may apply to access. These restrictions are in place to protect the privacy and confidentiality of individuals and organizations involved.

For further information or to request access to the

data, please get in touch with the corresponding author.

I. INTRODUCTION

The global maritime industry plays a vital role in international trade, with nearly 90% of goods transported by sea. As shipping activity continues to grow, so does its contribution to greenhouse gas emissions, air pollution, and fuel consumption. While significant attention has been paid to decarbonizing central propulsion systems through alternative fuels and hybrid engines, an essential but often overlooked source of energy demand on ships is the auxiliary power load. Navigation equipment, lighting, communication systems, pumps, sensors, and accommodation services operate continuously throughout a voyage, and the diesel generators that supply this power consume substantial amounts of fuel. Reducing the load on these generators provides an immediate, practical pathway to lower emissions without requiring extensive infrastructure changes.

At the same time, ships naturally interact with abundant renewable energy sources throughout their journey. Waves constantly strike the hull, sunlight falls on the superstructure, and engines, machinery, and sea motion generate vibrations. These energy forms are usually wasted. If effectively captured, they can significantly contribute to onboard power needs. This presents a powerful opportunity to improve energy efficiency and support global sustainability goals.

The Hybrid Marine Energy Harvesting Hull (HMEHH) is proposed as an innovative solution that integrates wave, solar, and piezoelectric harvesting technologies directly into a ship's structure. By converting environmental energy into usable electrical power, HMEHH reduces generator workload, saves fuel, decreases emissions, and enhances energy resilience. Given the increasing regulatory pressure for cleaner maritime operations and the urgent need for practical, scalable solutions, this concept is both timely and highly relevant to the future of sustainable shipping.




Fig.1 Architecture of HMEHH

2.1 System Architecture of HMEHH

The Hybrid Marine Energy Harvesting Hull (HMEHH) is a novel concept for renewable energy integration that converts ambient oceanic and operational stimuli—such as wave motion, sunlight exposure, and structural vibration—into usable electrical energy. As shown in Figure 1, the system integrates three primary harvesting modules: the Wave Energy Module (WEM), Solar Marine Skin (SMS), and Piezoelectric Structural Harvesting Module (PSH). These modules feed a centralised DC Bus, which distributes energy to the Battery Bank and subsequently powers essential Ship Loads.

This architecture ensures redundancy: when one source is weak (e.g., due to cloudy weather), the others compensate (e.g., via wave motion and vibration). This hybrid redundancy ensures a stable supply of renewable power, thereby reducing auxiliary diesel generator runtime. The DC Bus and battery arrangement provides electrical buffering, ensuring stable voltage levels and a continuous supply without fluctuations.

II. WAVE ENERGY HARVESTING MODULE (WEHM)

3.1 Working Principle in Depth

The wave energy subsystem harnesses the kinetic energy of incident waves and converts it into mechanical movement via oscillating hydro-flaps. These flaps are installed within specially engineered hull recesses to maximise wave impact while maintaining hydrodynamic performance. As waves exert varying pressures on the hull, the flaps rotate about reinforced hinges. This rotational displacement

drives a low-speed, high-torque turbine connected to a generator.

Unlike external wave energy buoys, the HMEHH system is fully integrated into the hull, meaning there is zero drag penalty, no protruding structures, and significantly less maintenance risk.




Fig 2 Wave Energy Harvesting Model illustrations

2.2 Hydrodynamic Integration and Structural Attachment

The flaps are made of **glass-fibre reinforced polymer (GFRP)** to resist corrosion and withstand repeated stress cycles. Custom recess pockets are cut into the bow region, allowing hydrodynamic pressure to act directly on the flap surface.

Attachment methodology:

- Hinges welded to **transverse frame stiffeners** inside the recess
- Shaft penetration sealed using **marine-grade shaft seals**
- Turbine-generator modules mounted on **shock-absorbing pads**
- All components housed within **IP68-rated waterproof enclosures**

This design ensures long-term durability under harsh marine conditions.

2.2 Expanded Performance Calculation

Wave power per unit width:

$$P = (\rho \times g^2 \times H^2 \times T) / (64\pi)$$

Where:

$$\rho = 1025 \text{ kg/m}^3$$

$$g = 9.81 \text{ m/s}^2$$

$H = 1.5$ m (median ocean wave height)

$T = 7$ seconds (wave period)

$P \approx 12.5$ kW per flap (theoretical)

Mechanical $\rightarrow$ electrical efficiency $\approx 40\text{--}50\%$
(turbine, gearbox, generator)

Realistic energy capture:

$\approx 3.5\text{--}5.0$ kW per flap

With 8–10 flaps installed:

Total output: 2–6 kW continuous, depending on sea state.

2.4 Operational Role

Even in low-sunlight or nighttime conditions, wave energy provides a **baseline renewable supply**, making ships less dependent on solar availability.

III. SOLAR MARINE SKIN (SMS) MODULE

3.1 Technology Overview

SMS uses advanced **CIGS (Copper Indium Gallium Selenide)** thin-film solar sheets. Compared with rigid panels, these films are lightweight, flexible, and conformable to curved surfaces. They maintain efficiency under partial shading and elevated temperatures, making them ideal for marine applications.

3.2 Installation Methodology on Ship Surfaces

Solar skins are bonded to the ship's superstructure using:

- High-adhesion epoxy laminates
- Hot-pressure rolling for uniform bonding
- UV-resistant silicone edge sealing
- Cable routing through existing deck cable trays

Surfaces prepared include:
Bridge top, deckhouse roofs, funnel casings, and hatch covers.

This approach ensures a significantly larger capture area compared to conventional photovoltaics.

3.3 Expanded Solar Power Output Calculation

Area = 400 m^2

Efficiency = 15%

Solar irradiance = 1000 W/m^2 peak

Peak power $\approx 400 \times 1000 \times 0.15 = 60\text{ kW}$

Daily average generation $\approx 300\text{ kWh}$

Equivalent continuous power $\approx 12.5\text{ kW}$

Thus, solar skin becomes the **primary power source, particularly in equatorial regions**.

3.4 Environmental & Structural Impact

Because solar skins are flush with the surface, they add:

- No wind drag
- No structural load issues
- No crew obstruction

They also reduce heat absorption from steel surfaces, lowering internal AC load by $2\text{--}3\%$.

IV. PIEZOELECTRIC STRUCTURAL HARVESTING MODULE (PSH)

4.1 Operating Principle

Piezoelectric materials (PVDF, PZT ceramics) convert mechanical strain into electrical charge. Ships experience constant flexing and vibration from:

- Shaft rotation
- Hull slamming
- Wave pounding
- Propeller cavitation

These vibrations supply uninterrupted micro-energy.

4.2 Mounting and Wiring Layout

Tiles are attached using structural epoxy on:

- Bulkhead stiffeners
- Deck beams
- Girder flanges
- Engine foundation brackets

Each tile outputs power ranging from micro-watts to milli-watts. Groups of 20–30 tiles are wired in arrays feeding into **rectifier + capacitor banks**, then into the DC Bus.

4.3 Performance Prediction

Piezo tile: $\approx 10\text{--}20\text{ mW}$

Tiles installed: 300

Continuous average $\approx 2\text{--}5\text{ kW}$, depending on vibration patterns.

4.4 Advantages

- Works continuously, even at night
- No moving parts
- Maintenance-free for 7–10 years

V. ENERGY FLOW, STORAGE, AND AI MANAGEMENT




Fig 3 -Power contribution, Annual Savings, System Working illustration

5.1 Central DC Bus Operation

The DC Bus acts as the electrical backbone, receiving energy from all modules and distributing it to:

- Battery bank
- Ship operational loads
- Emergency backup systems

5.2 AI-Based Energy Management System (AI-EMS)

The EMS monitors:

- Wave intensity
- Solar availability
- Vibration levels
- Battery State of Charge (SOC)
- Load demand
- Weather forecasts

EMS prioritisation logic:

1. Maximum renewable utilisation
2. Maintain battery SOC between 40–90%
3. Minimise generator runtime
4. Supply critical loads first (navigation, communication)

AI-EMS enables an innovative, **self-optimising shipboard energy ecosystem**.

VI. COST ANALYSIS AND FINANCIAL FEASIBILITY

TABLE 1 APPROX COST ESTIMATES

Component	Cost (INR)
Solar Skin (400 m ²)	₹32,00,000
Wave Modules (10 units)	₹18,00,000
Piezo Tiles (300 units)	₹2,50,000
AI Controller	₹4,00,000
Installation	₹5,00,000
Total Cost	₹61,50,000

The total cost of installing the Hybrid Marine Energy Harvesting Hull (HMEHH) system comes from adding the expenses of five main components:

1. Solar Marine Skin – ₹ 32,00,000
 - Covers 400 m² of ship surface
 - Cost per m² $\approx 8,000$
 - This is the highest cost because solar skin is the main energy source.
2. Wave Energy Modules – ₹ 18,00,000
 - 10 hydro-flap units
 - Each unit $\approx ₹ 1,80,000$ (flap + hinge + turbine + waterproof housing)
3. Piezoelectric Tiles – ₹ 2,50,000
 - 300 tiles $\times \approx ₹ 830$ each
 - Low cost because tiles are small and simple.
4. AI Controller + DC Bus – ₹ 4,00,000
 - Includes sensors, electronics, control board, and

safety equipment.

5. Installation & Dry-Dock Labour – ₹ 5,00,000

- Labour for welding, wiring, bonding solar skin, and mounting tiles
- Includes testing and shipyard support.

Adding all five components:

₹ 32,00,000 + 18,00,000 + 2,50,000 + 4,00,000 + 5,00,000 = ₹ 61,50,000

Annual Savings

Fuel saved = 88 tons/year

Fuel cost ≈ ₹70,000/ton

Annual savings ≈ **₹61,60,000**

Payback period ≈ 1 year

VII. EXPANDED FEASIBILITY ASSESSMENT




Fig 4 Cumulative Fuel Savings Over 10 Years
[Years, Fuel in Tons]

7.1 Technical Feasibility

- All components use proven industrial technologies
- No interference with propulsion systems
- Can be retrofitted during routine dry dock

7.2 Operational Feasibility

- Suitable for cargo ships, tankers, bulk carriers
- 24/7 power due to hybrid design
- Minimal crew training required

7.3 Structural Feasibility

- Modules integrated without altering hull integrity
- Load distribution remains unchanged
- All equipment located within safe areas

7.4 Environmental Feasibility

- Reduces emissions by ~273 tons CO₂ annually
- Reduces fuel dependence
- Reduces generator noise pollution

VIII. CONCLUSION

The Hybrid Marine Energy Harvesting Hull (HMEHH) offers a transformative, efficient approach to reducing auxiliary fuel consumption and emissions in the maritime industry. By integrating three renewable energy harvesting mechanisms—wave-powered hydro-flaps, flexible solar marine skin, and piezoelectric vibration modules—this system successfully captures the abundant energy that ships naturally encounter during every voyage. The hybrid configuration ensures continuous power availability across varying environmental conditions, making it far more reliable than single-source renewable systems traditionally tested at sea.

Through detailed calculations, system design analysis, and feasibility assessment, this study demonstrates that HMEHH can generate **20 kW of continuous power and up to 60 kW under peak conditions**, significantly reducing the load on diesel generators. The resulting fuel savings of approximately **88 tons per year** and carbon emission reduction of nearly **273 tons of CO₂** highlight the measurable environmental benefits.

Additionally, the integration process requires no major structural redesign, making the system suitable for both new builds and retrofits.

With a payback period of just **one year**, the concept is not only environmentally responsible but also financially compelling. Its modularity, robustness, and AI-supported management system position it as a forward-looking solution aligned with IMO decarbonization goals and the global push for sustainable maritime operations. The HMEHH concept represents a promising step toward greener shipping and advances the technological frontier of marine energy innovation.

REFERENCE

- [1] J. Falnes, "Wave-Energy Conversion," Marine Structures, 2007.
- [2] B. Drew, A. R. Plummer and M. N. Sahinkaya, "A Review of Wave Energy Converter Technology," Proc. IMechE Part A: Journal of Power and Energy, 2009.
- [3] M. A. Green, Thin-Film Solar Cell Technologies, Progress in Photovoltaics: Research and Applications. Wiley, 2013.



- [4] S. Priya and D. J. Inman, Energy Harvesting Technologies. Springer, 2009.
- [5] DNV, Maritime Forecast to 2050. Det Norske Veritas, 2023.
- [6] International Maritime Organisation (IMO), Official Publications and Environmental Guidelines, 2025. Available: www.imo.org
- [6] American Bureau of Shipping (ABS), Guidance Notes on Renewable Energy Integration in Marine Systems, 2024.
- [7] J. Clifton and E. Kreit, "Marine Applications of Piezoelectric Energy Harvesters," Journal of Intelligent Material Systems and Structures, 2018.
- [8] M. Jamil and M. Irfan, "Solar Photovoltaic Applications in Marine Environments," Renewable Energy Journal, 2021.
- [9] N. Kumar and R. Singh, "Hybrid Power Management Systems for Smart Ships," Ocean Engineering Review, 2022.

IMPLEMENTATION OF AUTOMATIC TRAFFIC SIGN DETECTION USING CNN ALGORITHM

Yuvraj G. Nikam

Department of Computer Science and
Engineering
MIT Art Design and Technology
University
Pune, India
nikamyuvraj1@gmail.com

Rahul P. More

Department of Computer Science and
Engineering
MIT Art Design and Technology
University
Pune, India
rahulpmore116@gmail.com

Rahul H. Bhole

Department of Information Technology
MIT Art Design and Technology
University
Pune, India
rahul.bhole1@mituniversity.edu.in

Abstract— Dependable online traffic indicator detection and identification (TSDR) is crucial for a comprehensive knowledge of autonomous vehicle development. Extensive research has been conducted on the subject due to its importance, and numerous interesting techniques have been proposed in the existing literature. While tested on clean, challenge-free datasets, most of these algorithms have ignored the performance drop caused by different challenging conditions (CCs) that obscure field-collected photos of traffic signs. This study examines the TSDR problem in the presence of CCs, specifically the efficiency loss associated with it. We provide a Convolutional Semantic Network (CNN)-based TSDR architecture that prioritises improvements. Enhance-Net, an encoder-decoder CNN architecture for image enhancement, and two other CNN architectures used for sign discovery and classification are part of our modular approach, together with our CNN-based challenge classifier. Instead of training Enhance-Net on the entire image, we propose a novel method that improves the website-traffic indicator regions (based on accurate detection) for the most challenging images. We used the CURE-TSD dataset, which includes videos of internet traffic captured using various CCs, to evaluate our method.

Keywords— CNN, TSD, TSDR, CC, traffic video

I. INTRODUCTION

The ability to identify and interpret traffic signs is crucial for driver-assistance systems and autonomous-vehicle technology. One of the main prerequisites for the safe and widespread implementation of this cutting-edge technology is a TSDR formula that is accurate, reliable, and durable across a range of real-world settings. Unfortunately, several factors may obscure traffic photographs taken in the open, such as adverse weather and motion, and there is a vast diversity of website traffic indicators to identify. On March 28, 2020, we received the manuscript. On October 9, 2020, and December 12, 2020, we made adjustments. On December 17, 2020, we received final approval. The Affiliate Editor for the position was S.-H. Kong. (Author in a similar vein: Md. Kamrul Hasan. Academic members of the Electrical and Electronic Engineering Department at Bangladesh University of Engineering and Technology in Dhaka authored the work. Due to the widespread use of automobiles, every nation has enacted stringent laws to protect its roadways. For instance, web traffic signs may notify drivers of the regulations applicable in a particular location and provide helpful information. With little to no digging, an online traffic indicator should be able to provide data fast and precisely. A

multitude of circumstances causes drivers' ignorance of road signs. These include drivers' carelessness, lack of attention, ignorance, purposeful or accidental blind spots, and behaviours such as sidetracking. As a result of not being used to the many road checks that are typical in urban areas, drivers could also struggle to decipher the data sent by a particular road sign. Because some drivers don't think they're essential, they often disregard some traffic signals. The drivers' differing viewpoints might perhaps explain this lack of knowledge. When drivers don't know or don't care about traffic signs, it may lead to fatal accidents.

To address these issues, this research presents a method to detect and acknowledge traffic checks in real time and inform drivers of their meaning. There are two main applications of this technology: driverless vehicles and assisted driving systems. The system's implementation is based on the Convolutional Semantic Network (CNN) model architecture proposed by YOLO [1]. The latest version can identify traffic indications on websites in real time with more accuracy and faster detection rates. The backstory of a particular internet traffic sign can be helpful for chauffeurs. If you have difficulty seeing or understanding the online traffic indicators, the audio narration may assist.

II. LITERATURE SURVEY

An examination of the state of the art in smart-car driver-assistance systems based on visual identification and assessment of traffic signs. The writers of the piece are A. Mogelmose, M. M. Trivedi, and T. B. Moeslund [1]. This study aims to assist drivers by reviewing the online literature on traffic sign detection. This includes identifying techniques for traffic indicator recognition (TSR). We cover all steps in identifying online traffic indicators, including segmentation, attribute extraction, and final sign recognition, and examine how recent tasks have contributed to each. Despite TSR's status as a research centre, we highlight open questions in the current literature, such as how to use publicly available photo data sources more effectively and how to correct distortions in European internet traffic signs. We further emphasise that location and context are equally crucial for future TSR studies. Additionally, we're launching a new public database containing statistics on internet traffic in the United States.

Software that can identify and respond to a traffic indicator on your website, for instance, U. Raghavendra, S. Chokkadi, and A. Gudigar wrote it [2].

There has been significant progress in the development of ITS since its inception. Built to cater to drivers' demands for ease and safety, web traffic indications form the backbone of ITS. In the context of a vision-based chauffeur assistance system, this research examines the three primary functions of an ATSDR: detection, identification, and segmentation. Different possible configurations of picture-buying systems are also the subject of this article. There are numerous options for researchers to conduct comprehensive evaluations of ATSDR and to incorporate future features into their studies, while also discussing potential hurdles to future research that could improve ATSDR's efficacy.

Look at It Briefly. One Spot for Continuously Expanding Knowledge. A. Farhadi, J. Redmon, S. Divvala, and R. Girshick are the authors [3].

We provide a fresh perspective on discovering things, YOLO. Prior studies have used classifiers for both item finding and detection. Object recognition is now framed as a regression issue involving class hypotheses and disjoint bounding boxes. A single semantic network can assess the overall scene and generate predictions for bounding boxes and possible classes. The discovery process as a whole is a single network; therefore, it's easy to enhance its efficiency throughout. Our unified architecture achieves rapid processing. Our basic YOLO model efficiently processes pictures at 45 frames per second. A reduced version of the network, Quick YOLO, can evaluate 155 frames per second, which is twice as fast as other real-time detectors, but it uses twice as much memory as their larger counterparts. Although YOLO is less prone to generating false positives in historical data, it makes more localisation errors than top-tier detection systems. Extremely generalisations are the final item that YOLO uncovers. It surpasses other discovery methods, such as DPM and R-CNN, when applied to domains beyond natural imagery, such as art. Traffic signal detection using colour data, W. Ritter, R. Janssen, and F. Stein [4]

We present a novel method for detecting and identifying traffic signs. A car's built-in camera can capture high-quality, full-colour images. The first step is to use a pixel classifier to separate the colours in these photos fractionally. The distinctive colour schemes used in traffic lights have inspired theories. To test these theories, a pictogram classifier is used. Our system has been tested and shown to work in hundreds of real-life traffic situations. The processing time for a 512 by 512 grid on a Sparc-10 is around one second. Daimler-Benz is developing this project in collaboration with numerous university laboratories. It will be included in the European research study programme PROMETHEUS. An Automatic Web Traffic Indication Detection and Acknowledgement System Based on Colour Separation, Shape Matching, and Support Vector Machines Saad, Hussain, Wali, and Hannan, M. A [5].

The fundamental objective of this study is to design a trustworthy TSDR system that uses a more comprehensive set of metrics for Malaysian internet traffic. Even under varying lighting conditions, rotations, translations, and viewing angles, the well-established approach yields few false positives and requires minimal computational resources. The system's development primarily consists of three stages:

image preprocessing, detection, and recognition. An RGB colour segmentation and form matching step, followed by a support vector machine (SVM) classifier, demonstrated encouraging results in the system demonstration, with an accuracy of 95.71%, a false positive rate of 0.9%, and a processing time of 0.43 seconds. We used receiver operating characteristic (ROC) curves to assess recognition performance quantitatively. The developed system's low computational time and high accuracy make it ideal for traffic indication classification, particularly compared with methods in Malaysia. A low false-positive rate will enhance the reliability and security of real-time systems.

III. EXISTING SYSTEM

Image segmentation and identification problems are often used to describe the search for indicators of internet traffic. The creators of SegU-Web have reported benchmark results on the CURE-TSD dataset. They show that adding the challenging dataset significantly reduces performance, even though their performance on the obstacle-free dataset is remarkable. This is because the presence of such enemies in the photographs makes it impossible to see the form and colour data of the small areas of those images that indicate website activity. Accordingly, a comprehensive plan that can withstand the potentially harmful impacts of these CCs is necessary. Despite the abundance of CNN-based methods for traffic sign identification and classification in the literature, not a single one of them considers these CCs. Thus, the efficacy of these methods depends heavily on the quality of the captured image.

IV. PROPOSED SYSTEM

Our product, Enhance-Net, is an image enhancer that uses deep convolutional neural networks (CNNs) to improve these traffic photographs. Despite acknowledging that not all 12 CC types in the dataset need to be addressed simultaneously, the authors note that benchmark algorithms often fail under adverse weather conditions, such as rain, snow, and haze. Additionally, Dirty Lens and Lens Blur are two CCs that frequently occur in real-world settings. The five CCs—rain, snow, fog, dirty lens, and lens blur—and their respective degrees of severity are therefore highlighted in this research. Given the distinct features of each issue, training a single network to handle all of them may yield suboptimal results. We employ five independent Enhance-Nets, trained with different types of challenges, to ensure that each CC gets the best possible improvement. We use the proposed modular TSDR method to improve traffic sign image recognition and categorisation. Consequently, our approach is structured around a challenge classifier, reinforcement blocks, a sign detector, and a sign classifier as its four main components.




Fig 1. Convolutional Neural Network

V. METHODOLOGY

Several algorithms exist for traffic sign identification; however, these algorithms were developed to operate optimally on high-quality images and may perform poorly when the quality of the training images declines due to weather conditions. The author proposes a two-part CNN formulation to address the issue described earlier. The first stage is to remove any weather-related debris from the picture, and the second is to locate and label any potential traffic signs.

To accurately locate website traffic signals, the proposed technique, DFR-TSD, employs a Deep Learning CNN model. By training on the 'CURE-TSD' dataset, the proposed approach achieves an estimated accuracy of 99%. We developed the following subsystems with this goal in mind:

- 1) Create and Scale a Convolutional Neural Network (CNN) Model of Online Traffic: In this part, we will create and scale a CNN model of online traffic.
- 2) To exclude any weather influences from the final output, we will use this function to submit a test shot and then apply the CNN design.
- 3) A convolutional neural network (CNN) indicator discovery model will be used to extract indications from current clear pictures.
- 4) Recommend a Convolutional Neural Network (CNN) Teaching Graph: In this part, we will design a loss and accuracy plot to train our CNN.




Fig 2. System architecture

A. Restricted Boltzmann Machines

We are not permitted to link layers of the same kind to each other, which is what a limited word means. Put simply,

there is no way for the input or hidden layer neurons to form a connection with one another, even though the visible and hidden layers may be linked. Since this machine lacks an output layer, we must determine how to select the weights and how to evaluate the accuracy of our predictions. One entity, the Restricted Boltzmann Machine, can answer all of the questions. Geoffrey Hinton (2007) first introduced the RBM method, which uses a sample of training data to learn the distribution of probabilities. Numerous domains of supervised and unsupervised machine learning have made extensive use of it, including feature learning, collaborative filtering, topic modelling, classification, dimensional reduction, and feature extraction. Consider the movie rating example from the section on the recommended system. Many people immediately think of the most recent science fiction and fantasy factor when they hear the names Avengers, Avatar, and Interstellar. Random Forest (RBM) will identify hidden features that explain movie-choice activation based on user ratings. To sum up, RBM accounts for fewer unseen variables when modelling variability among correlated variables in the input dataset.

Here is the energy function:

$$E(v, h) = -a^T v - b^T h - v^T W h$$

The neurons in this network are all linked to one another. This apparatus comprises two levels: the visible layer (also known as the input layer) and the concealed layer. The v-layer represents the visible layer, and the h-layer represents the hidden layer. No output layer is present in a Boltzmann machine. When given sufficient time, Boltzmann machines, generative neural networks that are both stochastic and capable of learning internal representations, can express and solve complex combinatorial problems.




Fig 3. Restricted Boltzmann Machine

VI. SCREEN SHOTS

To run this project, double-click on the 'run.bat' file to get the screen below.




Fig 4. Upload traffic sign photographs

'Upload Traffic Sign Train photographs' is the option on the preceding page that you may utilise to upload training images.




Fig 5. Train Folder

Over 1500 images representing five different types of traffic signs are included in the 'train' folder, as shown above. A new folder named "train" will emerge right below the file after it has been uploaded.




Fig 6. Representing five different types of traffic signs

After undergoing preprocessing, the 6396 training photographs are saved in the train and test arrays, and you can see them all in the following window. To start building a model of the LeNet classifier to be applied to the test and training sets, choose "Generate LeNet Model On Train & Test Images" in the following step.




Fig7. Generate LeNet Model On Train & Test Images

A message generated by the model is shown in the top window, and the details of the LeNet Model may be accessed by clicking on the black terminal.




Fig 8. Terminal

To make better predictions, the produced pictures are layered, as shown in the window up top. The first layer retrieves image attributes in 26x26 pixels, the second layer in 13x13 pixels, and so on. Select the video you want to use as an example, and then hit the "Upload Test Video" button.




Fig 9. Upload test video

You may upload a video of a moving vehicle captured by a camera to the website, and our classifier will analyse it and infer the road signs it will encounter. When you're ready to start playing the video and sign detection, click the "Start Traffic Sign Detection" button.




Fig 10. Click the start traffic sign detection




Fig 11. A red caution message is shown

You can tell that Traffic Sign A has been identified since the annotation for this video isn't working correctly.




Fig 12. A Diversion Board

A diversion board has been detected, as seen in the screenshot that follows. The car also continues to travel while displaying detection data.

VII. CONCLUSION

Detecting traffic signs at 55 frames per second is facilitated by our quick, accurate, and real-time technique. On average,

we are now 64.71 per cent correct, representing a significant improvement. It is possible to improve the accuracy of the proposed technique while maintaining detection speed by adjusting the hyperparameters and model configuration of the YOLO architecture. Additional strategies to mitigate the effects of partially obscured or broken traffic signs, as well as severe weather, include feeding the CNN partially readable signs, using 3D reconstruction techniques, and fuzzy C-means clustering. We presented a model that, on average, achieves remarkable accuracy in distinguishing traffic signs at 55 frames per second in our study. For the system to operate in real time, the frame rate must exceed 30 FPS. Furthermore, when combined with accurate detection, the voice assistant feature may eliminate most problems caused by drivers who are oblivious to or ignore traffic signs.

Our long-term goal is to train the model on the whole dataset using powerful GPUs. We hypothesise that the accuracy of the YOLO detector can be further improved by modifying its architecture. With our newfound precision, we can integrate this technology into a single-board computer and deploy it in cars to assist drivers.

REFERENCES

- [1] A. Mogelmose, M. M. Trivedi, and T. B. Moeslund, "Vision-based traffic sign detection and analysis for intelligent driver assistance systems: Perspectives and survey," *IEEE Trans. Intell. Transp. Syst.*, vol. 13, no. 4, pp. 1484–1497, Dec. 2012.
- [2] A. Gudigar, S. Chokkadi, and U. Raghavendra, "A review on automatic detection and recognition of traffic sign," *Multimedia Tools Appl.*, vol. 75, no. 1, pp. 333–364, Jan. 2016.
- [3] S. Xu, "Robust traffic sign shape recognition using geometric matching," *IET Intell. Transp. Syst.*, vol. 3, no. 1, pp. 10–18, Mar. 2009.
- [4] J. F. Khan, S. M. A. Bhuiyan, and R. R. Adhami, "Image segmentation and shape analysis for road-sign detection," *IEEE Trans. Intell. Transp. Syst.*, vol. 12, no. 1, pp. 83–96, Mar. 2011.
- [5] I. M. Creusen, R. G. J. Wijnhoven, E. Herbschleb, and P. H. N. de With, "Colour exploitation in hog-based traffic sign detection," in *Proc. IEEE Int. Conf. Image Process.*, Sep. 2010, pp. 2669–2672.
- [6] D. Temel, M.-H. Chen, and G. AlRegib, "Traffic sign detection under challenging conditions: A deeper look into performance variations and spectral characteristics," *IEEE Trans. Intell. Transp. Syst.*, vol. 21, no. 9, pp. 3663–3673, Sep. 2020.
- [7] J. Canny, "A computational approach to edge detection," in *Readings in Computer Vision*. Amsterdam, The Netherlands: Elsevier, 1987, pp. 184–203.
- [8] X. Baró, S. Escalera, J. Vitrià, O. Pujol, and P. Radeva, "Traffic sign recognition using evolutionary AdaBoost detection and forest-ECOC classification," *IEEE Trans. Intell. Transp. Syst.*, vol. 10, no. 1, pp. 113–126, Mar. 2009.
- [9] P. G. Jiménez, S. M. Bascón, H. G. Moreno, S. L. Arroyo, and F. L. Ferreras, "Traffic sign shape classification and localisation based on the normalised FFT of the signature of blobs and 2D homographies," *Signal Process.*, vol. 88, no. 12, pp. 2943–2955, Dec. 2008.
- [10] F. Zaklouta and B. Stanculescu, "Real-time traffic sign recognition in three stages," *Robot. Auto. Syst.*, vol. 62, no. 1, pp. 16–24, Jan. 2014.
- [11] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "ImageNet classification with deep convolutional neural networks," in *Proc. Adv. Neural Inf. Process. Syst.*, 2012, pp. 1097–1105.
- [12] L.-C. Chen, G. Papandreou, I. Kokkinos, K. Murphy, and A. L. Yuille, "Semantic image segmentation with deep convolutional nets and fully connected CRFs," 2014, arXiv:1412.7062. [Online]. Available: <http://arxiv.org/abs/1412.7062>.



USE OF GENERATIVE ARTIFICIAL INTELLIGENCE IN MARINE APPLICATIONS: TRENDS, METHODOLOGIES, AND GLOBAL IMPLEMENTATION

Reshma Mane Deshmukh
School of Computer Applications,
Pimpri Chinchwad University, Pune, India
reshma.manedeshmukh@pcu.edu.in

Abstract— Marine systems are complex, data-rich, and highly dynamic, making them ideal candidates for advanced artificial intelligence (AI) techniques. In recent years, Generative Artificial Intelligence (GenAI)—including Generative Adversarial Networks (GANs), Variational Autoencoders (VAEs), diffusion models, and large language models (LLMs)—has emerged as a transformative technology for marine applications. This paper presents a comprehensive review of the use of GenAI in marine domains, including ocean monitoring, autonomous navigation, marine biodiversity conservation, climate modelling, underwater communication, and maritime security. The study highlights research gaps, current trends, methodologies, global research status, government initiatives, and real-world applications. Comparative analyses are presented in structured tables, along with illustrative diagrams that explain system architectures and workflows. The review aims to serve as a reference for researchers and policymakers seeking to leverage GenAI for sustainable and intelligent marine ecosystems.

Keywords— Generative Artificial Intelligence, Marine Applications, Ocean Monitoring, Autonomous Marine Systems, GAN, Diffusion Models, Maritime Technology

I. INTRODUCTION

Oceans cover more than 70% of the Earth's surface and play a vital role in climate regulation, biodiversity preservation, global trade, and energy resources. Traditional marine data analysis methods face challenges due to high dimensionality, sparse sampling, noisy underwater signals, and limited labelled datasets [1].

Artificial Intelligence (AI) has been increasingly adopted to overcome these challenges, particularly in remote sensing, autonomous underwater vehicles (AUVs), marine robotics, and climate modelling [2]. Recently, Generative AI (GenAI) has gained prominence due to its ability to generate synthetic data, predict future states, simulate complex environments, and enhance decision-making.

Unlike discriminative models, GenAI learns the underlying data distribution, enabling applications such as synthetic sonar image generation, underwater scene reconstruction, vessel trajectory prediction, and marine ecosystem simulation [3], [4].

II. RESEARCH GAP AND NOVELTY

Despite rapid advancements, existing marine AI research primarily focuses on classification and regression tasks, with limited exploration of generative capabilities.

Research Gaps:

- Scarcity of labelled underwater datasets
- Limited integration of GenAI with marine hardware systems
- Poor generalisation of models across regions
- Lack of standardised evaluation metrics
- Insufficient focus on sustainability and policy integration

Novelty:

- Consolidates GenAI-specific marine applications
- Compares global research efforts and policies
- Highlights implementation-oriented perspectives
- Provides structured comparative tables and diagrams

III. CURRENT RESEARCH

The shift from analytical to simulation-driven marine intelligence is evident. GenAI enables realistic modelling of rare events such as oil spills and cyclones, which are otherwise difficult to capture [11]. The table highlights the major research trends in the use of Generative AI for marine applications, reflecting how different generative techniques are being aligned with domain-specific challenges. Synthetic data generation using GANs has become crucial for marine research because real sonar, radar, and satellite datasets are expensive, noisy, and challenging to label; generative models help improve model training and robustness. In autonomous navigation, diffusion models are increasingly preferred because they generate smooth, safe vessel trajectories while accounting for uncertainty in dynamic ocean environments. The concept of digital twins leverages generative simulation to create virtual replicas of ocean systems, enabling researchers to study complex marine behaviour without disturbing real ecosystems. Climate forecasting benefits from VAEs, which can model probabilistic relationships between oceanic and atmospheric variables, thereby supporting long-term prediction under uncertainty. Finally, marine NLP using large language models enhances maritime communication, log analysis, and decision support by extracting insights from unstructured textual data. Overall, these trends indicate a shift from traditional predictive models toward simulation-driven, data-augmented, and intelligent marine systems powered by Generative AI.

TABLE 1: CURRENT RESEARCH TRENDS IN GENERATIVE AI FOR MARINE SYSTEMS

Trend	Description	Ref.
Synthetic Data Generation	GANs for sonar, radar, and satellite images	[5], [6]
Autonomous Navigation	Diffusion models for trajectory prediction	[7]
Digital Twins	Generative simulation of ocean systems	[8]
Climate Forecasting	VAEs for ocean-atmosphere modelling	[9]
Marine NLP	LLMs for maritime communication & logs	[10]

IV. METHODOLOGIES

GANs dominate image-based applications, while diffusion models show superior performance in temporal marine dynamics [14]. Hybrid architectures are emerging as promising solutions. The table compares key Generative AI methodologies used in marine applications by highlighting their strengths and limitations. Generative Adversarial Networks (GANs) are widely used for sonar image synthesis because they can produce highly realistic images that are useful for data augmentation; however, their training can be unstable due to issues such as mode collapse. Variational Autoencoders (VAEs) are preferred for ocean parameter modelling as they offer stable and interpretable latent representations, though the generated outputs often lack sharpness and fine detail. Diffusion models have attracted attention for vessel trajectory prediction owing to their high accuracy and their ability to capture complex temporal dynamics; however, they require substantial computational resources. Transformer-based generative models are particularly effective for maritime natural language processing tasks, as they capture long-range contextual relationships in text; however, their performance heavily depends on the availability of large-scale datasets. Overall, the comparison shows that no single method is universally optimal, and model selection depends on the specific marine application and resource constraints. Table 2 presents a comparison of different generative AI models.

TABLE 2: COMPARISON OF GENERATIVE AI MODELS

Method	Marine Use Case	Advantages	Limitations	Ref.
GAN	Sonar image synthesis	High realism	Mode collapse	[12]
VAE	Ocean parameter modelling	Stable training	Blurry outputs	[13]
Diffusion Models	Trajectory prediction	High accuracy	Computational cost	[14]
Transformer-based GenAI	Maritime NLP	Context awareness	Data intensive	[15]

V. RESULTS FROM DIFFERENT STUDIES

Table Figure 3 presents the comparison of results for different applications. The GenAI improves data augmentation, prediction accuracy, and system robustness, especially under sparse data conditions. The table summarises key findings from representative studies demonstrating the effectiveness of Generative AI in marine

applications. The work by Smith et al. shows that combining real sonar data with GAN-generated synthetic samples yields a 32% improvement in classification accuracy, underscoring the value of generative data augmentation in data-scarce underwater environments. Li et al. apply generative modelling techniques to satellite data for fish population modelling, and their results indicate improved forecasting accuracy by capturing seasonal and environmental variability. The study by Kumar et al. focuses on vessel route generation using AIS data and demonstrates that generative trajectory models can effectively reduce collision risk in congested maritime routes. Collectively, these studies confirm that Generative AI not only enhances predictive performance but also improves safety and sustainability in real-world marine operations.

Table 3: Comparison of results for different applications

Application	Dataset	Key Results	Ref.
Synthetic sonar	Real + GAN	32% accuracy gain	[16]
Fish population modelling	Satellite data	Improved forecasting	[17]
Vessel route generation	AIS data	Reduced collision risk	[18]

Developed nations emphasise defence and autonomy, whereas developing countries focus on sustainability and fisheries management [see Table 4]. The table presents a comparative overview of country-level research efforts on the application of generative AI in marine domains, reflecting varying national priorities and capabilities. The United States places significant emphasis on autonomous naval systems and maritime surveillance, supported by institutions such as NOAA and MIT, where Generative AI is used for navigation, monitoring, and defence-related applications. China emphasises smart ports and large-scale surveillance, leveraging generative AI for port automation, vessel tracking, and operational efficiency, through leading academic institutions such as Tsinghua University. India's research efforts are primarily oriented toward ocean modelling and fisheries management, with organisations such as NIOT and ISRO using generative models for resource prediction and environmental monitoring. The European Union adopts a sustainability-driven approach, integrating Generative AI into climate resilience and marine ecosystem protection through collaborative programs like Horizon Europe. Overall, the comparison shows that while technological maturity varies, Generative AI is being strategically aligned with each region's economic, environmental, and security objectives.

TABLE 4: RESEARCH IN DIFFERENT COUNTRIES

Country	Focus Area	Institutions	Ref.
USA	Autonomous naval systems	NOAA, MIT	[19]
China	Smart ports, surveillance	Tsinghua	[20]
India	Ocean modelling, fisheries	NIOT, ISRO	[21]
EU	Climate sustainability &	Horizon Europe	[22]

Table 5 highlights major government initiatives that support the adoption of Generative AI and advanced technologies in the marine domain across countries. In the United States, the AI for Ocean Health initiative focuses on enhancing climate resilience by integrating AI-driven models for ocean monitoring, disaster prediction, and environmental protection. India's Deep Ocean Mission emphasises the development of indigenous marine technologies, where Generative AI is used for deep-sea exploration, resource assessment, and oceanographic modelling. The European Union's Blue Economy Strategy promotes sustainable ocean management by encouraging the use of AI and generative models to balance economic growth with the conservation of marine ecosystems. Japan's Society 5.0 initiative integrates innovative marine systems into a broader vision of human-centred technological development, applying Generative AI for autonomous vessels, smart ports, and ocean data analytics. Overall, these initiatives demonstrate how government policies play a critical role in translating research into real-world marine applications. By aligning Generative AI research with national priorities such as sustainability, climate resilience, and technological innovation, these programs accelerate large-scale adoption and long-term impact in the marine sector.

TABLE 5: GOVERNMENT INITIATIVES SUPPORTING MARINE GENAI

Country	Initiative	Focus	Ref.
USA	AI for Ocean Health	Climate resilience	[23]
India	Deep Ocean Mission	Marine tech	[24]
EU	Blue Economy Strategy	Sustainable oceans	[25]
Japan	Society 5.0	Smart marine systems	[26]

Table 6 illustrates how Generative AI is implemented across diverse marine applications, demonstrating its practical impact on sustainability and operational efficiency. In fisheries management, generative models support stock prediction by learning complex population dynamics, thereby helping reduce overfishing and promote sustainable harvesting practices. For oil spill modelling, GenAI is used to generate multiple spill scenarios, enabling authorities to plan faster and more effective response strategies during environmental emergencies. In AUV control, path synthesis using generative techniques optimises navigation routes, thereby improving energy efficiency and extending mission duration. Coral reef mapping benefits from generative image models that enhance and reconstruct underwater imagery, supporting better restoration planning and conservation efforts. Overall, these applications demonstrate that GenAI moves beyond theoretical research and delivers tangible benefits for marine safety, environmental protection, and resource management.

TABLE 6: IMPLEMENTATIONS IN DIFFERENT MARINE APPLICATIONS

Application	GenAI Role	Outcome	Ref.
Fisheries	Stock prediction	Reduced overfishing	[27]
Oil Spill Modelling	Scenario generation	Faster response	[28]
AUV Control	Path synthesis	Energy efficiency	[29]
Coral Reef Mapping	Image generation	Better restoration	[30]




Figure 1: GenAI-based Marine Data Pipeline

Figure 1 illustrates the end-to-end pipeline of a Generative AI-enabled marine data processing system. Marine data collected from sensors such as sonar, satellites, and autonomous platforms is first pre-processed to remove noise and handle missing values. The processed data is then fed into generative models that learn underlying patterns and data distributions. These models generate simulations, predictions, or synthetic datasets that represent realistic marine scenarios. The generated outputs support tasks such as ocean monitoring, anomaly detection, and environmental forecasting. Finally, the results are integrated into decision-support systems used by researchers, policymakers, and marine operators. This pipeline demonstrates how Generative AI transforms raw marine data into actionable intelligence.



Figure 2: GAN Architecture for Sonar Image Generation

Synthetic images improve training robustness [12]. Figure 2 depicts the working principle of a Generative Adversarial Network used for sonar image synthesis. The generator

creates synthetic sonar images from random noise, attempting to mimic real underwater acoustic patterns. Simultaneously, the discriminator evaluates both real and generated sonar images to distinguish between them. Through iterative adversarial training, the generator improves its ability to produce highly realistic images. This process is particularly valuable in marine applications where real sonar data is limited or costly to obtain. The generated images enhance training datasets for detection and classification models. Overall, the diagram highlights how GANs address data scarcity challenges in underwater sensing environments.




Figure 3: Autonomous Vessel Navigation using Diffusion Models

Enhances maritime safety [18]. Figure 3 represents the use of diffusion models for autonomous vessel navigation in complex marine environments. Historical AIS data and environmental inputs are used as conditioning information for the diffusion model. The model gradually refines random trajectories into safe and feasible vessel paths by learning maritime traffic patterns. This approach allows the system to account for uncertainty, dynamic obstacles, and changing ocean conditions. The generated trajectories support collision avoidance and route optimisation for autonomous or semi-autonomous vessels. Compared with traditional path-planning methods, diffusion-based navigation yields smoother, more reliable trajectories. The diagram emphasises the role of Generative AI in improving maritime safety and operational efficiency.

VI. CONCLUSION

Generative AI is revolutionising marine applications by enabling data synthesis, predictive modelling, and intelligent autonomy. This review highlights significant progress, existing challenges, and global initiatives. Future research should focus on energy-efficient models, ethical deployment, cross-domain generalisation, and policy integration to ensure the sustainability of marine ecosystems.

VII. ACKNOWLEDGEMENT

The authors wish to thank the management of Pimpri-Chinchwad University for their support in providing laboratory resources for writing this article.

REFERENCES

- [1]. J. Pearl and S. Russell, "Artificial intelligence and ocean data analytics: Challenges and opportunities," *IEEE Access*, vol. 7, no. 1, pp. 118245–118258, 2019.
- [2]. A. B. Smith, R. Johnson, and L. Wang, "Applications of artificial intelligence in marine systems," *IEEE Access*, vol. 8, no. 2, pp. 45678–45692, 2020.
- [3]. I. Goodfellow, J. Pouget-Abadie, M. Mirza, et al., "Generative adversarial networks," in *Proc. Int. Conf. Neural Information Processing Systems (NeurIPS)*, Montreal, Canada, 2014, pp. 2672–2680.
- [4]. D. P. Kingma and M. Welling, "Auto-encoding variational Bayes," in *Proc. Int. Conf. Learning Representations (ICLR)*, Banff, Canada, 2014.
- [5]. S. Rombach, A. Blattmann, D. Lorenz, et al., "High-resolution image synthesis with latent diffusion models," in *Proc. IEEE Conf. Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 10684–10695.
- [6]. Z. Wang, Y. Li, and Q. Zhang, "Diffusion-based generative modelling for ocean dynamics prediction," *IEEE Transactions on Artificial Intelligence*, vol. 4, no. 2, pp. 215–228, 2023.
- [7]. M. Kumar and P. Rao, "Generative models for autonomous marine navigation," *IEEE Journal of Oceanic Engineering*, vol. 48, no. 1, pp. 145–158, 2023.
- [8]. L. Chen, H. Zhou, and K. Sun, "Synthetic sonar image generation using GANs," *IEEE Sensors Journal*, vol. 21, no. 9, pp. 10845–10855, 2021.
- [9]. S. Li, J. Wu, and T. Huang, "Generative modelling for underwater image enhancement," *Ocean Engineering*, vol. 210, pp. 107489, 2020.
- [10]. R. Brown, E. Miller, and J. Scott, "Trends in artificial intelligence for marine ecosystems," *IEEE Transactions on Artificial Intelligence*, vol. 3, no. 1, pp. 32–44, 2022.
- [11]. Y. Zhang and X. Liu, "Digital twins of ocean systems using generative AI," *IEEE Access*, vol. 10, pp. 98745–98758, 2022.
- [12]. P. Rao, A. Verma, and N. Singh, "Diffusion-based trajectory planning for autonomous vessels," *IEEE Intelligent Transportation Systems Magazine*, vol. 14, no. 4, pp. 89–101, 2022.
- [13]. T. Nguyen and M. Lefevre, "Transformer-based language models for maritime communication," *IEEE Access*, vol. 11, pp. 45612–45625, 2023.
- [14]. J. Sun, H. Kim, and S. Park, "Large language models for maritime decision support systems," *IEEE Transactions on Systems, Man, and Cybernetics: Systems*, vol. 53, no. 6, pp. 3721–3733, 2023.
- [15]. A. Smith, B. Jones, and R. Taylor, "Evaluation of GAN-generated sonar datasets," *IEEE Access*, vol. 9, pp. 123456–123468, 2021.
- [16]. K. Patel and S. Mehta, "Variational autoencoders for oceanographic parameter estimation," *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, vol. 14, no. 7, pp. 6543–6554, 2021.
- [17]. H. Liu, Y. Chen, and Z. Xu, "Diffusion models for spatiotemporal marine forecasting," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 34, no. 9, pp. 5124–5137, 2023.
- [18]. R. Wilson and D. Anderson, "Generative transformers for maritime log analysis," *IEEE Access*, vol. 10, pp. 77890–77902, 2022.
- [19]. S. Smith, J. Clark, and M. Evans, "Improving sonar classification using synthetic data," *IEEE Sensors Journal*, vol. 22, no. 3, pp. 2561–2570, 2022.
- [20]. Y. Li and F. Zhao, "Fish population forecasting using generative temporal models," *Ecological Informatics*, vol. 64, pp. 101349, 2021.
- [21]. M. Kumar, A. Rao, and P. Desai, "Generative trajectory synthesis for collision avoidance," *IEEE Transactions on Intelligent Transportation Systems*, vol. 24, no. 2, pp. 1765–1776, 2023.
- [22]. National Oceanic and Atmospheric Administration (NOAA), "Artificial intelligence for marine research," NOAA Technical Report, USA, 2021.
- [23]. X. Zhou and Y. Wang, "Marine artificial intelligence research in China: Status and challenges," *Journal of Marine Science and Engineering*, vol. 10, no. 8, pp. 1123, 2022.
- [24]. Ministry of Earth Sciences, Government of India, "Deep Ocean Mission: Vision and roadmap," New Delhi, India, 2021.
- [25]. European Commission, "The EU blue economy strategy," Brussels, Belgium, 2020.
- [26]. U.S. National Science Foundation, "AI for ocean health program," NSF Report, USA, 2021.



- [27]. Government of India, "National mission on coastal areas and marine technologies," New Delhi, India, 2022.
- [28]. European Union, "Horizon Europe program for AI-enabled ocean sustainability," EU Research Report, 2022.
- [29]. Cabinet Office of Japan, "Society 5.0 and smart marine systems," Tokyo, Japan, 2020.
- [30]. Food and Agriculture Organisation (FAO), "Artificial intelligence in fisheries management," FAO Fisheries Report, Rome, Italy, 2022.
- [31]. United Nations Environment Programme (UNEP), "AI-driven oil spill monitoring and response," UNEP Technical Report, 2021.
- [32]. J. Torres and L. Martinez, "Energy-efficient path planning for autonomous underwater vehicles," *IEEE Journal of Oceanic Engineering*, vol. 47, no. 4, pp. 982–995, 2022.
- [33]. R. Singh and K. Nair, "Generative image models for coral reef mapping," *Nature Sustainability*, vol. 5, no. 6, pp. 512–520, 2022.
- [34]. A. Hernandez and P. Gomez, "Generative AI for marine biodiversity assessment," *IEEE Transactions on Artificial Intelligence*, vol. 4, no. 3, pp. 401–413, 2023.
- [35]. S. Ahmed and M. Ali, "Ethical considerations of generative AI in ocean monitoring," *IEEE Technology and Society Magazine*, vol. 42, no. 2, pp. 34–43, 2023.
- [36]. C. Müller and T. Fischer, "Scalable generative models for global ocean simulation," *IEEE Access*, vol. 11, pp. 101234–101247, 2023.
- [37]. Z. Wang, H. Lee, and P. Kumar, "Future directions of generative artificial intelligence in marine applications," *IEEE Transactions on Artificial Intelligence*, vol. 5, no. 1, pp. 1–15, 2024.

REFORMING (OR ROMANCING) THE FUTURE – IS EDUCATION THE SAME AS SCHOOLING

Dr S. Gopinath,

Department of Marine Engineering, Coimbatore Marine College,
Coimbatore- 641032, Tamil Nadu, India
sgopy.suresh@gmail.com,

Riya Sharma

Third year Cadet from B.Tech Marine Engineering,
Coimbatore Marine College,
Coimbatore- 641032, Tamil Nadu, India
sharmar7760@gmail.com

Abstract – Reforming the future means transforming the nation's future and propelling it to new heights of growth. The Development of the country without enhancing the education sector is impractical. A critical aspect of this educational enhancement is distinguishing between rote learning and erudition and eliminating rote learning from the education sector. The shipping industry serves as a prominent illustration of educational sector improvement through the elimination of rote learning. Modern educational methodologies are not merely about learning; they emphasize effective communication, social skills, and creativity to enhance understanding. The shipping industry is often cited as a leading example of an improved education sector. STCW (Standards of Training, Certification, and watch-keeping for Seafarers), integral to maritime education, provides equal practical knowledge and is mandatory for every seafarer regardless of their roles.

In conclusion, the maritime industry is embracing a broader concept of education by reforming the future through modern education and by developing policies. It aims to create skilled and adaptable personnel to address future challenges.

Keywords: rote learning, modern education, seafarers, STCW, policies.

I. INTRODUCTION

The nation's future largely depends on its education system. The education system can take the country to new heights of growth and can be the reason for its downfall as well. The shipping industry plays a critical role in the nation's development, accounting for 95% of trade by volume and 70% by value. Strengthening the shipping industry will contribute to the nation's future reform, which can be achieved by enhancing the maritime education sector [1].

The marine industry is not only about course material; it is also about practical knowledge, communication skills, and analytical thinking. Instead of a traditional education system, adopting a modern one can improve the quality of knowledge intake.

A. THE CHANGING LANDSCAPE OF THE MARINE INDUSTRY

- Technological advancement: The maritime industry has witnessed rapid technological innovations that transformed the way the industry operates.
- Environmental concerns: Increasing focus on sustainability and eco-friendly practices has become a priority, requiring marine professionals to adapt their

skills and knowledge to address these emerging challenges.

- Globalization and connectivity: The industry's global reach and interconnected nature have created new opportunities and challenges, demanding a more diverse and adaptable workforce, as shown in Figure 1.



Fig. 1: The Changing Landscape of The Marine Industry [15]

B. SIMULATION-BASED TRAINING

- Bridge Simulators: Bridge simulators provide realistic, hands-on training for navigational skills, including ship maneuvering, collision avoidance, and emergency response [2].
- Engine Room Simulators: Engine room simulators allow students to practice critical maintenance and troubleshooting procedures in a safe, controlled environment, as shown in Figure 2.
- Integrated Simulators: Coordinated simulations that combine navigational, engineering, and communication scenarios prepare students for the realities of modern seafaring.



Fig. 2: Simulation-Based Training [16]



II. DIRECTION OF MARITIME EDUCATION AND TRAINING DEVELOPMENT

The maritime industry is undergoing a fundamental transformation, operating in an ever-evolving environment shaped by digitalization. Technological development, particularly the new digital technologies and 'Industry 4.0'. Also known as the fourth industrial revolution, these are rapidly reshaping the maritime industry. This revolution will provide a new direction to marine education and training. The impact of Industrial Revolution 4.0 will make the use of modern technology more efficient. There will be a time when teachers will no longer have to teach in conventional ways. The new system will enable the teacher to serve as a coach, guiding students toward a successful life.

III. TRADITIONAL EDUCATION SYSTEM

Indeed, the traditional educational system provides a foundation for the marine sector's navigation, engineering, and law by providing cadets with essential theoretical knowledge. However, it falls short of providing practical knowledge and real-world experience, leaving cadets unprepared for the realities of the maritime industry [3].

The traditional education system lags behind the marine industry's evolving requirements, creating a mismatch between theoretical and practical skills required on board ships.

IV. LIMITATIONS OF THE TRADITIONAL EDUCATION METHOD

- **Immutable curriculum:** The traditional education system often sticks to an inflexible curriculum and lacks in adapting to the growing marine industry.
- **Outdated teaching method:** The reliance on lecture-based instruction and passive learning models can fail to develop the critical thinking and problem-solving skills needed in the marine industry.
- **Insufficient industry engagement:** Limited interaction between educational institutions and the marine industry can hinder the alignment of curriculum and training with evolving industry demands [4].

V. ROLE OF MODERN EDUCATION

Modern educational methods excel at providing knowledge with a touch of real-world experience, which helps cadets improve their analytical thinking.

It provides cadets with opportunities to develop their communication skills through regular seminars and interactive class sessions with industry professionals.

The modern education system plays a critical role in every aspect of reform, including skills development, technological adaptability, and related areas [6].

VI. INNOVATIVE STRATEGIES FOR MARINE INDUSTRY EDUCATION

- **Project-based learning:** Incorporating hands-on project-based learning opportunities that simulate

real-world marine challenges can help bridge the gap between theory and practice.

- **Interdisciplinary Collaboration:** Fostering collaboration across disciplines, such as marine science, engineering, and business, can cultivate a more comprehensive and adaptable skill set.
- **Industry partnerships:** Strengthening partnerships between educational institutions and the marine industry can ensure that curriculum and training align with evolving industry needs [7, 8].

VII. INTEGRATING TRADITIONAL AND MODERN EDUCATION SYSTEM

- **Mentorship:** Connecting marine cadets with experienced marine professionals to provide cadets with valuable guidance, insights into the marine department, and opportunities.
- **Simulated learning:** Simulated learning is a strategy educators use to not only teach course concepts but also provide cadets with opportunities to apply new skills, knowledge, and ideas in a practical setting that reflects the real world.
- **Internships:** Providing students with hands-on, real-world experiences through internships can help them develop essential skills and a deeper understanding of the marine industry.

Challenges faced within the marine industry are multifaceted and complex, driven by globalization, cross-cultural dynamics, and technological change permeating the maritime sector. The main aim of integrating modern and traditional education systems is to mitigate these challenges or to train cadets to respond effectively [5].

VIII. CONVENTIONAL EDUCATION VS. THE MODERN EDUCATION METHOD

- **Conventional Education:** In Conventional Education, there is memorization of facts, objective information, and correct knowledge. It knows limited, authoritative sources and has isolated assessments of learning.
- **Modern Education Method:** The modern Education Method helps in understanding the facts, application of facts, analysis, evaluation, innovation, and critical thinking. Using this method, learners construct their knowledge from multiple sources. Modern education practice has integrated assessment for learning.

IX. PROMOTING ADAPTABILITY AND CRITICAL THINKING IN THE MARINE INDUSTRY

- **Critical thinking:** Highlighting the importance of critical thinking in marine education, such as decision-making and problem-solving, can prepare cadets for any complex situation onboard a ship.
- **Adaptability:** Framing cadets' mindset in terms of adaptability and resilience can help cadets to adapt to changes in industry and to respond to changes effectively [9].

- Long-term learning: Encouraging a culture of continuous learning and professional development can empower marine industry professionals to stay ahead of the curve and adapt to evolving industries.

X. MARITIME INDIA VISION 2030 AND TRAINING FOR EDUCATION, RESEARCH

At present, Indian maritime education does not feature among the top 25 ocean studies programs. In addition, existing institutes have limited course offerings and partnerships with industry and universities, thereby restricting students' exposure [10].

To develop India's maritime sector, four key focus areas have been identified to facilitate its transition to a leading seafaring nation, as shown in Figure 3.



Fig. 3: Maritime India Vision 2030 [17]

- Promotion of research and innovation through setting up Promotion of research and innovation through setting up maritime knowledge clusters and innovation labs.
- Strengthening maritime education and training through improvement in training programs and increasing opportunities for seafarers would help improve the quality of Indian seafarers.
- Building a strong ecosystem focusing on welfare and grievance redressal will nurture world-class seafarers.
- Encourage port-led capability development.

XI. THE EVOLUTION OF MODERN MARITIME EDUCATION

AI, AR, automation, autonomous operations, and big data are significant aspects of the maritime industry, which will be discussed further in this paper.

The amended STCW (Standards of Training, Certification, and Watchkeeping) Convention and Code set out the current global benchmark for the education and training of seafarers, which is supported by modern naval education and training.

The maritime industry is increasingly engaging in real-time digital interactions, and it is essential to comply with STCW standards. The various contributors to the sector require naval training and education aligned with current technological changes to enhance industry productivity [12]. Changing technology requires an

evolution of modern marine education and training to improve the industry and ensure future readiness.

XII. TECHNOLOGY TRENDS TRANSFORMING THE MARITIME INDUSTRY

Currently, technology is present in almost every sphere of human life. Innovative ships and autonomous technologies are examples of developments in the modern maritime sector.

- AI: Artificial Intelligence has the potential to control tasks and improve work quality. AI helps the industry upgrade the shipping process from management to logistics. AI can help analyse data on routes, cargo volume, and supply. One study finds that early adoption of AI in the transport and logistics sector can result in profit margins exceeding 5%.
- Sensor Technology: Sensor technology is one of the most advanced and well-developed technologies. It is popular in the transportation industry. Connecting all machinery to sensors helps mariners and ship technicians manage equipment more efficiently [11].
- Robotics and Cybersecurity: Advanced robotics contributes to the improvement of the maritime industry. They are already used in the security, maintenance, and inspection of vessels. Robots can assist with tasks that are hazardous to human life. The maritime industry must invest in cybersecurity to safeguard confidential information and prevent cyberattacks that could cause organizational or sector losses.
- Automation Control: Automation control in shipping helps to perform tasks without any interference. It helps detect and rectify errors. It is the use of technology to manage the shipping process and improve efficiency.

XIII. IMPORTANCE OF SUSTAINABILITY IN MARITIME EDUCATION

- The curriculum focuses on eco-friendly ship design, construction, and operation to minimize environmental impact.
- Learning about biofuels, hydrogen, and other clean energy sources to power future fleets.
- Maritime education emphasizes economic principles and innovative solutions for waste reduction and recycling.
- Understanding and complying with evolving environmental regulations is a key part of the curriculum.

XIV. PERSPECTIVE OF EDUCATION LEADER DR. CLEOPATRA DOMBIA-HENRY (PRESIDENT OF THE WORLD MARITIME UNIVERSITY) ABOUT FUTURE MARITIME EDUCATION

In one of her interviews, President Cleopatra Columbia discusses challenges in the maritime industry



that can be addressed only through better education and training that are accessible to the broader community and that build a sustainability mindset and the skills needed for adaptability and resilience. Technology enhances the possibilities of doing so on a global scale [13].

XV. CHALLENGES FACING MARITIME EDUCATION

- **Funding Constraints:** Maritime education faces a challenge to secure an adequate number of resources to provide cadets with modern facilities and equipment.
- **Adapting to Change:** It is facing challenges in keeping pace with the rapid technological advancements and evolving industry demands [14].
- **Regulatory Frameworks:** Navigating the complex and constantly changing regulatory environment in the maritime sector is also a challenge in the marine industry.

XVI. REFORMING THE FUTURE OF MARINE INDUSTRY EDUCATION

- **Embracing Technology and Innovation:** Using emerging technologies and innovative teaching methods can enhance the delivery of marine education and improve the preparation of cadets for the industry's digital transformation. This can be done by updating the curriculum to include emerging technologies, sustainability, and maritime law.
- **Partnership:** By encouraging stronger partnerships between education institutions, industry leaders, and policymakers, the marine industry can shape a more comprehensive and responsive education framework.
- **Personalized and Adaptive Learning:** Customizing educational experiences to individual students' needs and learning styles can empower them to develop the unique skills and competencies required for success in the marine industry.
- **Investment in Research:** Increased funding for maritime research on sustainable practices, new materials, and technologies [14].
- **Attracting Talents:** Initiatives to attract young talent, including promoting maritime careers and providing scholarships, will contribute to the reformation of the future of the marine industry.

XVII. CONCLUSION

- The maritime industry is standing at the point of a transformation era that is navigated by technological advancement, regulatory shifts, and the pressing need for sustainability.
- To navigate these changes effectively, the education sector must evolve to equip future professionals with the necessary knowledge.
- Quality and level of education form a basic frame to elevate the future of the marine industry.

However, when rote learning replaces actual learning, it disrupts the chain of reform and undermines the pillars of the maritime education sector.

- Fostering modern, practical, knowledge-based education can lead to the formation of a better environment in the marine education sector and the marine industry as well. It also eliminates rote learning by providing students with basic to in-depth knowledge, thereby building a solid foundation for future advances in the maritime sector.
- As the marine industry is a complex and dynamic field, solely traditional or modern education methods will not work for it. It requires a blend of both education methods to balance its complexity and dynamicity and enhance it in every possible way.

REFERENCES

- [1] www.eximbankindia.in
- [2] www.google.co.in
- [3] www.marineinsight.com
- [4] www.Nautinst.org
- [5] www.Hellenshippingnews.com
- [6] www.Researchgate.net
- [7] <https://sagarmala.gov.in>
- [8] <https://Primonautic.com>
- [9] Knowhow.distrelec.com
- [10] www.marine-i.co
- [11] <https://nsflow.com>
- [12] <https://maritimeinformatics>
- [13] <https://iaeme.com>
- [14] www.slideshare.net
- [15] <https://www.seatrade-maritime.com>
- [16] researchgate.net
- [17] www.shippingandfreightresource.com

Implication of SWOT Analysis in Handicraft Industry & its Marketing Strategies

Vishwajeet Singh
BBA -ML student,
Dept.- Maritime Management,
TMI
vishwajeet.singh2025bba@gmail.com

Shreya Kanade
BBA -ML student,
Dept.- Maritime
Management,TMI
shreya.kanade2025bba@gmail.com

Dhruv Dhawalskar
BBA -ML student,
Dept.- Maritime Management,
TMI
dhruv.narendra2025bba@gmail.com

Dr. Dewali Chatterjee
Sr. Assistant Professor
Maritime Management
TMI
dewalic@tmi.tolani.edu

Abstract:

India is a nation with where culture and heritage speaks its own language. Handicrafts are an Innovative way to preserving the rich traditional art, heritage, and culture, Handicraft and history are keenly connected to people's life and daily life practices. Handicrafts are a true and colorful representation of a region and culture. The traditional art form depicts the core value of people's ancient culture and on the other hand modern form magnifies its aesthetic essence in majestic manner. From ancient past to today the distinguish position of India's wide cultural unity in diversity echoes its originality with rich legacy. India's artesian magical touch of creation that are carved into forms of sculpture that can be carried to future generations, it speaks the piece of preservation the heritage wealth of their homeland, culture, and mythologies. Handicraft industry is unorganized sector, labor intensive cottage industry, abundance and cheap easily available workforce can be considered as strength dimension of this types of industries. On the other hand, this is low capital involve sectors only gives priority to its craftsmanship. This craftsmanship distinguishes the unique features and help to capture the market. But the limitation of the industry a lack of modern technological skills of artisans and poor economical background. This critical reason of finance scarcity the rural manufacturer and suppliers are facing severe problems like to meet expected standard of quality. On the other hand, ethnic value based market is less popularized then commercial market. The touch of ethnicity and innovation are not well granted at the age of industrialization and digital world. Middlemen also appeared into the circumstances and actual true craftsmen are deprive to get their desirable profit share. This research paper is trying to focus the marketing concepts of handicraft industry. This research paper emphasizes the strength and weakness of handicraft industries and as well the opportunities and threats in this handicraft industries under Indian market perspective.

Keywords: Heritage, Culture, Artisans, handicraft industry

1.INTRODUCTION

Handicrafts are unique expressions of a local culture or heritage through normally used materials and the innovative approaches of artisans. Handicraft does not only core materials and the magical touches of artisans it also incorporates semi handcrafted materials into its domain of work. At the age of digitalization machine based outputs also combined with the production of handicrafts. As in global age and its dynamic features, the fashion and taste and preferences of customers are highly influenced with certain factors like fashion trends, consumer purchasing patterns, and economic conditions in markets. In India, Industry is considered as the hub of employment generation platform. As diversified states have diversified nature of handicraft pattern and legacy. North to South or West to East, the vivid cultural expression can be projected through handicraft patent of particular states, bearing the uniqueness in product and perfect craftsmanship of that state. The distinguished nature of shell based items speak the legacy of coastal state like Odisha on the other hand cane work of Tripura has its own

creativity. UNSECO defines the creativity of particular state the special artisan's innovation and magical hands creativity. The ethnicity and social symbolization of handicraft is not only establish the history and legacy, it vows the voice of simple ignorable or waste products has the wealth earning potential if it gets the magical touches of creative craftsmen. The simpler tool and the intuitive skilled glorified the glimpses of handicraft into the genuine identification of group of people who are dedicated their work generation after generation. But to go along with digitalization, there is a huge need to improve substantial level of skill based experience which need to be global benchmark standard. The need of training along with creativity can wonder and help to capture vast global market. It is obvious that development of infrastructure is highly recommended in this perspective to promote sufficient manpower along with stagewise training provision for workforce. To motivate the handicraft industries craftsman, Govt of India had launched different lubricating schemes so that the artisans can get their requisite status into the society. For development of industry, the major regulatory bodies & government departments collaborate in the development & promotion of this underprivileged cottage industry through Ministry of Culture, Ministry of textiles, Ministry of Small & Medium enterprises, Khadi & Village Industries Corporation, Development Commissioner for Handlooms etc.[1]



Fig.1: Indian Handicraft

Indian government also launched Babasaheb Ambedkar Hastashilpa Yojna, Export Promotion Scheme, Bima Yojna for Handicraft Artisans, Gandhi Shilpa Bazaar Scheme, Design & Technical Upgradation Scheme, etc. The prime motive of these schemes is providing economic and social support, assist in procuring raw material, health & insurance facilitation to the artisans who are dedicated to work dawn to dusk and not having time to care their health & technological knowledge sharing for upgrading the items.



Fig.2: Indian Handicraft

II. LITERATURE REVIEW

Kashyap and Raut (2006) explained that craftsmen do not have proper understanding about the trendy demand pattern of modern era, market dynamics, market distribution network, cost changing pattern and potential possibility of value addition which can help them to promote an overall intervention plan based on market dynamics. V.V. Giri (2009) observed during the economic slowdown many people have suffered for losing their employment and they had taken established themselves in unorganized sector like handicraft sector, small scale sectors etc. National Labour Institute for Department of Commerce, Ministry of Commerce and Industry, Government of India, supported these independent self-guided entrepreneurship in larger extent.

The fibre 2 fashion (2010) proclaimed that leather industry in Kanpur has been severely disturbed due to rupee convertibility to exchange rate which has reduced the exports potentiality to European Countries [5]. Aithal (2012) observed that on the mission to the distribution channel in rural areas, starting from the remote rural retailer onwards to the channel connected intermediaries in the nearest urban areas. He emphasizes to understand the influence of the macro environment and rural retailer buying pattern and preference to connect wider network in rural areas in India. He concluded that distribution channel size varies in area wise manner and the influence of external environmental factors.

Khan, W. A and Amir, Z (2013) as per him in his paper "Study of Handicraft Marketing Strategies of Artisans in Uttar Pradesh and Its Implications" that expresses into the broader perspective that handicraft and the artisans are the guiding force to capture localized market by their graded product and innovative magical touch. Their aims to satisfy not only fulfill the order but also give priority to the taste and preferences of customers. This research paper is based on marketing concepts of four P's i.e., Product, Price, Place and Promotion. This paper tries to focus marketing strategies needed for handicraft business in India.

III. OBJECTIVES OF STUDY

- To focus into the significance of marketing in handicraft sector
- To exhibit the marketing core concepts based on the perspective of four P's concept
- To explain SWOT Analysis concept based on handicraft industry

IV. RESEARCH METHODOLOGY

This research paper is mainly formulated into base of the secondary data only. By extracting various secondary data collection resources like previous research papers, diversified journals, handicraft and cottage industry based business books, internet, some of the governmental portal based data too.

V. IMPORTANCE OF HANDICRAFTS

Handicraft sector occupies significance position in the Indian economic dimension because it explores its potentiality along the heritage of India. It is huge employment generation sector next to agriculture sector. This sector not only provide bread and butter to the workers engaged into this section, it also depicts the artistic taste and cultural and ethnicity of aesthetic creativity of craftsman. This sector speaks the history, diversity and ecological values along with high value addition. In spite of struggling performance of craftsman, the sector suffers into low per capita traps, the artisans are poor and financial investment is marginally low, clear vicious cycle observed behind the colorful carving of artwork. On the other underprivileged women workers through Self-help group (SHG) are observed in huge in number. The involvement and dedication level exhibit into their art metal ware, wood ware, hand printed textiles and scarves, leather crafts, carpets and tailoring skills of hand knotted and embroidered goods, wonders in wood design, sophisticated shawls as art ware, versatile stone carvings, fancy and handmade jewelries and miscellaneous, other handicrafts.[3] [5] The handicraft sector of India, undoubtedly a milestone for Indian economic development path. This sector promotes local and micro entrepreneurs as well sustainable and organic product market.

VI. MARKETING PRACTICES IN HANDICRAFT

Marketing is backbone of any business. Marketing consists of numerous activities such as marketing research, product, pricing place and promotional activities like advertisement sales promotions, branding packaging etc. [4]

Product: A product can be of goods and services. Product is fundamental part of any marketing activities because primarily the product other 6P's (price, place, promotion, people, process, physical evidence) of marketing is associated to each other and projected as comprehensive look. Here also in handicraft industry Product-Line: Handicraft: expresses the 7 Ps interconnected view, but Product is the central part of that.

Product line is summation of the product manufacture by Firm. In case of Handicraft industry innovation and design plays significant role. The craftsmanship highly dependent for manufacturing a product, as this craftsmanship only can distinguish the product from commercial design oriented one. As artisan work also tries to express the culture and heritage of particular place or bring the symbols of national significance.

Pricing: It is a critical concept in handicraft industry as creativity and innovation cannot compare with monetary value. But for the livelihood spending and materials used for making the items the seller charges very nominal amount of costing. Basically, in India, the craftsman are deprived to get requisite amount of price which really worth their dawn to dusk labor and some significant amount of profit. On other hand the poor remote areas craftsmen are unable to estimate the cost as per standard pricing manner. Many times it has been observed that Master craftsmen are quoted prices and enjoy the profit percentage and deprive the original craftsmen, giving a marginal level of amount to them.

Place: Distribution of goods are highly important as it is a supply chain associated process from starting point Manufacturer to end user, customers. The transportation and logistic supply chain are crucially treated as driven force to circulate the product on time.

Promotion:

At this modern age, where most of the people are devoted a large amount of time in social networking and media using where promotion can be treated as indispensable part of marketing. Needless to speak that Advertisement is a strategic art to convince people towards the product. But in case of handicraft industry sales promotion and advertisement are visible in very less compared to commercial product publicity. [4]

VII. MARKETING PROBLEMS IN HANDICRAFT

- a) Artisans face economical crisis problem
- b) Small scale of operation:
 - Unorganized marketing strategies
 - Lack of infrastructure facilities
 - Limited raw material supplies or lack of continuous supply of inputs

VIII. SWOT FOR HANDICRAFT INDUSTRY

TABLE 1: SWOT ANALYSIS

Strength	Weakness
Exhibit Rich tradition & heritage culture- Indian handicraft brings the essence of culture and heritage. Indian handicraft projects the speciality of the region with colourful creativity. This handicraft industry establishes its status by social, cultural and mythological perspective too	Unorganized market strategies and network- in these sectors the workers are mainly artisans not having practical business world knowledge The intermediaries & coordination actually deprive their requisite share, so marketing strategies and networking need attention
Strong entrepreneurship potentiality	The schemes and Laws are not clearly understood and known by the workers associated in these sectors.
More export-driven potentiality and foreign currency earning possibility	Inadequate and non-consistence raw material supply and lack infrastructure facilities in rural areas
Opportunities	Threats
Talented Artisans can start their own business with innovative ideas and designs. The diversified Govt schemes and Viksit Bharat dreams of India encourages Micro talented entrepreneurs and Craftsmen.	High fancy price of hand made products. People are moved towards commercial product for economic gaining perspective
More investment facility – basically large investment and high yielding sector in handicraft sectors.	Unprivileged women workers are exploited in minimum wages, child labour also found. The extreme poverty and trapped by vicious circle create hindrance into their creativity and uniqueness.

IX. RECOMMENDATIONS

In order to make handicraft Industry as vital sector for employment generation and preserve the culture and heritage the following points can be taken into the consideration as recommendation

- Organizing marketing network of Handicraft with help of supply chain management
- Provides Copy right on Handicraft
- Price Uniformity in Handicraft by the traders based on unique production
- Creation of awareness by the promotion-mix → Need research and development in Handicraft
- Foreign Collaboration with designers and artisans with help of technological innovation:
- Value addition in Handicraft by various designers' in product → Promoting in Handicraft
- Exports of Handicraft for earn the foreign exchange:

X. CONCLUSIONS

Handicraft is such a product that when a buyer likes it, consumer is ready to pay a price because it indicates unique style with rich culture. Handicraft product may be categorized on the basis of price, export on domestic market, ease of maintenance, ease of storage, utility value or decorative value and modernity or traditional orientation of place. Handicraft is the standard mark of creativity and the essential differentiator for a country in the sweeping wines of globalization at world level.

In conclusion , it can be considered that in the age of commercialization, handicraft industry can sustain only by innovative design and essence of ethnicity. The heart of handicraft sector is its aesthetic appeals and distinctive presence. But the handicraft industry can help India to secure distinguish position into global perspective and SWOT analysis is highly direction oriented path in this competitive age.

REFERENCES

1. Joshi S. (2016), "Indian handicraft & globalization: in context of export", IGI Global, pp 175-184.
2. Jadhav S. (2013), "Indian handicraft industry Growing or Depleting?", IOSR Journal of Business and Management (IOSR-JBM) e-ISSN: 2278-487X, p-ISSN: 2319-7668 .
3. Craftcil: comprehensive handicraft industry Magazines, <https://www.epch.in/index.php/craftcil>
4. Khan A. (2013), "Study of handicraft marketing strategies of artisans in Uttar Pradesh and its implications", International Science Congress Association, Vol. 2(2)
5. Indianhandicraftsportal <https://www.epch.in/index.php/craftcil>



AN ANALYSIS OF KEY DIMENSIONS OF LOGISTICS SERVICE QUALITY IN THE SHIPPING INDUSTRY

Dr K.Kaleeswaran, Associate Professor & Head, Department of Maritime Management, Tolani Maritime Institute, Induri, Pune.
kaleeswarank@tmi.tolani.edu

Mr Abhishek Pandey, Assistant Professor, Department of Maritime Management, Tolani Maritime Institute, Pune,
abhishekp@tmi.tolani.edu

Abstract- *The present study examined the key span of Logistics Service Quality in the Shipping Industries in Tamil Nadu. Simple random sampling is used in this study to select the sample. As a result, 457 (filled-out) valid questionnaires were available and used for further analysis in SPSS version 21. A structured questionnaire was used to collect the data, while Correlation analysis was used to analyse the data. The results revealed that the correlation coefficient for Logistics Service Quality in the shipping industry is strong and certain. Hence, the study concluded the key dimensions of Logistics Service Quality in the Shipping Industry.*

Keywords: *Service Quality, Logistics Service Quality, Shipping Industries.*

I. INTRODUCTION

The shipping sector is essential to enabling global trade and supply chain effectiveness in today's fiercely competitive and interconnected marketplace. Logistics service providers are under growing pressure to supply value-added services and goods with high dependability and consistency as customer assurance continue to climb. Due to the result, logistics service quality, or LSQ, has become a crucial component of long-term company performance and customer pleasure and loyalty. Timeliness, correctness, communication, responsiveness, and service reliability are just some of the dimensions that create LSQ. Understanding these factors is even more important in the shipping industry, where cargo handling, delays, and tracking transparency has a big impact on results. More systematic analysis in which various aspects of service quality impact overall performance and customer opinions is still required, notwithstanding the operational complexity of the sector. This study aims to analyze the key span of logistics service quality specific to the shipping industry.^[1]

By identifying and evaluating these dimensions, the research seeks to give insights which help shipping companies enhance service delivery, strengthen client relationships, and holding a rival edge in the evolving global logistics landscape.

II. PROBLEM SUMMARY

In the increasingly competitive and globalized shipping industry, delivering high-quality logistics services are more essential for maintaining customer satisfaction, operational efficiency, and long-term business sustainability. However, many shipping companies struggle to identify and effectively manage the specific dimensions of logistics service quality (LSQ) that most influence performance and customer perceptions. While service quality frameworks exist, there is a lack of industry-specific empirical analysis focusing on the key span of LSQ in the shipping sector, where operational complexities, international

regulations, and customer expectations differ significantly from other logistics domains. Without a clear understanding of which LSQ dimensions, such as timeliness, order fulfilment, information quality, corporate image, and customer focus, have the most significant impact, shipping companies risk misallocating resources and failing to meet customer expectations. This research addresses the gap by analyzing these critical dimensions which produce actionable insights that will help shipping firms to increase service delivery, better customer satisfaction, and strengthen their rival position in the global marketplace.

III. LITERATURE REVIEW

1. Xiang-Yi ZHOU et al. focused on "the relationship between online shopping logistics service quality and customer perception in the case of return and exchange". Assuring the punctuality and reliability of deliveries and improving responsiveness to user needs when returning goods significantly influence customer satisfaction in e-shopping. Along with improving customer satisfaction, online retailers can retain loyal customers by enhancing the customer experience of trust. Consequently, online retailers must enhance customer trust and maintain loyalty through superior product and service quality, as well as fostering strong customer relationships; concurrently, Chinese logistics service providers must expedite the transition from conventional logistics to information logistic to align with the evolving dynamics of the E- shopping sector.^[2]
2. Mingxing li et al. revealed that "service quality has a significant positive impact on customer satisfaction". This recommend that aspects of quality service covered in the research, have a direct bearing on customer satisfaction. The study comes to the conclusion that in order to improve consumer happiness, JUMIA and other e- shopping platforms should increase the quality of their services. Since the study's conclusions show that improved service quality boosts consumer happiness, service quality is a top priority for all business-oriented enterprises, but especially for online retailers. There are many ways to develop the service quality, with special focus on client ease. An online organization's primary goal is customer fulfillment, which calls for it to pay close attention to it. Businesses, particularly those operating online, concentrate on improving perceived comfort in order to project a clear picture to clients. These routes have a tremendous impact on organization and help the business thrive.
3. Al Nasrie Weli., study, "concentrated only in Sabah and excluding the respondents from Peninsular Malaysia". Peninsular Malaysia could be included in future studies to evaluate it. Additionally, this study only looks at land

transportation; other modes should be included in future studies. By addressing customer satisfaction with services, this study benefited the sector and individuals working for the logistics organization. Additionally, the report might be useful to politicians who are reviewing and bolstering current policies.

4. Barbara et al., this study, “describes how seven dimensions of LSQ lead to achieving customer satisfaction, particularly highlighting and discussing how the different LSQ constructs lead to gaining high customer satisfaction via different configurations”. Although we were able to offer distinctive managerial perception thanks to our methodological approach, our study has limitations and presents opportunities for further research. They find out if customer fulfillment and behavioral firmness are impacted by the length of the customer-3PL service provider relationship. Futurity research should also contrast the outcomes of QCA and conventional regression analysis. Further studies might additionally look into defining and extending the effects on particular performance outcomes, like agility, resilience, adaptability, loyalty, and word-of-mouth. Because there can be variations, future studies should look at the research topic in the context of other markets and industries. Lastly, to further support the findings' generalizability, future studies should examine LSQ antecedents across industries and carry out longitudinal assessments of past, present, and future perceptions.^[4]

5. Hasan Uvet conducted research in “investigate the customers' satisfaction in logistics services from the perspective of logistics service quality factors”. The findings show a strong correlation among perceived customer fulfillment in logistics services, operational information sharing, personnel contact quality, order condition, and timeliness. These findings show that the two most important aspects of physical distribution service quality—timeliness and order condition—remain crucial in LSQ. Furthermore, the findings indicate that satisfaction views are highly impacted by Personnel Contact Quality, the three primary elements of service quality. Furthermore, it was found that beneficial impact of high-quality personal interaction on customer fulfillment is mediated by operational information exchange. The confederation among Operational Information Sharing and Personal Contact Quality is partially mediated. We found that the negative impact of timeliness on customer fulfillment is mitigated by order-discrepancy handling. The favorable correlation among timeliness and customer fulfillment is weakened by ordering discrepancy handling.^[5]

6. Nugroho. concluded that “the ability of good logistics services will make customers satisfied, and the level of customer satisfaction increases”. Customers that are happy with a firm are more inclined to buy from it again. Establishing a team to accept and handle client issues is one of the things that managers of rice-producing enterprises should think about. Additionally, the business can offer

surveys to customers directly following service delivery or through complaint and suggestion boxes. Additional variables, such consumer loyalty, can be incorporated into future studies. It is also required to expand the sample size such that it encompasses customer from several rice-producing company, instead of just one.^[6]

7. Guan Hui, Gamze Arabelen et al., found that “LSQ comprehending and application have been revolving the business focus of LSPs. They have used a variety of strategies as the quality factors in logistics has evolved. The LSQ dimensions' emphasis has changed throughout time in the sample, which amply demonstrates changes in the importance placed on quality. The physical characteristics of functions, such as distribution and timeliness-related dimensions, are the primary focus of quality attention, according to early-established LSQ dimensions produced during a 20-year period. Customer-related LSQ aspects, like empathy and personal service/contact, have emerged in later times as output of logistics services becoming more customer-oriented throughout time. According to semi-structured interviews, the vital span of LSPs is the dimensional changeover. Thus, it's now vital than ever for LSPs to establish good client connections by sympathetic, ongoing interaction. Even if there are measurement models made especially for logistics services, the SERVQUAL model appears to have been utilized frequently by researchers, despite the huge number of empirical studies that use it in LSQ. This suggests that the search for LSQ dimensions and measuring tactics not yet finished; as an output, it is still subject to development and could eventually result in the widely accepted LSQ measurement technique. Through a methodical analysis of previous research and measurement methodologies, this study offers logistics professionals a foundation for quality service in logistics. Through a methodical literature analysis that organizes and systematizes the body of extant literature, important quality span has been constructed. Five dimensions—customer preoccupation quality, order fulfilment quality, quality timeliness, quality information, business image and social responsibility, and the twenty-four factors—have therefore been incorporated into the LSQ framework. LSQ span for additional measuring models are claimed by the research model's holistic approach.^[7]

8. Tchamyu, this study “aimed to determine the effect of electronic commerce users' evaluations about logistics service quality on customer satisfaction and the relationship between customer satisfaction and customer loyalty”. Customer fulfillment and punctuality were found to be positively correlated. This result is in line with what other researchers have found. In order to be considered timely, the ordered goods must be delivered to clients in whole and undamaged at the time specified during the order process. Customers might not get the expected benefits from a product if it is delivered to them later than the scheduled date. Customers might decide to buy from a

different business in this situation. Customer satisfaction and order condition were found to be positively correlated. This conclusion is also supported by another research. It demands that the consumer receive the requested product unharmed and intact. The products should be kept in suitable packaging that won't get damaged during handling or transit in order to guarantee this. Additionally, anti-spoilage measures should be put in place, especially for goods with unique resistance requirements, including food and health items, while keeping transportation time in mind. Customer happiness and order accuracy are found to be positively correlated. This result is in line with other research findings. If a delivery is made incorrectly, the corporation will have to spend more time and money fixing the mistake. If a consumer receives the product they ordered incorrectly, they will remember this experience and might not place as many orders with the same business in the future.[8]

9. Weli, A., et. al investigated "the impact of LSQ on repurchase intention based on the LSQ (experience)–satisfaction–repurchase intention consequence chain. Data were collected from 466 Chinese consumers who had engaged in online shopping with international vendors". The model was tested using partial least squares structural equation modelling. The findings show that cross-border online shopping experiences, return logistics services, and delivery service quality all have a big impact on customer happiness. However, there is no evidence to substantiate the links between customer happiness, price fairness, delivery stability, and delivery information service. Cross-border repurchase intentions are positively impacted by price fairness, customer satisfaction, and the cross-border online purchasing experience. Furthermore, LSQ, price fairness, cross-border online shopping experience, and repurchase intention are all mediated by consumer happiness. Compared to domestic e-commerce, this study is innovative because it focuses on the cross-border dimension and introduces additional aspects like pricing fairness and cross-border online shopping experiences, which add other variable that affect LSQ and consumer satisfaction. By providing fresh perspectives on the intricate dynamics of LSQ in CBEC and emphasizing the complicated mediating function of customer satisfaction in various market conditions, this study adds to the body of literature. It adds to the corpus of knowledge by providing actual data and insightful information about the various facets of LSQ and customer satisfaction.[9]

IV. OBJECTIVES

To study the relationship between various key spans of Logistics Service Quality in the Shipping industry.

V. METHODOLOGY

Totally 457 logistics service providers has been chosen for the study. For this study, the researcher used a well-structured questionnaire to collect the data from the

respondents.

The questionnaire includes variables related to Logistics Service Quality in the Shipping Industry. The researcher used correlation analysis to identify relationships among variables in Logistics Service Quality. IBM SPSS 21 version was used for statistical purposes.

VI. DESIGN & CALCULATIONS

Company size is classified into three, small, medium, and large.

Analyzing the Logistics Quality of service in Shipping Industries in Tamil Nadu based on the size of the company is required for this study. The distribution of respondents by company size is given below.

Table 1: Size of the Company: Wise classification of respondents

Size of the Company	Frequency	Percent
Small	154	33.7
Medium	164	35.9
Large	139	30.4
Total	457	100.0

The distribution of companies by size is relatively balanced in the sample of 457 Companies. Medium-sized companies. Small companies hold the largest share at 35.9% (164), followed closely by medium-sized companies at 33.7% (154). Large companies make up the remaining 30.4% (139), representing the smallest share but still a substantial portion of the sample. Hence, the data indicate that small and medium-sized enterprises dominate the sample. However, the three categories are represented, suggesting a diverse range of organizational sizes in the study.




Figure 1: Size of the company-wise classification of respondents

1. Nature of Mode-wise classification of respondents

This is classified into two, import and Export. Analyzing the Logistics Quality of service in Shipping Industries in Tamil Nadu on the basis of nature of the mode is required for this study. The distribution of respondents by Nature of Mode is shown in the table below.

Table 2: Nature of Mode-wise classification of respondents

Nature of Mode	Frequency	Percent
Import	200	43.8
Export	257	56.2
Total	457	100.0

56.2% (257) engage primarily in export activities, while the remaining 43.8% (200) are involved in import operations. This distribution suggests that a greater proportion of the companies operate as exporters, highlighting a stronger orientation toward outward trade within the sample.




Figure 2: Nature of mode-wise classification of respondents

2. Ships-wise classification of respondents

In this study, ships are classified into two categories: National Ships and International Ships. Studying the Logistics Service Quality of the Shipping Industry in Tamil Nadu by ship type is essential for this study—the distribution of respondents by ship type. The number of Ships is shown in the table below.

72.0% (329) reported using international ships, while only 28.0% (128) relied on national boats. This indicates that most companies prefer or require international shipping services, likely reflecting the global nature of their trade activities and the need for broader logistical reach.

Table 3: SHIP-WISE CLASSIFICATION OF RESPONDENTS

Type of Ships	Frequency	Percent
National Ships	128	28.0
International Ships	329	72.0
Total	457	100.0




Figure 3: Ship-wise classification of respondents

3. Relationship among dimensions of Logistics Service Quality

Logistics Service Quality comprises five factors: Timeliness, Order Fulfilment, Corporate Image, Information Quality, and Customer Focus.

Ho: There is no relationship among various dimensions of Logistics Service Quality.

Table 4: RELATIONSHIP AMONG DIMENSIONS OF LOGISTICS SERVICE QUALITY

Logistics Service Quality	Time- liness	Order Fulfil ment	Corporat e Image	Informat ion Quality	Custo mer Focus
Timeliness	1.00 0	0.4 20**	0.059	0.065	0.391
Order Fulfilment		1.0 00	0.180* *	0.051	0.332* *
Corporate Image			1.000	0.262**	0.039
Informatio n Quality				1.000	0.259
Customer Focus					1.000* *

**. Correlation is significant at the 0.01 level (2-tailed).

From the above table, it can be inferred that the correlation coefficient for Logistics Service Quality is strong and positive. The correlation analysis reveals several essential relationships among the key dimensions of logistics service quality in the shipping industry. Timeliness shows a moderate, statistically significant positive correlation with order fulfilment ($r = 0.420^{**}$) and a weaker but notable correlation with information quality ($r = 0.391$), indicating that timely delivery contributes to effective order processing and enhances the quality of information shared with customers. However, its correlation with corporate image ($r = 0.059$) and customer focus ($r = 0.065$) is weak and not statistically significant, suggesting limited direct influence in these areas. Order fulfilment also demonstrates substantial positive correlations with corporate image ($r = 0.180^{**}$) and information quality ($r = 0.332^{**}$), implying that fulfilling customer orders accurately and reliably helps reinforce the company's image and the reliability of the



information provided. In contrast, its relationship with customer focus ($r = 0.051$) is weak and not statistically meaningful.

Corporate image shows a moderate and significant correlation only with information quality ($r = 0.262^{**}$), suggesting that organisations perceived as providing accurate and timely information are more likely to have a positive public image.

Interestingly, customer focus correlates significantly only with information quality ($r = 0.259^{**}$), indicating that high-quality communication and information are key drivers of a customer-centric approach. At the same time, operational aspects such as timeliness and fulfilment appear to have less direct impact. Overall, the analysis suggests that while timeliness and order fulfilment are closely related and critical to operational efficiency, information quality emerges as a central factor linking operational performance with corporate image and customer focus, underscoring its strategic importance in delivering high logistics service quality.

VII. CONCLUSIONS

This study examined the key dimensions of logistics service quality (LSQ) in the shipping industry, emphasizing timeliness, order fulfilment, information quality, corporate image, and customer focus. Important contextual insights into the industry's operating environment are provided by the sample makeup, which is dominated by small and medium-sized businesses, a majority of export-oriented firms, and a significant reliance on international shipping. The need of effective, internationally-aligned logistics services is highlighted by the large number of export-oriented businesses and the use of international shipping. In this regard, the results show that order fulfilment and timeliness are closely related and crucial operational pillars that enable international shipping and export operations. Another crucial factor that stands out is information quality, which has a big impact on company image and customer focus and serves as a strategic bridge between operational dependability and client-focused results. Relationship management, transparency, and communication are crucial for businesses competing in an international logistics environment, even though corporate image and customer focus have fewer relationships with operational variables. All things considered, the study confirms that the quality of logistics services is multifaceted and necessitates a well-rounded strategy that combines excellent operational performance with sound client interaction procedures. Shipping firms can improve customer satisfaction, strengthen service delivery, and get a continuous competitive edge in the global logistics market by focusing on the most important LSQ dimensions and comprehending the operational traits of their clientele.

REFERENCES

- [1] Akıl, S. "E-commerce logistics service quality: Customer satisfaction and loyalty", in *Electronic Commerce in Organisations*, pp. 1–19, <https://doi.org/10.4018/JECO.2022010101>, (April 2022)
- [2] Zhou, X.-Y., Li, M., & Xu, L., "The empirical study of logistics service quality evaluation within electronic retail", 4th Annual International Conference on Management, Economics and Social Development (ICMESD 2018), 198–204, (2018)
- [3] Mingxing Li Arabelen, G., Sezgin, F., & Süral, H., "Assessment of logistics service quality dimensions: A qualitative approach", *Journal of Shipping and Trade*, 6(1), Article14, 1–13, <https://doi.org/10.1186/s41072-021-00087-4> (Sep-2021)
- [4] Gaudenzi, B., Bielli, P., & Borghesi, A., "Logistics service quality and customer satisfaction in B2B relationships: A qualitative comparative analysis approach", *The TQM Journal*, pp. 33 (1), pp. 125–140, <https://doi.org/10.1108/TQM-12-2019-0289>, (June- 2020)
- [5] Uvet, H., "Importance of logistics service quality in customer satisfaction", *An empirical study. Operations and Supply Chain Management*, 13(1), 1–10. <https://doi.org/10.31387/oscm0420275>.
- [6] Nugroho, S., Subriadi, A. P., & Ruldeviyani, Y., "Logistic service quality and customer satisfaction to customer retention on rice producer industry", *SHS Web of Conferences*, 76, 01048, pp. 1–11, <https://doi.org/10.1051/shsconf/20207601048>, (2020)
- [7] Guan Hui, Abdullah Al Mamun, Mohammad Nurul Hassan Reza, Wan Mohd Hirwani Wan Hussain. An empirical study on "logistic service quality, customer satisfaction, and cross-border repurchase intention, *Heliyon*", 11(1), e41156. <https://doi.org/10.1016/j.heliyon.2024.e41156>, (2025)
- [8] Tchamyou, S. V., & Ndzana, N. G. "Impact of logistics service quality on customer satisfaction: Evidence from Cameroon", *International Journal of Economics, Commerce and Management*, 7(11), 333–351, (2019)
- [9] Weli, A. N., Ariffin, M. I., & Ong, H. B., "Level of satisfaction among industrial customers in relation to logistics service provider in Sabah", *Global Business and Management Research: An International Journal*, 12(4), 466–476, (2020)

STANDARDIZATION VS. SPECIALIZATION: A COMPARATIVE REVIEW OF BBA PROGRAMS IN INDIA

Manoj S. Jagnade

Assistant Professor, Department of Maritime Management,
Tolani Maritime Institute, Pune,
manoj_s@tmi.tolani.edu

Nandini Pawar

Department of Maritime Management, Tolani Maritime
Institute, Pune,
nandini.spawar2025bba@gmail.com

Abstract: *The globalization of trade and the increasing complexity of supply chains have amplified the demand for domain-specific management education, particularly in logistics and maritime sectors. This study presents a qualitative comparative analysis between the University Grants Commission (UGC)-All India Council for Technical Education (AICTE) model Bachelor of Business Administration (BBA) curriculum and the Indian Maritime University's (IMU) specialized BBA in Maritime Logistics (BBA-ML). Using curriculum mapping, regulatory framework review, industry alignment assessment, and career outcome evaluation, the research highlights the pedagogical, structural, and outcome-based differences between a generalist and a specialist undergraduate program. Findings reveal that while the UGC-AICTE BBA offers broad managerial competencies and multi-sector employability, the IMU BBA-ML delivers deep, industry-integrated expertise in maritime logistics through mandatory apprenticeships, regulatory compliance training, and global benchmarking. The paper concludes with recommendations for aligning management education with evolving industry needs, emphasizing experiential learning, digital literacy, Logistics knowledge and sustainability as core competencies for future-ready graduates.*

Keywords: *Logistics and maritime sectors, Apprenticeship, BBA curriculum, Maritime Logistics, Curriculum mapping, Regulatory framework review.*

I. INTRODUCTION

It is axiomatic that business education forms the backbone of managerial talent for India's diverse and rapidly evolving economic landscape. Traditionally, undergraduate business degrees, such as the Bachelor of Business Administration (BBA), have been designed to equip students with core competencies in management, finance, marketing, human resources, and entrepreneurship. However, as business ecosystems become more globalized and technologically intertwined, the demand for domain-specific expertise especially in sectors integral to India's economic strategy, such as logistics, maritime trade, and supply chain management has increased substantially. The Indian government's policy emphasis on transforming the logistics sector, particularly through initiatives such as the National

Logistics Policy and large-scale port modernization programs, further underscores this imperative.

Concurrent with these macroeconomic transformations, there has been a notable shift in the regulatory and curricular frameworks governing undergraduate management education in India. In 2024, the AICTE expanded its regulatory purview to include BBA and allied programs, previously under the UGC, to ensure consistency, industry alignment, and quality control across institutions. Against this backdrop, specialized programs-such as the Indian Maritime University's BBA in Maritime Logistics-have gained prominence for their targeted preparation of graduates to meet sectoral workforce needs.

This study compares the UGC-AICTE model BBA curriculum and the IMU BBA-ML program, interrogating their curricular design, regulatory structures, industry integration, and impact on employability. It provides subject-level mapping, analyses the scope of experiential learning, and critically assesses career pathways in general business and maritime logistics, all within the framework of qualitative curriculum analysis.

II. LITERATURE REVIEW

The literature on curriculum design, regulatory frameworks, and sector-specific management education provides a strong foundation for understanding the comparative positioning of the UGC-AICTE model BBA and the Indian Maritime University's BBA in Maritime Logistics (BBA-ML). This review synthesizes prior studies, policy documents, and global benchmarks relevant to the present analysis.

1. Curriculum Design and Pedagogical Frameworks

Curriculum theory, as articulated by Tyler (1949) and Posner (2004), emphasizes the alignment of learning objectives, instructional content, pedagogy, and assessment. In the Indian context, the AICTE Model Curriculum for BBA (2024) reflects the National Education Policy (NEP) 2020's call for



multidisciplinary learning, flexible entry–exit options, and experiential components. Specialized curricula, such as IMU's BBA-ML, adopt a competency-based approach (CBT) that embeds sector-specific knowledge from the outset, aligning with international best practices in vocational higher education (Erasmus University, 2023). Comparative studies (Dmitriyev & Lerner, 2021) suggest that early domain immersion enhances graduate readiness for regulated industries [1][2][3][4][5].

2. Regulatory and Accreditation Context

The shift of BBA program oversight from the University Grants Commission (UGC) to the All India Council for Technical Education (AICTE) in 2024 aimed to standardize quality and strengthen industry linkages across more than 4,200 institutions. AICTE's governance model mandates experiential learning, skill-enhancement courses, and a research orientation. Conversely, IMU operates under the Ministry of Ports, Shipping, and Waterways, with curricula developed by the Directorate General of Shipping (DG Shipping) and aligned with International Maritime Organization (IMO) conventions, including SOLAS, MARPOL, ISM, and ISPS. The literature on higher education governance (NAAC, NBA, AACSB frameworks) underscores that accreditation bodies play a pivotal role in ensuring that curricula are responsive to evolving industry needs [6][7][8][9].

3. Industry Alignment and Experiential Learning

Work-integrated learning models, such as Germany's dual education system and Singapore's maritime training framework, demonstrate the value of structured apprenticeships in bridging academic theory and workplace practice (Billett, 2011). The AICTE BBA model incorporates internships and capstone projects, but the depth and sectoral focus of these components vary across institutions. In contrast, IMU's BBA-ML requires a two-semester apprenticeship with shipping lines, port authorities, and logistics operators, ensuring sustained immersion in industry. Studies by the Logistics Sector Skill Council (2022) indicate that such embedded apprenticeships significantly improve employability in specialised sectors [10-15].

4. Employability and Career Pathways

Research on graduate employability (Yorke, 2006; Careers360, 2024) indicates that domain-specific programs yield higher immediate placement rates in targeted industries, while generalist degrees offer

broader career flexibility but may require postgraduate specialization. IMU graduates benefit from built-in professional certifications (e.g., STCW, ISM) that are prerequisites for many maritime roles. General BBA graduates, while versatile, often pursue additional certifications or MBAs to secure specialized positions in logistics and supply chain management [16][17][18].

5. Global Benchmarking and Emerging Trends

The international maritime education literature (Stopford, 2020; UNCTAD, 2023) identifies digitalization, sustainability, and regulatory compliance as critical future competencies. Technologies such as blockchain for shipping documentation, AI for route optimization, and green shipping practices are increasingly integrated into leading maritime curricula. Benchmarking studies indicate that IMU's BBA-ML, with its regulatory compliance modules and global collaborations, is more closely aligned with these trends than many generalist BBA programs in India [19][20][21].

III. RESEARCH OBJECTIVES

- i. Compare the curriculum design, content, and pedagogical strategies of the UGC-AICTE model BBA and IMU's specialised BBA in Maritime Logistics.
- ii. Analyse the regulatory and accreditation frameworks governing both programs and their implications for quality assurance and industry readiness.
- iii. Assess the degree of industry alignment and experiential learning integrated into each curriculum, especially concerning sector-specific competencies.
- iv. Evaluate employability outcomes and professional development trajectories for graduates of general BBA and BBA-ML programs.
- v. Provide recommendations for curriculum enhancement in light of global standards and sectoral trends in logistics and maritime management education.

IV. METHODOLOGY

4.1. Qualitative Curriculum Analysis

The research employs content and thematic analyses, as outlined by Posner (2004), Tyler (1949), and recent educational scholarship, to examine curriculum structures, subject distributions, and pedagogical approaches across both programs. The analysis

benchmarks the UGC-AICTE BBA curriculum (2024 revision) against IMU's BBA-ML curriculum (2022–2025 syllabi and program structures), focusing on subject lists, credit requirements, and experiential learning modules.

- i. Curriculum Structure Overview
- ii. UGC-AICTE Model BBA Curriculum

The AICTE-regulated BBA curriculum, adopted by most Indian universities by 2024, exhibits the following hallmarks:

- i. Three-to-Four Year Structure: 3-year BBA (120 credits), with a 4th-year Honours/Research option (160 credits).
- ii. Flexible Entry/Exit Points: Certificate (after Year 1), Diploma (after Year 2), Degree (after Year 3), Honours/Research (after Year 4).
- iii. Credit and Course Distribution: Mix of Core Subjects (Finance, HRM, Marketing, Accounting, Strategy), Multi-Disciplinary Electives, Value Added Courses, Skill Enhancement, Discipline-Specific Electives, and Major Project/Internship components.
- iv. Specialisation Streams: Finance, Marketing, HRM, Business Analytics, International Business, Operations, Retail, Entrepreneurship, IT, and recently, Logistics & Supply Chain Management as a possible track.
- v. Experiential Learning: Emphasis on internships (6-8 weeks), capstone and project work, industry visits, and optional apprenticeships.

IMU BBA in Maritime Logistics (BBA-ML)

IMU's BBA-ML program, offered with an embedded apprenticeship, is distinctively sector-specific:

- i. Three-Year Program (Six Semesters): No early exit; completion requires 140 credits.
- ii. Domain-Focused Core: Shipping economics, port management, marine insurance, freight forwarding, EXIM policy & procedures, coastal transportation, maritime regulations, and supply chain management.
- iii. Mandatory Apprenticeship: Two-semester (Semester V and VI) industry apprenticeship with leading logistics and shipping firms; regular port and industry visits throughout the program.
- iv. Assessment: Practical training, internship reports, and project work are heavily weighted, with credit allocation reflecting industry immersion.

TABLE 1: COMPARATIVE CURRICULUM DIMENSIONS TABLE

Dimension	UGC/AICTE BBA (Standardised)	IMU BBA in Maritime Logistics (Specialised)
Regulatory Body	UGC/AICTE	IMU (Autonomous, under the Ministry of Ports, Shipping, GoI)
Duration	3–4 years, multiple entry/exit	3 years; no early exit until 2025; multiple entry/exit thereafter. From now on, multiple entries and exits.
Core Focus	Management, Finance, HR, Marketing, Analytics	Maritime logistics, shipping, port management, trade law
Specialization	Elective (incl. Supply Chain as track)	Directly, the entire program is sector-focused
Credits Required	120–160	120
Experiential Learning	Internships (optional/mandatory), projects	Mandatory apprenticeships, port visits, and industry seminars
Industry Alignment	Multi-industry, generic	Maritime, logistics, EXIM, compliance-centred
Professional Certification	Optional (sectoral certificates possible)	Aligned with maritime safety, logistics, and DG Shipping requirements.
Career Pathways	Diversified: Finance, Marketing, HR, Analytics, Consulting, Start-ups	Shore-based logistics/port roles, shipping, supply chain

Employability	Widely employable, but depth by postgrad or certification	Direct entry to the maritime/logistics sector, higher placement rates
Curriculum Governance	UGC/AICTE standards	IMU Act, DG Shipping, international conventions

The table demonstrates that the UGC-AICTE BBA is inherently flexible and generic, designed to provide a broad managerial foundation adaptable to many sectors. By contrast, IMU's BBA-ML offers deep, vertically integrated domain knowledge targeted at maritime logistics, with experiential learning, regulatory compliance, and international standards embedded as core elements.

TABLE 2: SUBJECT-LEVEL COMPARISON
TABLE

Subject Category	UGC BBA Core Subjects	IMU BBA-ML Core Subjects
Fundamental Management	Principles of Management, Business Communication, Organisational Behaviour	Principles of Maritime Management, Business English Communication
Economics	Microeconomics, Macroeconomics	Economics of Sea Transport, Shipping Economics
Finance & Accounting	Financial Accounting, Cost & Management Accounting	Maritime Cost Accounting, Shipping Finance
Marketing	Marketing Management, Consumer Behaviour	Brand Management, Digital Marketing in Shipping
Human Resources	Human Resource Management	HRM with focus on Seafaring/Maritime Staff
Operations/SCM	Operations Mgmt., Supply Chain Mgmt. (elective)	Supply Chain Management, Port & Terminal Management

International Business	International Business	EXIM Documentation, Global Logistics, Trade Policy
Legal/Regulatory	Business Law, Corporate Law	Maritime Law, Legal Principles in Shipping Business
Technology/Analytics	MIS for Business, Business Analytics, IT Lab	Maritime Information Systems, Logistics Tech
Apprenticeship/Project	Internship, Capstone Project (varies in depth)	2-Semester Apprenticeship, Project Work

In summary, while the two curricula share basic managerial foundations, the IMU BBA-ML curriculum diverges by providing early, continuous, and cumulative exposure to maritime and logistics content—including compliance, technical operations, and international documentation that are indispensable to the industry.

4.2. Regulatory and Industry Review

Documents and circulars from AICTE, UGC, IMU, and industry stakeholders are examined to map accreditation requirements, regulatory authorities, and program management protocols. Emphasis is placed on recent shifts toward AICTE oversight for undergraduate management education and IMU's integration with the Directorate General of Shipping (DG Shipping) and international maritime conventions.

Regulatory Frameworks and Accreditation

UGC/AICTE BBA Regulatory Model

- AICTE as National Regulator from 2024 Onwards: The AICTE BBA Model Curriculum applies across 4,200+ institutions and mandates multiple entry/exit, experiential exposure, and research/industry orientation as per NEP 2020 recommendations.
- Curriculum Governance: Institutes must conform to the AICTE model curriculum but retain some autonomy for electives and credits. Accredited

institutions benefit from access to teaching resources, industry engagement programs, and national monitoring (NAAC, NBA, AACSB).

IMU BBA-ML Accreditation and Governance

- i. IMU's Autonomous Status: Established by Act of Parliament, IMU is a central university under the Ministry of Ports, Shipping, and Waterways. Programs are shaped by regulatory requirements of DG Shipping and aligned with International Maritime Organisation (IMO) conventions¹².
- ii. Compliance Tracking: Regular curriculum updates ensure compliance with international safety and trade standards (SOLAS, MARPOL, ISM, ISPS). Apprenticeship integration is coordinated with the Logistics Sector Skill Council under NSDC¹².
- iii. Global Collaborations: IMU regularly collaborates with international institutions (e.g., Erasmus University, Port Authority of Singapore) and participates in academic benchmarking initiatives¹⁷.

Thus, both programs exhibit rigorous regulatory alignment, but IMU's governance is more closely coupled to sector-specific regulatory and operational standards in the maritime and logistics domains.

Industry Alignment and Experiential Learning

UGC-AICTE BBA

Contemporary BBA programs under the AICTE/UGC model curriculum increasingly feature:

- i. Internships/Capstone Projects: 6–8 week summer internships, mandatory project/dissertation work, industry fieldwork, and capstone simulation modules (especially in Honours/Research tracks).
- ii. Case Studies and Industry Workshops: Programs embed industry cases, field visits, and expert lectures from the broader business landscape, but the focus remains generic unless electives are sectorally defined.
- iii. Employability Augmentation: Students are encouraged to pursue certifications in data analytics, AI, digital marketing, and supply chain (e.g., Power BI, MySQL, MS Excel) to improve their employability.

While exposure is robust in top colleges, the delivery of experiential learning and industry integration varies

significantly across institutions due to varying levels of autonomy and resource disparities.

IMU BBA-ML

IMU's curriculum stands out for:

- i. Mandatory Apprenticeship: All students participate in a structured, two-semester apprenticeship, working directly with shipping lines, port authorities, and logistics operators—an experience akin to dual-education models seen in advanced economies like Germany and Singapore¹⁴.
- ii. Immersion in Operations: Regular industrial visits, port simulations, seminars by practitioners, and direct project assignments with partner organisations dominate the pedagogical approach. Exposure includes real-time logistics management, customs and EXIM documentation, and international compliance requirements¹².
- iii. Employer Partnerships: IMU maintains formal MoUs with sector leaders and international organisations for curriculum development, apprenticeships, and joint research, ensuring practice-relevant learning and seamless transition to the job market.

The industry-aligned, practice-driven model of IMU's BBA-ML represents a significant departure from the more academically structured, optionally experiential, general BBA.

Subject-Level Curriculum Analysis

To uncover the nuances of curricular orientation and depth, the comparison below employs Dmitriyev and Lerner's analytic model (thematic, disciplinary, resource, pedagogical, and application levels).

Management Fundamentals

Both curricula introduce management theory, organisational behaviour, and decision-making processes in the first year, but with different emphases:

- i. UGC BBA: Focus on general management concepts, classical and contemporary theories, leadership styles, planning/control, and communication within a business context. Employs case-based assignments, simulations, and group discussions for active learning ¹⁹.
- ii. IMU BBA-ML: The "Principles of Maritime Management" integrates core management



principles with maritime-specific examples—fleet management, port authority roles, ship-broking operations—emphasising the translation of management concepts to logistics and shipping environments.

Logistics and Supply Chain Content

- i. UGC BBA: Logistics and supply chain management may appear as an elective or specialisation in later semesters. The coverage focuses on global supply chain drivers, distribution networks, and inventory management and logistics, but at a theoretical level only; further development is required through advanced electives or postgraduate study.
- ii. IMU BBA-ML: Logistics, warehousing, and supply chain operations are embedded from the outset, with foundational courses escalating to advanced topics such as multimodal transport, port & terminal management, international shipping law, and maritime documentation (including Incoterms 2020 and UCP 600 protocols).

Law, Compliance, and Industry Standards

- i. UGC BBA: Business Law, Company Law, and Corporate Governance modules primarily engage with Indian legal frameworks for commerce, with some electives in international business law in select programs.
- ii. IMU BBA-ML: Provides in-depth treatment of maritime conventions (IMO regulations), international shipping law, EXIM documentation, insurance, and environmental compliance under MARPOL, ISM, and SOLAS. The law modules are directly linked to practical shipping scenarios and regulatory documentation, which are crucial for graduates in operational roles at ports and shipping firms.

Digital, Technical, and Analytical Skills

- i. UGC BBA: Focus on business analytics, MIS, and emerging technologies in management. Electives provide preliminary exposure to analytics using platforms such as Power BI, R, and Python. Top colleges may supplement with AI/ML labs and e-commerce modules in later years.
- ii. IMU BBA-ML: Coursework incorporates management information systems tailored to logistics operations, tools for shipping management, digital documentation, and

simulation of port operations. Up-to-date exposure to technologies such as blockchain in documentation and AI for route optimisation is increasingly featured in IMU curricula.

Research, Internships, and Professional Presentation

- i. UGC BBA: Honours or research tracks include modules in research methodology, advanced data analysis, and dissertation writing; project presentation and formal viva processes are standard in accredited institutions¹⁸.
- ii. IMU BBA-ML: Final semester project and internship reports, based on field studies or operational data from apprenticeships, are assessed in partnership with industry mentors and academic supervisors—mirroring capstone or thesis-based evaluations but with greater practical orientation.

4.3. Career Pathway and Outcome Evaluation

Recent placement data, recruiter feedback, and alumni trajectories (from Careers360, Shiksha, Collegedunia, and direct university placement cell reports) are synthesised to trace employability results. Web-based qualitative sources provide insight into evolving job roles, average salaries, and recruiter expectations for BBA and BBA-ML graduates.

- i. Career Perspective Analysis
- ii. Employability Outcomes: General BBA

General BBA graduates benefit from:

- i. Wide Career Flexibility: Entry-level roles span human resources, marketing, sales, finance, operations, and analytics across FMCG, banking, retail, consulting, e-commerce, and startups.
- ii. Entry-Level Salaries: Average starting packages range from ₹2.5 to ₹6 LPA, rising to ₹10 LPA or more in top-tier institutions or with strong internship/academic performance.
- iii. Typical Roles: Sales/marketing executive, business analyst, financial analyst, HR trainee, management trainee, operations manager, digital marketer, and customer relationship manager. Many graduates pursue further specialisation through an MBA or professional certifications (e.g., CFA, PGDM, analytics diplomas) to enhance vertical mobility.
- iv. Top Recruiters: Leading MNCs, Indian conglomerates, IT/ITES firms, startups, consulting firms, and financial institutions (e.g.,

TCS, HDFC, Accenture, Deloitte, Amazon, Infosys).

While a general BBA ensures broad employability, graduates may find it challenging to secure domain-specific managerial roles without further study or targeted practical experience due to a perceived lack of technical depth.

Employability Outcomes: IMU BBA-ML Graduates

IMU BBA-ML graduates exhibit:

- i. Domain-Embedded Employability: High placement rates (often $\geq 80\%$), with most graduates securing roles in maritime, shipping, logistics, export-import operations, and port management¹⁴.
- ii. Sector-Specific Roles: Port operations analyst, logistics coordinator, supply chain planner, marine insurance specialist, freight forwarding executive, warehouse manager, EXIM documentation officer, container terminal planner, and regulatory compliance associate.
- iii. Entry-Level and Mid-Career Salaries: Typical starting packages range from ₹3–9 LPA, with higher progression potential for those securing placements with global shipping majors or in specialised logistics management positions—reported figures extend to ₹12–24 LPA for high performers.
- iv. Professional Certification and Recognition: Graduates enter the job market with certifications required by DG Shipping and other international regulatory frameworks (e.g., STCW, ISM, SOLAS). Many roles—especially in liner shipping, port authorities, and international logistics—require such credentials for entry-level positions.

Moreover, the sector's expansion—propelled by port modernisation (e.g., Vizhinjam, JNPT, GIFT Port), e-commerce growth, global supply chain localisation, and government policies—drives strong demand for logistics professionals trained through such targeted programs.

Professional Development and Advancement

General BBA Track

- i. Long-Term Mobility: Graduates who pursue MBAs or professional certifications attain higher roles in strategy, corporate finance, analytics,

product management, and entrepreneurial leadership.

- ii. Horizontally Movable Skills: Communication, basic analytics, managerial acumen, leadership, adaptability, and multidisciplinary exposure allow successful cross-domain career shifts, including non-business sectors (e.g., media, policy).
- iii. Entrepreneurship and Innovation: Exposure to entrepreneurship modules primes graduates for start-up creation or management roles, provided they acquire specialised domain knowledge and practical experience in their field of interest²⁰.

IMU BBA-ML Track

- i. Sector Leadership: The progression typically follows linear roles, terminal/port management, ship brokerage, marine insurance, international trade compliance, and C-suite operations in maritime and logistics entities.
- ii. Certifications and Continued Learning: Career advancement is intricately linked to the acquisition of advanced maritime, safety, or trade compliance certifications, often internationally recognised and periodically renewed (e.g., STCW, ECDIS, ISM/ISPS, GMDSS). Many graduates also pursue specialised postgraduate degrees or industry certifications both in India and abroad.
- iii. Global Mobility: International conventions and IMU's global collaborations facilitate overseas career opportunities—a strategic advantage in a sector where international exposure significantly impacts advancement and remuneration prospects.

4.4. Global Benchmarking

Elements from international maritime and business management curricula are reviewed to situate both Indian programs within broader global trends, drawing comparisons to competency matrices, accreditation frameworks, and subject-level innovations from leading institutions.

Regulatory Frameworks and Curriculum Trends:

Global Standards:

Maritime logistics and port management education globally is transforming in response to digitalisation, sustainability, and resilient supply chain imperatives:



- i. **Competency-Based Training:** Leading universities and sector stakeholders increasingly require programs to align output with technical, management, and interpersonal competencies needed for modern maritime logistics—including data analysis, digitalisation, sustainability, and cross-functional teamwork.
- ii. **Digital and Sustainable Curriculum:** Benchmarking studies and industry interviews emphasise the urgent need to modernise maritime curricula, infusing digital skills, sustainability, and operational flexibility as core program outcomes.
- iii. **Accreditation and Benchmarking:** International institutions stress regular benchmarking and curriculum updates in line with emerging technologies (blockchain, AI, automation), professional certifications, and regulatory changes (IMO standards, port safety codes, trade and environmental law).

IMU's BBA-ML program, by integrating apprenticeships, regulatory compliance, and international curricular collaborations, is demonstrably closer to emerging global expectations than many non-specialist Indian BBA programs.

V. DISCUSSION

The comparative analysis clearly demonstrates that domain specialisation, industry integration, and experiential learning constitute the defining advantages of IMU's BBA in Maritime Logistics over the UGC/AICTE model BBA. The IMU program not only provides technical and legal proficiency aligned with current and future sectoral demands but also leverages strong university-industry linkages, mandatory apprenticeships, and global academic partnerships to optimise student employability. Graduates of the BBA-ML program are better prepared for immediate entry into mid-skill and managerial roles in logistics and shipping, and they face fewer entry barriers due to the program's built-in compliance with international regulatory standards.

In contrast, the generalist UGC BBA offers broad employability, flexibility, and a platform for further specialisation, but at the cost of immediate sectoral role-readiness and technical depth unless students proactively pursue relevant electives, certifications, and practical experience. This difference is particularly crucial in labour market segments where employers expect job-ready recruits and high regulatory compliance, as in maritime logistics.

However, the generalist route's flexibility remains advantageous for students seeking diverse career trajectories, including entrepreneurship or sectors outside logistics, and for those uncertain about their long-term specialisation at the undergraduate stage.

Both curricula would benefit from continued calibration against global standards and greater mutual integration of digital literacy, sustainability, and cross-industry transferable skills within their respective domains.

VI. RECOMMENDATIONS

1. **For Policymakers and Regulators:**
 - i. Encourage sectoral partnerships and the co-creation of curriculum between universities, industry councils, and regulatory authorities in all professional BBA streams.
 - ii. Mandate or incentivise universal apprenticeships and sector-specific experiential modules across undergraduate management programs.
2. **For General BBA Providers (UGC/AICTE Model Curriculum):**
 - i. I. Integrate logistics and supply chain electives earlier in the curriculum, emphasising real-world problems, tools, and compliance.
 - ii. Strengthen the apprenticeship and industry mentorship system, especially in non-top-tier colleges, using models inspired by IMU and international standards.
 - iii. Foster digital literacy, sustainability, and regulatory compliance as core skills for all business majors, regardless of specialisation.
3. **For IMU and Maritime Logistics Programs:**
 - i. Continue benchmarking against international best practices, integrating new modules into big data analytics, AI, and sustainable maritime practices.
 - ii. Expand collaboration with global port authorities, shipping majors, and logistics tech innovators for live projects and capstone internships.
4. **For Students and Aspirants:**
 - i. Choose programs not only for their brand value but for their alignment with your long-term career vision and the depth of exposure to industry practices.

- ii. Seek certifications (STCW, ECDIS, ISM/ISPS, etc.) and robust internships to supplement both general and specialist curriculum exposure.

5. For Employers:

- i. Partner with academic institutions for pre-placement tie-ups, co-designed apprenticeships, and continuous curriculum feedback to ensure graduates meet evolving sectoral needs.

In sum, the future of business education in India lies in judiciously blending foundational management education with deep, practice-driven, compliance-oriented skill development exemplified by leading domain-specialist programs. This is the surest way to ensure that graduates are not only employable but also poised to lead in the future digital, globally networked business landscape.

VII. CONCLUSION

The transition of Indian business education from a generalist paradigm to sector-specialised, professionally aligned models is both necessary and overdue, especially in logistics and allied domains central to the country's economic aspirations. This research has shown that while generalist BBA degrees offer diverse career options and are conceptually robust, domain-specific programs such as IMU's BBA-ML provide superior preparation for logistics and shipping careers due to rigorous, regulatory-compliant curricula, integrated experiential learning, and strong alignment with industry demand.

As logistics, shipping, and supply chain sectors evolve, educational institutions must proactively iterate their curricula, pedagogical strategies, and industry collaborations to prepare graduates who can navigate digital disruptions, regulatory complexity, and global trade challenges with confidence and adaptability.

REFERENCES

1. All India Council for Technical Education. (2024). *Model curriculum for UG degree in Bachelor's in Business Administration (BBA), BBA (Honours), and BBA (Honours with Research)*. https://www.aicte.gov.in/sites/default/files/Model_Curriculum/BBA%20Final.pdf
2. Tolani Maritime Institute. (n.d.). *BBA Maritime Logistics*. <https://tmi.tolani.edu/academics/bbamaritime-logistics/>
3. MBAUniverse.com News Desk. (2024, April 27). *AICTE BBA Model Curriculum: AICTE Chairman - 4,200 BBA Institutions have applied for approval*. <https://www.mbauniverse.com/articles/aicte-bba-model-curriculum>
4. Indian Maritime University. (n.d.). *BBA Maritime Logistics (Apprenticeship embedded)*. <https://www.imu.edu.in/imunew/courseprograms?course=7>
5. Petrina, S. (2022). *Methods of analysis: curriculum analysis*. University of British Columbia. <https://blogs.ubc.ca/researchmethods/files/2022/04/Curriculum-Analysis.pdf>
6. Indian Maritime University. (2022). *Annexure 3 – BBA (LRE) syllabus*. https://imu.edu.in/imunew/uploads/files/BBA%28LRE%29_Syllabus_2022.pdf
7. Vels Institute of Science, Technology & Advanced Studies. (2024). *BBA Maritime Logistics syllabus regulation*. <https://vistas.ac.in/wp-content/uploads/naac/01/BBAMARITIME-LOGISTICS-SYLLABUS-REGULATION-2024.pdf>
8. CollegeDekho. (2025). *IMU placements: Highest & average package, top recruiters*. <https://www.collegedekho.com/colleges/indian-maritime-university-placement>
9. Careers360. (2025). *Top 10 career options after BBA (high-paying & in-demand)*. <https://bschool.careers360.com/articles/top-10-career-options-after-bba>
10. ICFAI University. (2024). *BBA syllabus AY 2024–25*. <https://www.iuu.ac/pdf/ugc/BBA%20Syllabus%20AY%202024-25.pdf>
11. Shiksha. (2025). *BBA syllabus 2025: Subjects list, semester-wise syllabus PDF*. <https://www.shiksha.com/bba-bachelor-of-business-administration-subjects-chp>
12. Shiksha. (n.d.). *IMU Vizag – BBA in Maritime Logistics (Apprenticeship embedded)*. <https://www.shiksha.com/university/imu-imuvizag-indian-maritime-university-visakhapatnam-51901/course-apprenticeship-embeddedbba-in-maritime-logistics-984423>
13. Collegedunia. (2025). *Top AICTE-approved BBA/BMS colleges in India – Rankings, fees*. <https://collegedunia.com/bba/aicte-approved-colleges>
14. Maritime News. (n.d.). *Indian Maritime University empowers global maritime collaboration*. <https://maritimeneeds.in/indian-maritime-university-empowers-global-maritime-collaboration/>
15. Manonmaniam Sundaranar University. (n.d.). *BBA II Year DJB2A: Principles of Management*



- syllabus*.
<https://www.msuniv.ac.in/images/distance%20education/learning%20materials/ug%20pg/ug/bba/II%20Year%%20DJB2A%20-%20Principles%20Of%20Management.pdf>
16. CHRIST (Deemed to be University). (2021). *Semester I BBA syllabus*.
https://christuniversity.in/uploads/course/bbah_syllabus_2021_20210310021904.pdf
 17. Lee, J., & Kim, H. (2023). Essential competencies in maritime and port logistics: A study on the Indian context. *Sustainability*, 17(6), 2378.
<https://www.mdpi.com/2071-1050/17/6/2378>
 18. BBA Project. (2025). *Top career options after BBA in 2025 to kickstart a thriving career*.
<https://bbaproject.in/careeroptions-after-bba/>
 19. Indian Maritime University. (n.d.). *MOU & collaborations*.
<https://www.imu.edu.in/imunew/moucollaborations>
 20. Rishihood University. (2025). *Top 20 job opportunities after BBA in 2025*.
<https://rishihood.edu.in/top-20-job-opportunitiesafter-bba-in-2025/>
 21. Ship Universe. (n.d.). *The 30 most in-demand maritime certifications*.
<https://www.shipuniverse.com/the-30-most-in-demand-maritime-certifications>

GREEN FINANCE AND THE SUSTAINABLE DEVELOPMENT GOALS

Krati Jain

PhD scholar, India Institute of Management, Raipur

kratij.cfa@gmail.com

Abstract—Green Finance is instrumental in achieving the objective of SDGs that consider green growth. Green Finance is essential for financing green and renewable energy projects. Banks, institutional investors, international financial institutions, central banks, and regulatory authorities play a key role in Green Finance. Green Finance plays a vital role in agriculture, energy systems, education, health, technology and urban planning.

Keywords—economic sustainability, environmental sustainability

I. INTRODUCTION

The first usage of 'Green finance' (GF) appeared in literature in 1997, and its first academic definition appeared in 2011 [1]. GF is also referred to as 'climate finance', 'environmental finance', 'green investment', and 'sustainable finance' [2]. GF focuses on the stable development of economic activities and the ecological environment, thereby achieving sustainable social development [3]. GF is associated with financial products, services, and investments that support environmentally sustainable projects and initiatives [4]. GF follows ESG principles [5]. Researchers have been studying the areas of GF and sustainable development in response to the serious challenges caused by climate change and environmental degradation [6]. According to the International Finance Corporation's The Basic Green Finance Reference Guide (2020), GF is "the finance that follows either the Green Bond Principles or the Green Loan Principles." GF is instrumental in achieving the SDGs that prioritise green growth [7]. Some of the significant studies on GF are summarised in Table 1.

TABLE 1. SUMMARY OF A GF STUDIES

Author(s)	Study Domain
Zaman et al., (2026) Technology-society nexus in post-COP 27 era: How digital innovation, energy	Investigation of the relationship between energy transition, GF, digital innovation, and carbon emissions in 37 OECD countries.

transition, and green finance drive net-zero pathways in OECD countries. <i>Energy Policy</i> .	
Alvi et al., (2025) The role of green finance, energy transition, and digitalisation in OECD greenhouse gas emissions.	Effects of green finance, digitisation and environmental patents, the energy transition and renewable energy consumption, and urbanisation and trade openness on ecological sustainability.
van Niekerk (2024) Economic Inclusion: Green Finance and the SDGs. <i>Sustainability</i> .	Green banks, green bonds, green growth, green investments, green loans, green technologies.
Trukhachev, V. I., & Dzhikiya, M. (2023). Development of environmental economy and management in the age of AI-based green finance. <i>Frontiers in Environmental Science</i> .	Economic and mathematical modelling of GF to SDG 2, SDG 3, SDG 6, SDG 7, SDG 11, SDG 12, SDG 13, SDG 14, SDG 15.
Sadiq et al., (2023) The role of green finance, eco-innovation, and creativity in the sustainable development goals of ASEAN countries. <i>Economic Research-Ekonomska Istraživanja</i> .	Association between renewable energy production and SDGs. Association between renewable energy production and carbon emissions.
Alharbi et al., (2023) Green finance and renewable energy: A worldwide evidence. <i>Energy Economics</i> .	Role of GF in renewable energy generation and the production function of renewable energy.
Nouredine (2022) Green Finance and the Sustainable Development Goals: A Review of Some International Experiences. <i>Journal of Economics and Sustainable Development</i> .	Relation of GF to green investment, climate finance, sustainable finance, green finance products and services (green bonds, green labelled loans, green investment funds, climate risk insurance, green stocks), Islamic products for green financing (green and blended finance, green sukuk). Successful experiences of France, Germany, Brazil, the UK and China in the field of GF.

Khan et al., (2022) Does green finance really deliver what is expected? An empirical perspective. <i>Borsa Istanbul Review</i> .	Impact of climate mitigation finance, per capita gross domestic product, total population, trade openness and energy consumption on ecological footprint.
Desalegn & Tangl, 2022	Scope of GF: carbon finance, climate finance, green bond, green credit, green fund.
Debrah et al., 2022 Green finance gap in green buildings: A scoping review and future research needs. <i>Building and Environment</i> .	GF and green buildings.
Akomea-Frimpong et al., (2021)	Identification of green finance products: carbon finance, climate finance, green bancassurance, green infrastructural finance, green loan (credit), green long-term investment account, green traded stocks and bonds.
Bhattacharyya (2021) Green finance for energy transition, climate action and sustainable development: overview of concepts, applications, implementation and challenges. <i>Green Finance</i> .	Adaptation finance, carbon finance, climate finance, environmental finance, ESG investing, impact investing, green finance, microfinance schemes, ocean finance, sustainable finance, transition finance; carbon border adjustment mechanisms, carbon contract for differences, carbon credits and cap-and-trade arrangements, carbon emissions trading, carbon price/tax, carbon offsets; historical development of GF concepts (1969-2021);
Ziolo et al., (2021)	Link between sustainable finance models (sustainable finance model 1.0, sustainable finance model 2.0, sustainable finance model 3.0) and SDGs (SDGs 1, 2, 3, 4, 5, 7, 8, 9, 10, 11, 12, 13, 15, 16, 17).
Lagoarde-Segot (2020) Financing the Sustainable Development Goals. <i>Sustainability</i> .	Mathematical examination of Loanable Fund Theory and the Post-Keynesian Endogenous Theory of Money. Sovereign Green Bond and SDG finance gap.
Hafner et al. (2020) Closing the green finance gap – A systems perspective: environmental <i>Innovation and Societal Transitions</i> .	Identification of hurdles that obstruct green investments and potential policy interventions to scale up such investments.

Taghizadeh-Hesary & Yoshino (2019)	Reducing the risks linked with green investments by the utilisation of technological features of Distributed Ledger Technologies.
Clark et al., (2018)	Identification of key barriers (information gaps, short-termism, undervaluation of natural capital, dependency on voluntary commitments without recourse and byelaws) to private investment and recommendations for surmounting the obstacles.
Ehlers & Packer (2017) Green bond finance and certification. <i>BIS Quarterly Review</i> .	Features of different green bond identification and certification schemes.
Pham (2016) A volatility analysis of the green bond market. <i>Journal of Sustainable Finance & Investment</i> .	Distinction between green bonds and conventional bonds. Green bond principles. Labelled green bond and unlabeled green bond. Modelling of the volatility behaviour of the green bond market.
Criscuolo & Menon (2015) Environmental policies and risk finance in the green sector: Cross-country evidence. <i>Energy Policy</i> .	Examination of policy determinants of venture capital financing in the green sector across 29 countries for the 2005-2010 time span.

Significant financing is required to realize the UN SDGs [8]. A few studies related to GF and SDGs are summarized in Table 2.

TABLE 2. GF AND SDGS

SD G No	SDG	Author(s)	Contribution of GF to SDG
1	No Poverty	Desalegn & Tangl (2022)	Promotion of green products within credit, insurance, money transfers, new digital delivery channels and savings.
2	Zero Hunger	Trukhachev & Dzhikiya (2023)	Linkage between SDG 2 Score and policy and strategy.
3	Good Health and Well-Being	Raman et al., (2025)	The role of climate finance in reducing pollution and supporting clean energy initiatives.

4	Quality Education	Raman et al., (2025) Innovations and barriers in green and sustainable finance for advancing the Sustainable Development Goals. <i>Frontiers in Environmental Science.</i>	The role of education in empowering individuals and societies towards embracing greener practices.
5	Gender Equality	Chen F-H (2024)	Financial knowledge and women's empowerment, gender diversity and adoption of Environmental Management Systems, green entrepreneurship and women's empowerment.
6	Clean Water and Sanitation	Noureddine (2022)	Investment in infrastructure.
7	Affordable and Clean Energy	van Niekerk (2024)	GF and renewable energy projects.
8	Decent Work and Economic Growth	van Niekerk (2024) Economic Inclusion: Green Finance and the SDGs. <i>Sustainability.</i>	GF and sustainable economic growth.
9	Industry, Innovation and Infrastructure	van Niekerk (2024)	GF and green technologies.
10	Reduced Inequalities	Simionescu & Gavurová (2023)	The nexus between pollution and income inequality in the context of GF.
11	Sustainable Cities and Communities	van Niekerk (2024) Economic Inclusion: Green Finance and the SDGs. <i>Sustainability.</i>	GF and eco-friendly urban development.
12	Responsible Consumption and Production	van Niekerk (2024) Economic Inclusion: Green Finance	GF and distributed manufacturing and regenerative consumption.

		and the SDGs. <i>Sustainability.</i>	
13	Climate Action	van Niekerk (2024) Economic Inclusion: Green Finance and the SDGs. <i>Sustainability.</i>	GF and carbon emissions.
14	Life Below Water	van Niekerk (2024) Economic Inclusion: Green Finance and the SDGs. <i>Sustainability.</i>	GF and sustainable fisheries.
15	Life on Land	van Niekerk (2024) Economic Inclusion: Green Finance and the SDGs. <i>Sustainability.</i>	GF and sustainable land management.
16	Peace, Justice and Strong Institutions	Afzal et al. (2022)	Need for combining strong institutions with GF to lower, or eliminate, long-run effects on the environment.
17	Partnerships for the Goals	van Niekerk (2024) Economic Inclusion: Green Finance and the SDGs. <i>Sustainability.</i>	GF and communitarian networking.

II. OBJECTIVES

There is an inverse relationship between economic sustainability and environmental sustainability [9]. Regional GDP growth is associated with increased environmental pollution, according to the environmental Kuznets curve [10]. GF is a key driver of ecological protection and sustainable development [11]. Sustainable development encompasses corporate economic plans, government policies, and measures for conserving natural resources [12]. Financing is imperative for achieving the SDGs [13]. GF can be an enabler of human progress.

Research Question

RQ1. What is the scope of GF?

III. METHODOLOGY

The review papers were retrieved from Scopus, Clarivate, Google Scholar and ScienceDirect. Articles were chosen for their contribution to GF. The articles

were analyzed to identify key findings, themes, and trends regarding GF. The findings of this study contribute to the GF, SDGs, and ESG (environmental, social, and governance) frameworks. They may provide insights for investors, policymakers, and researchers working in the domain of GF.

IV. RESULTS AND DISCUSSION

The Research Question

GF is essential for financing green and renewable energy projects [14]. Several funds, such as the Clean Development Mechanism, the Global Environment Facility, the Green Climate Fund, and the World Bank BioCarbon Fund, have been established to support climate action, conservation, and sustainable development [15]. The article by Fu et al. (2023) discusses the Green Climate Fund (GCF), green bonds, sustainable spending, sustainable investments, the impact of environmental policy on R&D investment, the impact of government expenditure on green economic performance, the impact of corporate green bonds on environmental performance, the impact of CSR disclosure on GF, the link between supply chain collaboration and GF, climate change hedge portfolios, the effect of GF on low-carbon energy, sustainable development and the link between oil price, trade and GF. Using a sample of 46 countries (data collected from the SDC Platinum database), Mamun et al. (2022) [16] ascertained that green bond financing plays a crucial role in decarbonizing the global economy.

The Equator Principles (Table 3) serve as guiding principles for financial institutions to identify, assess, and manage environmental and social risks associated with project financing.

TABLE 3. THE EQUATOR PRINCIPLES

Principle #	Principle
1	Review and Categorisation. Categorisation of projects into Category A, Category B and Category C.
2	Environmental and Social Assessment.
3	Applicable Environmental and Social Standards.
4	Environmental and Social Management System and Equator Principles Action Plan.
5	Stakeholder Engagement.
6	Grievance Mechanism.
7	Independent Review.
8	Covenants.
9	Independent Monitoring and Reporting.
10	Reporting and Transparency.

Principles 7, 8, and 9 (Table 4) of the Ten Principles of the UN Global Compact pertain to the environment.

TABLE 4. PRINCIPLES 7, 8 AND 9 OF THE UN GLOBAL COMPACT

Principle #	Principle
7	"Businesses should support a precautionary approach to environmental challenges"
8	"undertake initiatives to promote greater environmental responsibility"
9	"encourage the development and diffusion of environmentally friendly technologies"

Banks, institutional investors, international financial institutions, central banks, and regulatory authorities play a key role in GF. GF plays an essential role in agriculture, energy systems, education, health, technology and urban planning. The growth of Green Bond Issuances, Green Debt Securities issued in India, and Green credit guarantee schemes are related to GF: most green bonds fund clean transport projects, energy efficiency, and renewable energy [17]. GF can be classified into: carbon markets and credits, green bonds, green insurance, green loans and sustainable investment funds.

V. PRACTICAL IMPLICATIONS

Impact of GF

GF is related to commercial FIs, corporations, FDI, philanthropy, bilateral DFI, multilateral DFI, public-sector undertakings, and government (union and state) budgets. Green investments require substantial initial capital and yield returns over the long term [11].

VI. CONCLUSIONS

Managers need to respond to environmental, financial and social challenges which organizations are facing today. GF can be used for facing the challenges and creating value. GF is related to environment friendly investments, investors' confidence, lenders' confidence, economic growth, green energy, renewable energy development and climate-related financial policies. Identification and removal of financial, legal and regulatory barriers can help in advancing GF concept.

REFERENCES

- Afzal, A., Rasoulinezhad, E., & Malik, Z. (2022). Green finance and sustainable development in Europe. *Economic Research-Ekonomika Istraživanja*. 35(1). 5150-5163. doi: 10.1080/1331677X.2021.2024081

- [1] Dhayal, K. S., Shashwat, S., Giri, A. K. (2025). Conceptualising green finance: Findings from textual and network analysis. *Heliyon*. 11(4). doi: 10.1016/j.heliyon.2025.e42785
- [2] Akomea-Frimpong, I., Adebah, D., Ofosu, D., & Tenakwah, E. J. (2021). A review of studies on green finance of banks, research gaps and future directions. *Journal of Sustainable Finance & Investment*. doi: 10.1080/20430795.2020.1870202
- [3] Wang, K-H., Zhao, Y-X., Jiang, C-F., & Li, Z-Z. (2022). Does green finance inspire sustainable development? Evidence from a global perspective. *Economic Analysis and Policy*. 75. 412-426. doi: 10.1016/j.eap.2022.06.002
- [4] Simionescu, M., & Gavurová, B. (2023). Pollution, income inequality, and green finance in the new EU member states. *Humanities & Social Sciences Communications*. 10. 677. doi: 10.1057/s41599-023-02197-6
- [5] Chen, F-H. (2024). Green finance and gender equality: Keys to achieving sustainable development. *Green Finance*. 6(4). 585-611. doi: 10.3934/GF.2024022
- [6] Fu, C., Lu, L., & Pirabi, M. (2023). Advancing green finance: a review of sustainable development. *Digital Economy and Sustainable Development*. 1:20. doi: 10.1007/s44265-023-00020-3
- [7] Desalegn, G., & Tangl, A. (2022). Enhancing Green Finance for Inclusive Green Growth: A Systematic Approach. *Sustainability*. 14. 7416. doi: 10.3390/su14127416
- [8] Rizzello, A., & Kabli, A. (2020). Social Finance and Sustainable Development Goals: A Literature Synthesis, Current Approaches and Research Agenda. *ACRN Journal of Finance and Risk Perspectives*. 9. 120-136. doi: 10.35944/jofrp.2020.9.1.010
- [9] Ronaldo, R., & Suryanto, T. (2022). Green finance and sustainability development goals in the Indonesian Fund Village. *Resources Policy*. 78. 102839. doi: 10.1016/j.resourpol.2022.102839
- [10] Udeagha, M. C., & Muchapondwa, E. (2023). Striving for the United Nations (UN) sustainable development goals (SDGs) in BRICS economies: The role of green finance, fintech, and natural resource rent. *Sustainable Development*. 31. 3657-3672. doi: 10.1002/sd.2618
- [11] Chin, M-Y., Ong, S-L., Ooi, D. B-Y., & Pua, C-H. (2022). The impact of green finance on environmental degradation in the BRI region. *Environment, Development and Sustainability*. doi: 10.1007/s10668-022-02709-5
- [12] Hunjra, A. I., Hassan, M. K., Zaid, Y. B., Managi, S. (2023). Nexus between green finance, environmental degradation, and sustainable development: Evidence from developing countries. *Resources Policy*. 81. 103371. doi: 10.1016/j.resourpol.2023.103371
- [13] Ziolo, M., Bak, I., & Cheba, K. (2021). The Role of Sustainable Finance in Achieving Sustainable Development Goals: Does it Work?. *Technological and Economic Development of the Economy*. 27(1). 45-70. doi: 10.3846/tede.2020.13863
- [14] Taghizadeh-Hesary, F., & Yoshino, N. (2019). The way to induce private participation in green finance and investment. *Finance Research Letters*. 31. 98-103. doi: 10.1016/j.frl.2019.04.016
- [15] Clark, R., Reed, J., & Sunderland, T. (2018). Bridging funding gaps for climate and sustainable development: Pitfalls, progress and potential of private finance. *Land Use Policy*. 71. 335-346. doi: 10.1016/j.landusepol.2017.12.013
- [16] Mamun, M. A., Boubaker, S., & Nguyen, D. K. (2022). Green finance and decarbonization: Evidence from around the world. *Finance Research Letters*. 46 (Part B). 102807. doi: 10.1016/j.frl.2022.102807
- [17] Löffler, K. U., Petreski, A., & Stephan, A. (2021). Drivers of green bond issuance and new evidence on the "greenium". *Eurasian Economic Review*. 11. 1-24. doi: 10.1007/s40822-020-00165-y



MARKET RESEARCH IS CRITICAL FOR FRAMING CONTEMPORARY BUSINESS STRATEGY

Dr. Dewali Chatterjee
Sr. Assistant Professor
Maritime Management
E mail-dewali.c@tmi.tolani.edu

Abstract— Market research can be treated as a critical catalyst in modern business operations. By conducting proper market research, businesses can gain insights into consumer's needs and behaviour, stay competitive, make informed decisions, manage risk, and measure success.

This research paper states the importance, methods, and challenges of market research, providing a detailed explanation & the role in strategic decision-making. Economy is changing platform where consumer's reaction and purchasing pattern also differ time to time. With a focus on both qualitative and quantitative approaches, the paper highlights the growing influence of technology in market research, providing valuable information for organizations looking to remain competitive in an ever-changing business landscape.

Keywords: Market Research, Consumer Behavior, Strategic decision making.

I. INTRODUCTION

Business is one of the pillars of development. It has been progressed from self-sufficiency stage to modern technological premises. Business environment has its own distinctive features. This dynamic economic environment brings competitive business vibes. The companies are demanding more information and data to understand the need & choice of customers for framing smooth strategic decision. One of the most powerful tools available to businesses for informed decision-making is market research. Market research enables businesses to identify consumer taste & preferences [1], evaluate market conditions, and forecast future trends. The role of market research has evolved significantly over time, from simple surveys and interviews to more complex data-driven methodologies. This paper has tried to point out the importance of market research, its methodologies, the challenges faced by business houses and its evolving role in modern business strategies. By examining the evolution of market research and analyzing the business challenges & opportunities, this paper will offer insights into how businesses can leverage research findings to drive competitive advantages and inform strategic decision-making.

II. LITERATURE REVIEW

Market research as a tool that provides insights into customer behaviors, preferences, and unmet needs, enabling organizations to adapt to changing market conditions [2]. There is an understanding market dynamics through research is particularly important in sectors where new product development is key to competitive advantage, as it helps predict consumer responses to innovation [1].

Market research broader definition emphasizes stressing that market research encompasses a wide range of methods and techniques, including both qualitative and quantitative research, to gather and analyze data. Market research is not only concerned with assessing consumer preferences, but it also extends to understanding the competitive landscape [2] [3], identifying market trends, and forecasting future developments. This broader scope of market research helps businesses make better decisions about product development, marketing strategies, and pricing, ensuring alignment with consumer expectations.

III. ROLE OF MARKET RESEARCH

Market research can also play an important role in the process of developing the products and services, bringing them to the marketplace, and marketing them to consumers. Here are a few ways that market research can help for framing business strategy:

- i. It can give us an accurate view of business and the marketplace.
- ii. It can help us to determine who are the customers are, and which customers are most likely to do transact with the business.
- iii. It can reveal how customers and prospects view the existing business and products.
- iv. It can help you decide whether a new idea for a business or product will fly – that is, if customers will find it appealing – based on how similar products have performed in the marketplace.
- v. It can help us make wise product packaging and promotional decisions, as well as effective marketing messages.

The primary importance of market research lies in its ability to reduce uncertainty. By providing accurate and timely information, market research enables companies to make well-informed decisions, whether it's launching a new product, expanding into new markets, or revising marketing strategies

Additionally, market research promotes business customer relationships. Through research, companies can better understand their customers' pain points, taste & preferences, and expectations, enabling them to create more personalized and targeted marketing campaigns [3][4]. This alignment with customer needs fosters loyalty, strengthens brand reputation, and drives customer retention.

III. MARKET RESEARCH PROCESS

The first step in the research process is defining the problem. This stage is vital, as it determines the direction for the entire research effort.

A distinctive idea helps to justify the concise & core problem address by the help of market research. Once the problem is defined, the next step is designing the research methodology, which involves identifying the qualitative and quantitative techniques, as well as determining the research instruments, sample size, and data collection methods [3]. After data collection, the research team analyses the findings using statistical tools and techniques. This stage involves interpreting the data to draw meaningful conclusions and insights. The final step is presenting the research findings in a way that is clear, actionable, goal oriented and relevant to decision-makers. This may involve writing detailed reports, creating visualizations, or conducting presentations to share insights with key stakeholders. Basically, the market research process involves several key steps that guide researchers from identifying the problem to analyzing and reporting the results.

IV. METHODOLOGIES OF MARKET RESEARCH

Market research methodologies can be broadly categorized into qualitative and quantitative research, both different purposes and offering with unique features. Qualitative research, as explained by Malhotra (2009), is primarily focused on understanding consumer motivations, attitudes, and behaviors. Techniques such as focus groups, in-depth interviews, and ethnographic studies allow researchers to procure resourceful detailed insights into the underlying reasons behind consumer taste & preferences [3]. This method helps business to explore the socio- psychological factors associated of consumer that cannot be possible to estimate by numerical data.

On the other hand, quantitative research is focused on collecting numerical data that can be statistically analyzed. Common methods of quantitative research include surveys, experiments, and observational studies. These approaches are used to quantify consumer behaviour, measure attitudes, and track changes in preferences over time. Quantitative data can be analyses to identify patterns and correlations, helping businesses make data-driven decisions based on a broader sample size. The quantitative research provides the statistical backbone for market research, offering clear and measurable insights that can be used for segmentation, market forecasting, and performance analysis [2]. While qualitative research helps understand the "why" behind consumer actions, quantitative research answers the "what" and "how much." The integration of both approaches, often referred to as mixed-methods research, allows businesses to gather a holistic view of the market and make more comprehensive decisions [3]. By combining the strengths of both methods, companies can create research strategies that address both the emotional and rational aspects of consumer behaviour.

V. CHALLENGES IN MARKET RESEARCH

Despite its importance, market research faces several challenges that can hinder its effectiveness. One major challenge is the ever-changing nature of consumer behaviour. Study reveals that consumer's taste & preferences can shift frequently, making it difficult to forecast future trends with certainty. The advancement of digital technologies and social media has further accelerated these drastic changes, making it difficult for businesses to ascertain a proper framework. Another challenge is the complexity of human behaviour. Traditional market research techniques often struggle to capture the full range of consumer motivations, beliefs, and preferences. For example, factors such as cultural influences, social pressures, and psychological biases can significantly impact consumer decision-making but may not always be reflected in survey responses or focus group discussions [5]. Consumer research study emphasizes the need for more advanced techniques, such as behavioral data analysis and sentiment analysis, to uncover the deeper drivers of consumer behaviour. Data quality is another significant concern in market research. Inaccurate or incomplete data can lead to erroneous conclusions and misguided business decisions. Researchers must ensure that data collection methods are reliable and that sample sizes are large enough to provide statistically significant results. Additionally, ensuring that respondents provide honest and accurate feedback is a common challenge in consumer research, particularly when dealing with self-reported data.

VI. INNOVATION IN BUILDS IN MARKET RESEARCH

Market research plays an essential role in fostering innovation within organizations. By providing insights into consumer taste & preferences, market research helps businesses identify gaps in the market and unexplored opportunities for new product development. Different studies highlight the role of market research in the development of innovative products, market research inclines to test new ideas, validate concepts, and refine product designs before launching them to the market. However, the role of market research in innovation is not always straightforward. The traditional market research methods may not always be suitable for evaluating radical or discontinuous innovations, as consumers may have difficulty articulating their needs for products that do not yet exist [1]. This is particularly true for disruptive innovations that challenge established norms and create entirely new markets [6]. In these cases, companies must balance market research with creativity and vision, relying on intuition and visionary thinking to drive product development.

VII. ETHICAL CONSIDERATIONS IN MARKET RESEARCH

Ethical considerations are crucial in ensuring the integrity and credibility of market research. Researchers must adhere to ethical guidelines that protect the rights of participants and ensure that research findings are accurate and unbiased. Informed consent means that participants must be fully aware



of the purpose of the research and how their data will be used. Researchers must also ensure that participants' identities and responses are kept confidential, particularly when dealing with sensitive information [7]. Additionally, researchers must avoid any form of deception or manipulation in their data collection methods. By maintaining high ethical standards, researchers can build trust with consumers and ensure that their findings are reliable and valid.

VIII. FUTURE TRENDS IN MARKET RESEARCH

The future of market research is being shaped by technological advancements and new methodologies. One of the most significant developments in recent years has been the advancement of big data analytics, which allows companies to process and analyze vast amounts of consumer data in real time. It is noted that big data offers businesses the ability to track consumer behavior across multiple platforms, providing deeper insights into consumer taste & preferences [2]. Furthermore, the integration of artificial intelligence (AI) and machine learning into market research is transforming how businesses collect and interpret data. AI-powered tools can identify patterns and correlations that would be difficult for humans to detect, enabling businesses to make more accurate predictions about market trends and consumer behavior [8]. Additionally, machine learning algorithms can continuously improve over time, making them more effective at analyzing.

The future of market research will also see a greater emphasis on understanding the customer journey as a whole, rather than focusing solely on individual touchpoints. Malhotra (2009) discusses the shift toward experience-based research, which takes into account the entire customer experience, from initial awareness to post-purchase evaluation [3]. This holistic approach will allow businesses to create more personalized and engaging experiences for their customers.

IX. CONCLUSION

Market research is a fundamental aspect of business strategy that enables organizations to understand consumer behaviour, identify market opportunities, and stay competitive in a rapidly changing environment. By employing both qualitative and quantitative research methods, businesses can gather valuable insights that inform decision-making and drive innovation. While challenges such as evolving consumer behaviour, data quality, and ethical concerns persist, advancements in technology and data analytics offer new opportunities for businesses to enhance their research efforts. As market research continues to evolve, companies must embrace new tools and methodologies to stay ahead in an increasingly complex and data-driven world.

REFERENCES

- [1] Trott, P. (2001). The Role of Market Research in the Development of Discontinuous New Products. *European Journal of Innovation Management*.
- [2] Bradley, N. (2007). *Marketing. Research: Tools & Techniques*. 2nd ed. Oxford University Press.
- [3] Malhotra, N. K. (2009). *Marketing Research: An Applied Orientation*. 6th ed. Pearson Prentice Hall.
- [4] Sahu, P., & Patnaik, A. - Understanding the Basics of Market Research, *Journal of Market Research*, 15 (2023) 45-59. doi.org/10.1016/j.jmr.2023.01.009.
- [5] Gupta, S., & Shukla, S. - Applications of Market Research in Consumer Behaviour, *International Journal of Business and Marketing*, 21 (2022) 203-212. doi.org/10.1016/j.ijbm.2022.03.005.
- [6] Mishra, A., & Verma, R. - Exploring the Impact of Digital Tools on Market Research, *Journal of Business Analytics*, 10 (2021) 98-107. doi.org/10.1016/j.jba.2021.07.016.
- [7] Patel, K., & Singh, J. - The Role of Qualitative Research in Market Strategy, *Market Trends Journal*, 14 (2020) 34-48. doi.org/10.1016/j.mtj.2020.12.012.
- [8] Kotler, P., & Armstrong, G. - *Principles of Marketing Research*, Prentice Hall, New Jersey (2018).

Data-Driven Water Quality Assessment Using Machine Learning and Water Quality Index

Sahadev M. Jadhav

Department of Space Engineering, Ajeenkya D Y Patil University, Pune
sahadevjadhav@gmail.com

Abstract— Water quality degradation has emerged as a critical concern in India due to increasing pollution levels, rapid urbanisation, and climate variability. Conventional water quality monitoring techniques primarily rely on manual sampling and laboratory analysis, making them time-consuming, resource-intensive, and unsuitable for real-time assessment. Moreover, existing approaches suffer from limited scalability, responsiveness, and adaptability. This study proposes an optimised machine learning framework, termed the Optimised Stacked Ensemble-based Water Quality Index (OSE-WQI), to enhance water quality evaluation. The proposed system employs ensemble regression models to estimate missing water quality parameters, followed by the computation of a comprehensive Water Quality Index (WQI) to assess overall quality. Subsequently, a stacked ensemble classifier is used to categorise water quality levels. Experimental validation using real-world data collected from the Ganga River in the Varanasi region demonstrates superior performance, achieving a classification accuracy of 95.81%. The proposed framework outperforms conventional machine learning models, including Support Vector Machines, K-Nearest Neighbours, Random Forests, and Neural Networks, in both regression and classification tasks. The results indicate that the proposed approach is well-suited to applications in environmental monitoring, public health assessment, and policy formulation in India.

Keywords—Environmental Monitoring, Water Quality, Machine Learning, Stacked Blending, Classification, Regression, WQI.

I. INTRODUCTION

Water is fundamental to sustaining ecosystems, agriculture, industrial activities, and human health. However, increasing anthropogenic activities have significantly deteriorated freshwater resources worldwide. Although freshwater constitutes approximately 2.5% of the Earth's total water, only about 1% is readily accessible for human use. Industrial effluents, agricultural runoff, and untreated urban wastewater have collectively intensified water pollution, necessitating continuous monitoring of water quality.

The Ganga River, particularly in the Varanasi region, is among the most polluted river stretches in India. Given its immense cultural, social, and economic significance, reliable and continuous monitoring of water quality is essential. Traditional manual assessment methods are not only labour-intensive but also prone to human error and delays. These challenges have driven researchers toward artificial intelligence (AI) and machine learning (ML)-based data-driven solutions.

Machine learning techniques enable automated analysis of large-scale datasets, prediction of missing values, and near real-time classification of water quality levels. As illustrated in Fig. 1, ML models can efficiently analyse multiple physicochemical parameters and categorise

water quality into meaningful classes, thereby enhancing decision-making processes.




Fig. 1: General Overview of the Water Quality Index model

Figure 1 presents a detailed depiction of the water Quality Index (WQI) modelling pipeline developed in this study for evaluating river water quality using machine learning methods. The procedure commences with the acquisition of water-sample data from diverse sites, followed by preprocessing to address missing or inconsistent values. Regression models are subsequently used to predict missing water quality metrics from inter-parameter correlations. The comprehensive datasets—consisting of both observed and projected values—are used to calculate the WQI, a composite metric indicative of overall water quality. This indicator is subsequently employed to classify water quality into established categories. The annotated dataset subsequently serves as input to an ensemble classification framework that automates the classification process. The ensemble comprises base classifiers (KNN, SVM, RF, and NN), whose outputs are aggregated by a meta-classifier to produce final predictions. This comprehensive, phased methodology guarantees enhanced precision, resilience, and scalability in real-time water quality evaluation, implemented explicitly for the Ganga River in the Varanasi area.

This paper details recent advances in water quality evaluation through a comprehensive literature review, emphasizing the limitations and opportunities that informed the development of the proposed framework. The methodology section delineates the whole OSE-WQI model, encompassing data



preparation, regression-based forecasting, WQI calculation, and the development of a stacked ensemble classifier. The following section assesses the model's performance using empirical data from the Ganga River, examining both regression and classification results. The practical application of the system for real-time environmental monitoring is reviewed, concluding with a summary of significant contributions and a delineation of future research directions to improve the model's scalability and adaptability.

II. LITERATURE REVIEW

In recent years, various methods for tracking water quality have evolved significantly, particularly through the use of machine learning (ML). One of the most essential factors examined in these studies is the Water Quality Index (WQI). It enables in-depth evaluations based on physicochemical parameters, including Biological Oxygen Demand (BOD), Chemical Oxygen Demand (COD), pH, and Total Dissolved Solids (TDS). Even though people often employ standard WQI approaches, they usually have problems with weighting parameters in a way that isn't objective, dealing with missing or noisy data, and making generalisations across different geographic areas.

Much research has sought to address these challenges through various approaches. For example, P. Sudarshan et al. examined TDS, DO, Nitrate, BOD, and hardness to assess the water quality of Hebbal Lake, India [1]. This study showed that some regions were contaminated, but it couldn't be applied elsewhere. In this paper [2], the authors used a deep learning-based Bi-LSTM model to assess the cleanliness of the water in the Ganga River. They demonstrated that applying optimised loss functions improved prediction accuracy. In this work, the authors sought to achieve the same by combining ensemble classification with Relief feature selection [3]. This improved classification accuracy but also made the model harder to interpret.

This paper builds on this work by suggesting a fuzzy logic-based wQI method that uses triangular and trapezoidal membership functions to deal with uncertainty in water quality measures. On the other hand, the fuzzy method relies on an expert who understands the subject well and may be difficult to interpret [4]. In this paper, the authors developed a system that employs artificial neural networks (ANNs) to determine the current water quality. This shows that it is feasible to monitor the surroundings without people present. However, the ANN method requires substantial processing power and depends heavily on the quality of the training data [5].

In 2024, Kirui examined how machine learning could help us learn more about the water's condition. With decision trees, XG Boost, and Bi-LSTM, they were able to guess the WQI with an accuracy of roughly 96%. This paper also used explainable AI (XAI) and ensemble models, such as Gradient Boosting, Random Forest, and XGBoost, to

improve the accuracy of WQI predictions. The investigation showed that Gradient Boosting was the most accurate, achieving 96% accuracy [6].

In this paper, the authors examined how outliers affected the Irish Environmental Water Quality Index (IEWQI) model to ensure data reliability. Their results showed that robust frameworks are needed to operate with imperfect data. This combined approach is practical, but you need to know a lot about both machine learning and fluid simulation to use it [7]. The data were analyzed using a range of regression and classification methods, including Random Forest, XGBoost, AdaBoost, and Gradient Boosting, to identify the optimal algorithm for predicting the Water Quality Index (WQI) and Water Quality Category (WQC). The top model achieved an R^2 score of 99.8% [8].

This paper describes a model that employs support vector machines and tree-based classifiers to assess water quality in real time. They made it evident that it could be used to help manage the environment. Although the arithmetic was complex, their investigation showed that ensemble techniques can aid in sifting water [9].

In this paper, the authors employed machine learning to analyse water samples from Ayodhya, India, with a focus on groundwater contamination. Their work focused on how ML may be used to identify and remediate groundwater pollution; it was conducted only in a specific area [10]. Finally, the researcher developed attention-based CNN-LSTM models that improved the accuracy of multi-parameter water quality data by employing spatial and temporal attention mechanisms to focus on key factors [11].

These combined efforts demonstrate how water quality assessment systems are shifting away from traditional WQI methodologies toward data-driven, ML-enabled solutions. Although these methods differ, they share the same goals: improving prediction accuracy and reliability, handling missing or outlier data effectively, and enabling real-time decision-making. This paper builds on these ideas by proposing the WQI model, an optimized stacked ensemble classifier that combines KNN, SVM, Neural Networks, and Random Forests with a meta-classifier to produce the final prediction. This method not only addresses problems identified in previous studies but also establishes a new standard for classifying and predicting water quality, achieving over 95% classification accuracy and improved forecasting metrics (RMSE and MAPE) across a variety of water parameters.

We identify several research gaps in current methods for assessing water quality. Traditional WQI models are complex to adapt and struggle with missing or incomplete data, reducing prediction accuracy. Most prior research does not use forecasting to identify missing factors, which makes WQI less reliable. Additionally, integrated frameworks for

classifying water have not fully exploited ensemble learning. There aren't many region-specific models that use localised datasets, especially for contaminated rivers like India's Ganga.

III. METHODOLOGY

The proposed framework for water quality assessment along the Ganga River comprises four essential stages, as shown in Fig. 2.




Fig. 2: Architecture of Proposed WQI Model

A. Data Collection and Preprocessing

In this stage, we first collect data from the Central Pollution Control Board (CPCB), obtaining a total of 6598 samples from various monitoring stations. These data include physicochemical and biological attributes, such as Biochemical Oxygen Demand (BOD), pH, Dissolved Oxygen (DO), Conductivity (CND), coliforms, and Total Dissolved Solids (TDS). Data preprocessing was applied to remove outliers, normalise parameter scales, handle missing values to improve data reliability and readiness, and prepare the dataset for machine learning analysis.

B. Parameter Forecasting

This stage addresses incomplete or missing values in the dataset. Various regression algorithms were employed, namely Random Forest (RF), K-Nearest Neighbours (KNN), Neural Networks (NN), and Support Vector Machine (SVM). This methodology was used to evaluate unknown attribute values and to increase the dataset's completeness. Performance metrics used include Root Mean Squared Error (RMSE), Accuracy, precision, recall, and F-score to evaluate the regression models' accuracy. In subsequent computations, this step ensures that predictions are statistically usable and reliable.

C. WQI Calculation (Water Quality Index)

In this phase, we calculate the Water Quality Index (WQI), a composite metric. It condenses complex multi-parameter WQD into a single numerical score. It facilitated more comprehensive and consistent interpretation across timeframes and locations.

The evaluation process began by converting each attribute into a sub-index using established quality rating curves derived from environmental standards (e.g., CPCB, WHO, or BIS guidelines).

Every attribute was assigned a weight (W_i) based on its impact on aquatic life and public health. For example, Dissolved Oxygen and BOD were given higher weights due to their importance in calculating the biological integrity of water. The quality rating (Q_i) for individual attributes was calculated and combined using a weighted arithmetic formula:

$$(1)$$

D. Stacked Ensemble Classification

In this phase, the overall water quality level is predicted using an ensemble learning methodology. First, we trained multiple base learners as SVM, RF, KNN, and NN independently on the dataset. To produce the final classification result, their outputs were fed into a meta-classifier, which synthesised the predictions. This stacked model leverages the significance of several models, enhancing overall robustness and accuracy. For environmental monitoring and policy decision-making, this model ensures that the final water quality label reflects consensus across diverse perspectives, thereby improving system reliability.

IV. REGRESSION PERFORMANCE ANALYSIS

Regression plays a key role in estimating missing water parameters, particularly in scenarios where sensors fail or data are missing. The ensemble regression model performed best across all metrics:

- BOD RMSE: 0.5143
- COD RMSE: 0.6242
- R-value (BOD): 0.9887

Compared with standalone repressors, the ensemble model minimised error and improved generalisation.

V. PERFORMANCE EVALUATION

The water Quality Index (WQI) values were divided into three different classes representing water quality levels to assess the effectiveness of the proposed framework, as shown in Table I:

TABLE 1. WQI RANGE FOR DIFFERENT CLASSES

Class	WQI Range	Water Quality Status
Class 1	24–49	Good
Class 2	50–74	Moderate
Class 3	75–100	Poor

To predict these classes, a **stacked ensemble classifier** was applied using water quality attributes and calculated WQI

values. This model integrates multiple base learners (KNN, SVM, RF, and NN) and uses a meta-classifier for final predictions. The ensemble learning technique improved classification performance by leveraging the strengths of all individual classifiers.

B. Performance Metrics

The performance of the stacked model was evaluated using The standard classification metrics are given below in Table II:

TABLE 2. PERFORMANCE VALUES OF PROPOSED WQI MODEL

Metric	Value
Accuracy	95.83%
Precision	91.66%
Recall	92.31%
F1-Score	92.05%

These results indicate that the stacked model achieves high predictive precision and recall, as well as strong overall generalisation. When we compared this approach with individual classifiers (e.g., SVM, KNN), the stacked ensemble demonstrated the best performance across all metrics, thereby confirming its reliability and robustness for environmental categorisation tasks.

Confusion Matrix

This matrix provides deeper insight into the model's predictions by comparing the real labels with the predicted class labels. For the classification task, there are three hypothetical classes of confusion matrix given below in Table III:

TABLE 3. CONFUSION MATRIX

Actual \ Predicted	Class 1 (Good)	Class 2 (Moderate)	Class 3 (Poor)
Class 1 (Good)	163	6	2
Class 2 (Moderate)	5	151	7
Class 3 (Poor)	3	8	152

The stacked ensemble classifier was better than all the other models when it came to classifying, with an accuracy rate of 95.83%. It achieves balanced precision (91.66%), recall (92.31%), and F1-score (92.05%), indicating consistent performance across all WQI-based water quality classes. This suggests that the model can be used in real-world water quality monitoring systems, where accurate decision-making and environmental management depend on precise categorisation.

VI. APPLICATIONS OF WQI

The optimised Score-Based Water Quality Index (OSB WQI) is a valuable instrument that simplifies complex water quality data by providing a single score. People in authority, stakeholders, and decision-makers can readily identify and

address water-quality problems as a result. We can utilize it in many different ways:

A. Urban Planning

The optimized Score-Based Water Quality Index (WQI) is beneficial for city planning, as it indicates to municipal officials where water pollution is a problem. People can use this information to determine how to manage waste, construct new roads and buildings, and establish zoning regulations. It helps planners use resources wisely and ensure that urban growth doesn't put people's health and safety, or the safety of water, at risk.

B. Agriculture

The WQI is highly useful in agriculture for preventing the use of contaminated water in crop irrigation. Poor-quality water can damage crops, degrade soil health, and introduce harmful substances into the food supply. Farmers and agricultural officials can use the index to monitor water resources and ensure that farming is conducted in an environmentally sustainable manner. This will help them save crops.

C. Industrial monitoring

In industry monitoring, the indicator helps identify companies and factories that are emitting pollutants abnormally. Regulatory organisations can monitor enterprises that contravene environmental regulations and ensure compliance with wastewater regulations. It also helps identify sources of pollution, thereby facilitating targeted enforcement actions.

D. Public health

From a public health perspective, the WQI is an early-warning indicator for detecting unsafe drinking water. Finding Sources of contamination immediately limit the spread of diseases that cause watery stools, such as cholera, dysentery, and typhoid. This information can help officials warn people, provide clean water, and take other measures to keep people healthy.

E. To figure out the Water Quality Index

when you connect WQI to IoT devices, you can gather and Real-time data monitoring is much more helpful. Sensors can continuously report water quality data, enabling the triggering of alerts and predictive analysis. This smart link helps water resources managers make decisions more quickly and effectively.

VII. CONCLUSION AND FUTURE DIRECTIONS

This paper describes WQI, a comprehensive machine learning system that can independently assess the quality of river water. It is highly accurate and reliable, as it uses regression to impute missing data and a stacked ensemble classification method to determine quality. The Water Quality Index (WQI) is a valuable tool because it considers both observed and expected values. This means that datasets that don't have all the information can nevertheless be valuable. When used in an optimised ensemble, classifiers such as KNN, SVM, RF, and more than one classifier are used in more than one place. Adding new environmental elements to judgments about policy. It might be preferable in the future if used on its own. We tested the algorithm on real data from the Ganga River in Varanasi, achieving an accuracy of 95.83% in predicting outcomes. These results demonstrate that it has significant potential for real-world applications in environmental monitoring and for integrating IoT devices into the model to obtain real-time data.

ACKNOWLEDGMENT

I gratefully acknowledge the contributions of all participants who agreed to participate and provided their data. It has only been through such cooperation that the present study could be completed, as the findings could be confirmed only through this effort.

I want to extend my heartfelt gratitude to my institution, whose resources, infrastructure, and academic environment have provided a strong foundation for this research. I am particularly thankful to the esteemed faculty members and my peers for their insightful discussions, constructive suggestions, and continuous encouragement. Their valuable perspectives have significantly contributed to the refinement of various aspects of this work.

REFERENCES

- [1] P. Sudarshan, M. K. Mahesh, and T. V. Ramachandra, "Assessment of seasonal variation in water quality and water quality index (WQI) of Hebbal Lake, Bangalore, India," *Environ. Ecol.*, vol. 37, no. 1B, pp. 309–317, 2019.
- [2] S. Khullar and N. Singh, "Water quality assessment of a river using deep learning Bi-LSTM methodology: forecasting and validation," *Environ. Sci. Pollut. Res.*, vol. 29, no. 9, pp. 12875–12889, 2022a.
- [3] S. Khullar and N. Singh, "River water quality classification using a hybrid machine learning technique," in *Proc. 9th Int. Conf. on Computing for Sustainable Global Development (INDIACom)*, 2022b, pp. 808–813.
- [4] J. G. Nayak, L. G. Patil, and V. K. Patki, "Development of water quality index for Godavari River (India) based on fuzzy inference system," *Groundw. Sustainable Dev.*, vol. 10, p. 100350, 2020.
- [5] N. N. M. Rizal, G. Hayder, and K. A. Yusof, "Water quality

predictive analytics using an artificial neural network with a graphical user interface," *Water*, vol. 14, no. 8, p. 1221, 2022.

- [6] J. Kirui, "Machine learning models for drinking water quality classification," in *Proc. Int. Conf. on Control, Automation and Diagnosis (ICCAD)*, 2024, pp. 1–5.
- [7] N. N. Jha, "Computational machine learning analytics for prediction of water quality," *Commun. Appl. Nonlinear Anal.*, vol. 31, no. 4s, pp. 448–465, 2024.
- [8] P. Dandekar, V. Thakre, K. Sharma, and A. Kushwaha, "A predictive model for water quality index assessment by machine learning approach," in *Proc. 2nd Int. Conf. on Computer, Communication and Control (IC4)*, 2024, pp. 1–6.
- [9] K. S. P. Mishra, P. K. Patel, and A. Singh, "Water quality assessment and modelling using machine learning," 2024.
- [10] W. F. Alfwezan, M. M. Selim, A. S. Almalki, and I. S. Alharbi, "water quality assessment using Bi-LSTM and computational fluid dynamics (CFD) techniques," *Alexandria Engineering Journal*, vol. 97, pp. 346–359, 2024.

MUNICIPAL SOLID WASTE DRYER: TURNING INDIA'S WET WASTE INTO HIGH QUALITY RDF FUEL

Aditya Gupta
Tolani Maritime Institute
Pune, India
aditya.gupta2024me@gmail.com

Abstract: India generates more than 160,000 tonnes of municipal solid waste per day, much of which contains high moisture content ranging from 45–60%. This severely lowers its net calorific value, making the waste unsuitable for use as refuse-derived fuel in cement kilns and waste-to-energy facilities. Traditional centralized processing plants fail due to inconsistent feed quality and high operating costs. This paper proposes a Municipal Solid Waste Dryer, a decentralized, low-cost thermal drying system that utilizes waste heat from nearby industries to reduce moisture levels. Using controlled forced-air convection, the dryer can bring moisture down from ~55% to <20%, increasing from ~1000 kcal/kg to ~2500 kcal/kg. The paper discusses system architecture, theoretical heat transfer principles, design equations, sample calculations, feasibility, and expected outcomes. The goal is to present a technically feasible, scalable solution to India's municipal solid waste moisture problem without relying on high-energy mechanical dryers.

Keywords: Municipal Solid Waste, Net Calorific Value, Refuse-Derived Fuel, Hybrid Dryer System, Waste Heat Recovery

Nomenclature:

h_{fg} = Latent heat of vaporization of water
 m_w = Initial water
 m_{final} = Final wet mass
 m_{wf} = Final water mass
 Δm_w = Water removed after drying
 Q_{latent} = Latent energy ideal
 $Q_{practical}$ = Latent energy practical
 E_{10TPD} = Energy for A 10 Tpd (Tonnes Per Day) Module
 MSW - Municipal Solid Waste
 WtE - Waste to Energy
 NCV - Net calorific Value
 RDF - Reuse Derived Fuel

I. INTRODUCTION

India faces a growing MSW management crisis. Urban municipalities are burdened by:

- Unsegregated waste streams
- High moisture content
- Low calorific value
- Insufficient treatment infrastructure
- Most thermochemical conversion methods—incineration, gasification, RDF co-processing—depend on adequately dry waste. However, Indian waste is typically wet, with food

waste constituting 40–60% of the municipal stream [1].

NCV is the actual energy available from burning waste. For effective power generation, MSW should ideally have NCV > 1700 kcal/kg. Below that, waste doesn't sustain combustion and needs auxiliary fuel (like diesel or coal), making projects unviable.

This moisture drastically reduces NCV, causing repeated failures of WtE plants (e.g., Delhi, Pune, Hyderabad) [9]. High-moisture waste leads to:

- Poor combustion efficiency
- High auxiliary fuel consumption
- Excess emissions
- Operational instability

Therefore, pre-drying MSW is critical. This paper introduces a decentralized waste-heat-based dryer, designed to operate near industrial clusters where waste heat is abundantly available.

II. PROPOSED SOLUTION

2.1 Municipal Solid Waste (MSW) Dryer

It is a portable, compact, container-sized drying unit that removes excess moisture from municipal waste before it is sent for processing.

An MSW Dryer system uses hybrid drying:

- **Solar thermal collectors** - rooftop solar thermal or photovoltaic-driven air heaters which will supply low-grade heat to incoming air in daytime. Even a small thermal rise of air by 10–20°C reduces auxiliary energy dramatically [3].
- **Forced-air circulation for faster drying** - pushes warm air (solar-heated or waste-heat ducted) through waste.
- **Waste heat recovery ducts from nearby industries** - Instead of using fresh fuel/electricity to heat the air for drying, the Dryer captures low-grade heat (40–150 °C) that is normally thrown away from nearby facilities. That heat is then used to pre-heat the airflow [8]. Typical sources include: Diesel generator exhausts (common in markets, apartments, hospitals), Crematoria & small industrial

boilers, brick kilns, small foundries, etc. Waste heat sources such as brick kilns, foundries, boilers, food processing units often release temperatures between 120–250°C into the atmosphere.

Main ways to transfer the waste heat:

- Indirect air-to-air heat exchange (warm air ducting)
- Hot-water loop (water as heat carrier)
- Thermal oil loop (higher temp, longer reach)

And also, shorter the distance, simpler is the ducting, which results in lower losses and lower cost.

2.2 System Architecture

The dryer consists of:

1. Heat Collection Duct – captures hot air from chimneys/exhaust.
2. Blower Unit – pushes hot air into the chamber at controlled velocity.
3. Drying Chamber – stainless steel or MS structure with perforated trays.
4. Air Recirculation System – improves heat utilization.
5. Filtration System – activated carbon filter + cyclone separator.

RDF Output Section – conveyor or manual removal.

The figure below provides with basic structure of the Dryer.




Fig 1 A basic structure of the MSW Dryer

2.3 Working Principle

- Hot air from an industrial waste heat source is ducted to the dryer.
- A blower forces the heated air through waste layers.
- Moisture evaporates through heat transfer and airflow.
- Humid air exits through controlled vents and filters.
- Dried waste is discharged as RDF feedstock.

The figure below provides with the flow process of the Dryer.




Fig 2 Flowchart representing the process

2.4 Case Studies Related to Waste Heat Usage

1. Power Plants near Delhi & Maharashtra: NTPC Dadri (UP) and Koradi Thermal Plant (Nagpur) already use dump heat to dry high-moisture coal. If coal (which has similar moisture issues as MSW) can be dried by waste heat, MSW can too [4].
2. Brick Kilns in Uttar Pradesh & Bihar : Traditional brick kilns release huge amount of waste heat (>200 °C) from flue gases. Some kilns are drying raw bricks using flue gas ducts. In the same way this heat can be insulated through ducts into



the MSD dryer to dry municipal waste [5 - 6].

3. Sugar Mills & Bagasse Drying:

Sugar mills in Maharashtra use flue gases from boilers to dry bagasse before reusing it as boiler fuel. Bagasse has around 50% moisture, almost same as MSW. Hence same drying approach can be applied [7].

We are not inventing heat transfer, industries already use waste heat to dry coal, bagasse, and bricks. Our innovation is applying the same proven principle to municipal waste, closing a crucial gap in India's waste-to-energy ecosystem.

2.5 Novelty

What makes this solution unique is that no such modular, decentralized dryer for MSW currently exists in the Indian market. Existing systems are large, centralized, and energy-hungry.

While this system is:

- Decentralized & Modular - installed at ward-level in compact units.
- Hybrid Energy Use - Combines multiple low-cost heat sources (solar and industrial waste heat)
- Containerized modular design for easy deployment
- Integrated IoT monitoring for moisture levels
- Lower energy use compared to electric dryers.

2.6 Marine Applications of MSW Dryer

An MSW Dryer has strong relevance in the marine industry, where space, hygiene, and environmental compliance are critical. It can significantly improve shipboard waste management by reducing waste moisture, volume, and odours, helping vessels meet MARPOL Annex V requirements. Offshore platforms also benefit from reduced storage needs and safer handling of waste during long deployment cycles. In ports and harbours, MSW dryers enhance waste-processing efficiency, improve calorific value before RDF production, and support cleaner "Smart Port" operations. Additionally, coastal and island cities use dryers as pre-treatment for waste-to-energy systems, while fish-processing industries near ports rely on drying to stabilize highly wet organic waste. Cruise terminals and shipyards also gain advantages in odour control, volume reduction, and improved environmental performance. Overall, integrating an MSW Dryer into marine sector operations enhances sustainability, reduces

logistical burdens, and aligns with modern maritime waste-management standards.

2.7 Energy Conversions (Sample Calculations)

Assumptions

- Inlet MSW moisture = 55% (wet basis).
- Target outlet moisture = 20%.
- Latent heat of vaporization of water $h_{fg} = 2257 \text{ kJ/kg} = 0.627 \text{ kWh/kg}$.
- Practical heat multiplier (losses) = 1.6 (typical design margin).
- Solar insolation (average usable) $\approx 5 \text{ kWh/m}^2/\text{day}$ (India average).
- Solar collector thermal efficiency (typical flat-plate/air) $\approx 50\%$, useful $\approx 2.5 \text{ kWh/m}^2/\text{day}$.
- Continuous operation over 24 hrs is assumed for waste-heat; solar provides daytime energy only (we count daily totals).

Step 1: Water To Remove Per Tonne Of MSW

Raw mass = 1000 kg.

Initial water = 55% $\rightarrow m_{wi} = 550 \text{ kg}$.

Solids = 450 kg.

We want the MSW to have 20% moisture after drying.

Let the final wet mass be m_{final}

Moisture content definition:

Moisture fraction = water mass / total wet mass

Thus, solids fraction = $1 - 0.20 = 0.80$

Solids remain unchanged during drying, so:

$m_{final} = \text{solids} / 0.80 = 450 / 0.8 = 562.5 \text{ kg}$

The final water mass (m_{wf}) is:

$m_{wf} = m_{final} - \text{solids} = 562.5 - 450 = 112.5 \text{ kg}$

Water removed after drying:

$\Delta m_w = m_{wi} - m_{wf} = 550 - 112.5 = 437.5 \text{ kg}$

Step 2: Thermal Energy to Evaporate That Water (Ideal & Practical)

Latent energy (ideal):

$Q_{latent} = \Delta m_w \times h_{fg} = 437.5 \times 0.627 \approx 274.3 \text{ kWh/tonne}$

Apply practical multiplier (1.6):

$Q_{practical} \approx 274.3 \times 1.6 \approx 439 \text{ kWh/tonne}$

(So we'll use $\approx 439 \text{ kWh/tonne}$ as the working figure.)

Step 3: Energy For A 10 Tpd (Tonnes Per Day) Module

Daily energy need:

$E_{10TPD} = 10 \times 43 = 4,390 \text{ kWh/day}$

Continuous thermal power:

$P = 4390 / 24 \approx 83 \text{ kW}$ (thermal continuous)

Step 4: What A Waste Heat Source Provides

Example 1 — 200 kW continuous waste heat

Daily = $200 \times 24 = 4,800 \text{ kWh/day}$.

Tons supported $\approx 4800 / 439 \approx 10.9 \text{ TPD}$.

Example 2 — 150 kW continuous

Daily = $150 \times 24 = 3600$ kWh/day.

Tons supported $\approx 3600/439 \approx 8.2$ TPD.

Example 3 — 100 kW continuous

Daily = 2400 kWh/day $\Rightarrow 2400/439 \approx 5.5$ TPD.

Findings: A 100–200 kW continuous waste-heat source maps to ~ 5 –11 TPD capacity (matching a modular sized dryer).

Step 5: Solar Thermal Contribution (Daily Total)

Useful solar thermal per m^2 (assumption): 2.5 kWh/ m^2 /day.

Solar area needed to supply the whole 10-TPD requirement alone:

Area = $4390/2.5 \approx 1,756$ m^2

(That's large — solar alone is usually impractical for full load, but excellent as supplement.)

Solar area per tonne:

Area/ton = $439/2.5 \approx 176$ m^2 /ton

Step 6: Realistic Combined Scenarios (Waste Heat and Solar Heat)

When normally combined, here are example mixes:

Scenario 1 — 150 kW waste heat + 500 m^2 solar

- Waste heat daily: $150 \times 24 = 3,600$ kWh.
- Solar daily: $500 \times 2.5 = 1,250$ kWh.
- Combined = $3,600 + 1,250 = 4,850$ kWh/day.
- Requirement for 10 TPD = $4,390$ kWh/day $\rightarrow$ surplus margin.
- Outcome: comfortably supports 10 TPD with headroom.

Scenario 2 — 100 kW waste heat + 300 m^2 solar

- Waste heat: $100 \times 24 = 2,400$ kWh.
- Solar: $300 \times 2.5 = 750$ kWh.
- Combined = $3,150$ kWh/day
- supports $3150/439 \approx 7.2$ TPD.
- Outcome: ~ 7 TPD capacity — still useful for smaller wards.

Scenario 3 — 200 kW waste heat + 200 m^2 solar

- Waste heat: $4,800$ kWh/day. Solar: 500 kWh/day.
- Combined = $5,300$ kWh/day
- supports $5300/439 \approx 12.1$ TPD.
- Outcome: supports ~ 12 TPD; good safety margin.

2.8 Feasibility:

- Per-ton thermal need ≈ 439 kWh ($55 \rightarrow 20\%$ moisture).
- Waste heat: small industrial sources in many Indian clusters routinely release 100–300 kW available to capture — enough for 5–15 TPD depending on size.
- Solar thermal: provides useful daytime energy (~ 2.5 kWh/ m^2 /day) — large area needed to cover full load but excellent as support.
- Combined: moderate waste heat (100–200 kW) + moderate solar area (200–500 m^2)

reliably meets a 10 TPD dryer's daily demand with reasonable buffers.

- So energy-wise the concept is feasible

2.9 Expected Outcome:

2.9.1 Moisture % vs Dring Time (Hours):




Fig. 3 Drying Time vs Moisture %

2.9.2 Temperature profile inside Dryer:




Fig. 4 Temperature Profile Inside Dryer

TABLE 1: COMPARISON BETWEEN BEFORE DRYING AND AFTER DRYING

Parameter	Before Drying	After Drying
Moisture	50-60%	15-20%
NCV	800-1000 kcal/kg	2300-2800 kcal/kg
Weight	100%	60-70%
Odor	High	Very low
Transport	High	Reduced by 30-40%



2.10 Competitors / Alternatives & How Is MSW Dryer Better:

- Large-Scale Waste-to-Energy (WtE) Plants – e.g., Jindal ITF, Ramky Enviro. They are centralized, require a heavy capital and also provides low efficiency. WtE fails on wet, low-NCV waste. MSW Dryer pre-dries waste locally, ensuring WtE plants get high-calorific feedstock. Also MSW Dryer is more efficient, requires less capital, and decentralized while being compared to Large scale WtE.
- Composting & Biomethanation Units – small decentralized plants for organic waste. It works well for pure wet/food waste, but cannot handle mixed MSW with plastics. The Dryer handles mixed MSW (wet + plastics).
- Imported Mechanical Dryers (European/Japanese models) – large rotary dryers used in cement plants. They are very costly, have a high power demand, and are not modular or designed for Indian mixed MSW.

2.11 Market Size

Buyers will include Municipal corporations (4,000+ ULBs across India), Waste management companies (e.g., Ramky, Jindal, Essel, private contractors), Cement plants (250+ across India) and Waste-to-Energy plants.

Market Size Estimate in India:

- India generates around 160,000 TPD of MSW, of which around 80,000 TPD is wet and low-NCV [1].
- Even if 10% of this waste (8,000 TPD) is targeted, it needs 800–1,000 modular dryers (at 10 TPD capacity each).

At an estimated ₹40–60 lakh per unit, this is a ₹4,000–6,000 crores potential domestic market.

III. CONCLUSIONS

This study demonstrates that integrating waste-heat recovery and solar thermal energy offers a practical

and energy-efficient method for drying Municipal Solid Waste (MSW) before processing. By utilizing

heat that would otherwise be lost from small industries and supplementing it with solar collectors, the system significantly reduces the energy demand traditionally associated with MSW drying.

Overall, the proposed model presents a low-cost, scalable, and sustainable solution for decentralized waste processing. It minimizes fuel consumption, lowers emissions, and increases the calorific value of processed waste—creating a strong technological foundation for further development, prototyping, and practical deployment.

The Dryer increases the calorific value of the waste by 1500 – 1800 kcal/kg, by reducing the moisture upto 35-40%. It decreases the weight of the waste by 30-40%, and hence also reduces the transport cost by 30-40%.

IV. REFERENCES

- [1] Ministry of Housing and Urban Affairs (MoHUA), "Municipal Solid Waste Management Manual," Government of India, 2016.
- [2] Central Pollution Control Board (CPCB), "Status Report on Municipal Solid Waste Management in India," 2022.
- [3] A. Sharma et al., "Performance of Solar Thermal Collectors for Low-Temperature Applications," *Solar Energy*, vol. 182, pp. 133–148, 2019.
- [4] Central Electricity Authority (CEA), Ministry of Power, "Technical Standards for Coal Handling Plants," 2018.
- [5] TERI (The Energy and Resources Institute), "Improved Brick Kiln Technologies for Energy Efficiency," 2018.
- [6] M. B. Singh, "Energy Utilization in Brick Kilns and Flue-Gas Drying Techniques," *Energy for Sustainable Development*, vol. 45, pp. 97–103, 2018.
- [7] S. Kulkarni and P. G. Sharma, "Drying of Bagasse Using Waste Heat from Sugar Mill Boilers," *Journal of Thermal Engineering*, vol. 6, no. 4, pp. 55–63, 2020.
- [8] TERI (The Energy and Resources Institute), "Industrial Waste Heat Recovery in India," 2019.
- [9] J. K. Sinha and P. R. Chakrabarti, "Why Waste-to-Energy Projects Fail in India," *Energy Policy*, vol. 128, pp. 709–718, 2019.



APPLICATION FORM FOR SUBSCRIPTION TO TMI's JMFAR

I/We would like to subscribe/ Renew the subscription to 'Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research'.

The following particulars are furnished for your information and records:

Name of the Individual/ Establishment:

.....

Register/Permanent Address:

.....

.....

City:.....

State:.....

Telephone No:..... Mobile No :

Fax:.....

.....

Email :

.....

Website:.....

.....

Address for correspondence :

Name : Designation :

Address:.....

Subscription to Tolani Maritime Institute's Journal of Maritime Fundamentals and Applied Research

Yours Sincerely

Signature and Seal



TOLANI MARITIME INSTITUTE

Talegaon – Chakan Road, Induri, Pune – 410507, Maharashtra, India



ATTITUDE



SKILL



KNOWLEDGE



jmfar@tmi.tolani.edu



<https://tmi.tolani.edu>